

4500962913

**XINGHAN**

冠县众冠新材料有限公司

GUANXIAN ZHONGGUAN NEW MATERIALS CO., LTD.

地址：中国山东聊城冠县新世纪工业园

Address:Guan Xian industry Park,Liaocheng,Shandong,China

产品质量证明书  
MILL'S TEST CERTIFICATE

订货单位 CUSTOMER		CUMIC STEEL LIMITED								钢号	GR.37					产品名称 PRODUCT		GALVALUME STEEL CORRUGATED SHEETS	
收货单位 PURCHASER		CUMIC STEEL LIMITED									签发日期 DATE OF ISSUE		2024.11.20						
标准 SPECIFICATION		ASTM A792M									合同号 CONTRACT NO.		ZG202408134488						
捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size (mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分 (%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION (%)					力学性能 MECHANIC PROPERTIES				
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>el</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB	
629	0.972	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	660	665	3	92	
630	0.968	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	665	665	4	93	
632	0.975	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	660	670	3	92	
633	0.975	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	102	0.032	0.21	0.009	0.009	0.04	660	670	3	93	
634	0.977	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	655	665	4	92	
636	0.969	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	109	0.035	0.26	0.008	0.009	0.04	660	670	3	93	
637	0.971	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	104	0.03	0.22	0.008	0.008	0.04	665	665	4	92	
638	0.97	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	660	665	3	92	
639	0.968	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	105	0.032	0.22	0.008	0.009	0.04	665	665	4	93	
640	0.971	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	107	0.033	0.23	0.008	0.009	0.04	660	670	3	92	
641	0.964	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93	
643	0.975	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	103	0.032	0.21	0.009	0.009	0.04	655	665	4	92	
644	0.985	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	660	665	3	92	
645	0.972	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	106	0.035	0.26	0.008	0.009	0.04	665	665	4	93	
647	0.976	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	660	670	3	92	
648	0.97	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	102	0.033	0.23	0.008	0.009	0.04	660	665	3	92	
649	0.965	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	107	0.035	0.26	0.008	0.009	0.04	665	665	4	93	
652	0.976	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	109	0.032	0.22	0.008	0.009	0.04	660	670	3	92	
653	0.971	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	104	0.033	0.23	0.008	0.009	0.04	660	670	3	93	
656	0.969	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.21	0.009	0.009	0.04	655	665	4	92	
657	0.966	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	105	0.031	0.25	0.007	0.01	0.04	660	670	3	93	
659	0.973	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	107	0.035	0.26	0.008	0.009	0.04	665	665	4	92	
660	0.972	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	104	0.03	0.22	0.008	0.008	0.04	660	665	3	92	
661	0.97	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	103	0.032	0.22	0.008	0.009	0.04	665	665	4	93	



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size (mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>el</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB
663	0.969	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	660	670	3	92
664	0.969	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	106	0.033	0.23	0.008	0.009	0.04	660	670	3	93
665	0.973	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	108	0.032	0.21	0.009	0.009	0.04	655	665	4	92
666	0.977	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	102	0.032	0.21	0.009	0.009	0.04	660	665	3	92
668	0.97	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	665	665	4	93
669	0.97	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	109	0.035	0.26	0.008	0.009	0.04	660	670	3	92
671	0.965	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	660	665	3	92
672	0.967	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	106	0.033	0.23	0.008	0.009	0.04	665	665	4	93
673	0.975	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	105	0.032	0.21	0.009	0.009	0.04	660	670	3	92
674	0.975	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	660	670	3	93
675	0.97	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	655	665	4	92
676	0.975	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	103	0.03	0.22	0.008	0.008	0.04	660	670	3	93
677	0.981	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	92
679	0.967	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	660	665	3	92
680	0.971	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	665	665	4	93
681	0.969	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	102	0.032	0.21	0.009	0.009	0.04	660	670	3	92
682	0.973	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	670	3	93
683	0.96	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	655	665	4	92
684	0.974	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	660	665	3	92
685	0.968	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	665	665	4	93
687	0.968	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	105	0.033	0.23	0.008	0.009	0.04	660	670	3	92
688	0.977	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
690	0.982	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	665	665	4	93
691	0.969	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	103	0.035	0.26	0.008	0.009	0.04	660	670	3	92
693	0.97	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	104	0.03	0.22	0.008	0.008	0.04	660	670	3	93
694	0.98	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	655	665	4	92
695	0.98	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	660	670	3	93
696	0.981	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	102	0.033	0.23	0.008	0.009	0.04	665	665	4	92
700	0.977	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
702	0.973	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	665	665	4	93
703	0.97	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	660	670	3	92
704	0.981	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	106	0.033	0.23	0.008	0.009	0.04	660	670	3	93
705	0.968	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	105	0.032	0.21	0.009	0.009	0.04	655	665	4	92
706	0.975	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	660	665	3	92
707	0.974	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	665	665	4	93
708	0.969	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	103	0.032	0.22	0.008	0.009	0.04	660	670	3	92
709	0.974	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	104	0.033	0.23	0.008	0.009	0.04	660	665	3	92




捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size (mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分 (%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION (%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	$R_{cl}$ (N/mm <sup>2</sup> )	$R_m$ (N/mm <sup>2</sup> )	A (%)	HRB
710	0.974	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	106	0.035	0.26	0.008	0.009	0.04	665	665	4	93
711	0.97	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	660	670	3	92
712	0.982	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	102	0.033	0.23	0.008	0.009	0.04	660	670	3	93
713	0.976	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	655	665	4	92
714	0.974	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	660	670	3	93
715	0.974	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	665	665	4	92
716	0.977	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	106	0.03	0.22	0.008	0.008	0.04	660	665	3	92
717	0.971	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	105	0.032	0.22	0.008	0.009	0.04	665	665	4	93
718	0.973	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.22	0.008	0.009	0.04	660	670	3	92
719	0.968	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	104	0.033	0.23	0.008	0.009	0.04	660	670	3	93
720	0.977	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	103	0.035	0.26	0.008	0.009	0.04	655	665	4	92
721	0.975	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	660	665	3	92
722	0.979	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	106	0.033	0.23	0.008	0.009	0.04	665	665	4	93
723	0.971	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	108	0.032	0.21	0.009	0.009	0.04	660	670	3	92
724	0.972	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	102	0.031	0.25	0.007	0.01	0.04	660	665	3	92
726	0.97	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	107	0.035	0.26	0.008	0.009	0.04	665	665	4	93
727	0.97	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	109	0.03	0.22	0.008	0.008	0.04	660	670	3	92
728	0.974	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	660	670	3	93
729	0.971	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	655	665	4	92
730	0.983	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	105	0.033	0.23	0.008	0.009	0.04	660	670	3	93
731	0.974	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	665	665	4	92
732	0.974	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	665	3	92
733	0.973	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	103	0.031	0.25	0.007	0.01	0.04	665	665	4	93
734	0.973	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	660	670	3	92
735	0.973	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	660	670	3	93
736	0.971	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	655	665	4	92
737	0.981	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	102	0.035	0.26	0.008	0.009	0.04	660	665	3	92
738	0.973	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.22	0.008	0.009	0.04	665	665	4	93
739	0.97	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	109	0.033	0.23	0.008	0.009	0.04	660	670	3	92
740	0.971	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	665	3	92
741	0.997	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	665	665	4	93
742	0.975	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	105	0.035	0.26	0.008	0.009	0.04	660	670	3	92
743	0.975	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	107	0.03	0.22	0.008	0.008	0.04	660	670	3	92
744	0.973	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	655	665	4	92
746	0.973	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	103	0.032	0.22	0.008	0.009	0.04	660	670	3	93
747	0.971	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	104	0.033	0.23	0.008	0.009	0.04	665	665	4	92
748	0.982	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.21	0.009	0.009	0.04	660	665	3	92



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size(mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass(g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	$R_{el}$ (N/mm <sup>2</sup> )	$R_m$ (N/mm <sup>2</sup> )	A (%)	HRB
749	0.974	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	108	0.032	0.21	0.009	0.009	0.04	665	665	4	93
751	0.973	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	102	0.031	0.25	0.007	0.01	0.04	660	670	3	92
752	1.496	312	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	107	0.035	0.26	0.008	0.009	0.04	660	670	3	93
627	0.976	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	109	0.032	0.22	0.008	0.009	0.04	655	665	4	92
628	0.975	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	104	0.033	0.23	0.008	0.009	0.04	660	665	3	92
631	0.977	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.21	0.009	0.009	0.04	665	665	4	93
635	0.973	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	105	0.031	0.25	0.007	0.01	0.04	660	670	3	92
642	0.974	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	107	0.035	0.26	0.008	0.009	0.04	660	665	3	92
646	0.963	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	104	0.03	0.22	0.008	0.008	0.04	665	665	4	93
650	0.977	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	103	0.032	0.22	0.008	0.009	0.04	660	670	3	92
651	0.975	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	660	670	3	93
654	0.976	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	106	0.033	0.23	0.008	0.009	0.04	655	665	4	92
655	0.966	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	108	0.032	0.21	0.009	0.009	0.04	660	670	3	93
658	0.978	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	665	665	4	93
662	0.97	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	109	0.035	0.26	0.008	0.009	0.04	660	670	3	92
667	0.974	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	660	665	3	92
670	0.968	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	106	0.033	0.23	0.008	0.009	0.04	665	665	4	93
678	0.983	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	105	0.032	0.21	0.009	0.009	0.04	660	670	3	92
686	0.968	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	660	670	3	93
689	0.972	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	655	665	4	92
692	0.973	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	103	0.03	0.22	0.008	0.008	0.04	660	670	3	93
697	0.976	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	92
698	0.977	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	660	665	3	92
699	0.976	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	665	665	4	93
701	0.973	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	102	0.032	0.21	0.009	0.009	0.04	660	670	3	92
725	0.974	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	670	3	93
745	0.969	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	655	665	4	92
750	0.976	200	0.33*851*2000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	660	665	3	92
1117	1.207	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1118	1.203	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	105	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1119	1.222	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1120	1.212	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1121	1.213	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	103	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1122	1.209	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1123	1.204	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	655	665	4	92
1124	1.205	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	660	670	3	93
1125	1.207	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	102	0.033	0.23	0.008	0.009	0.04	665	665	4	92

捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size(mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass(g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	$R_{cl}$ (N/mm <sup>2</sup> )	$R_m$ (N/mm <sup>2</sup> )	A (%)	HRB
1126	1.224	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1127	1.214	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1128	1.208	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1129	1.206	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	109	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1130	1.209	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1131	1.205	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	106	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1132	1.212	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	105	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1133	1.203	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	660	670	3	93
1134	1.205	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	655	665	4	92
1135	1.203	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	103	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1136	1.219	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	92
1137	1.208	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1138	1.206	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1139	1.2	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	102	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1140	1.209	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1141	1.22	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1142	1.206	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	660	665	3	92
1143	1.207	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1144	1.207	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	105	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1150	1.209	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1151	1.219	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1152	1.222	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	103	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1153	1.215	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1154	1.215	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	655	665	4	92
1155	1.215	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	660	670	3	93
1156	1.215	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	102	0.033	0.23	0.008	0.009	0.04	665	665	4	92
1157	1.216	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1158	1.216	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1159	1.213	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1160	1.224	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	109	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1161	1.215	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1162	1.222	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	106	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1163	1.214	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	105	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1164	1.22	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	660	670	3	93
1165	1.217	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	655	665	4	92
1166	1.215	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	103	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1167	1.211	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	92



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size (mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分 (%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION (%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	$R_{el}$ (N/mm <sup>2</sup> )	$R_m$ (N/mm <sup>2</sup> )	A (%)	HRB
1168	1.214	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1169	1.212	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1170	1.224	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	102	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1171	1.213	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1172	1.216	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1173	1.211	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	660	665	3	92
1174	1.212	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1176	1.215	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	105	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1177	1.216	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1178	1.216	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1179	1.211	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	103	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1180	1.211	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1181	1.21	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	655	665	4	92
1182	1.215	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	660	670	3	93
1183	1.216	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	102	0.033	0.23	0.008	0.009	0.04	665	665	4	92
1184	1.217	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1185	1.204	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1186	1.213	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1187	1.21	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	109	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1188	1.21	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1189	1.209	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	106	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1190	1.213	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	105	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1191	1.219	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	660	670	3	93
1192	1.214	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	655	665	4	92
1193	1.213	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	103	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1194	1.213	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	92
1195	1.214	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1196	1.213	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1197	1.212	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	102	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1198	1.215	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1199	1.215	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1200	1.219	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	660	665	3	92
1201	1.208	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1202	1.22	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	105	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1203	1.213	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1204	1.219	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1205	1.216	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	103	0.035	0.26	0.008	0.009	0.04	660	670	3	92

捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size (mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分 (%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION (%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>el</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB
1206	1.212	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1207	1.215	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	655	665	4	92
1208	1.213	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	660	670	3	93
1209	1.211	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	102	0.033	0.23	0.008	0.009	0.04	665	665	4	92
1210	1.214	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1211	1.206	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1212	1.221	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1213	1.218	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	109	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1214	1.208	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1215	1.206	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	106	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1216	1.212	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	105	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1217	1.215	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	660	670	3	93
1218	1.221	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	655	665	4	92
1219	1.22	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	103	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1220	1.212	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	92
1221	1.204	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1222	1.204	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1223	1.204	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	102	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1232	1.209	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1233	1.202	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1234	1.216	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	660	665	3	92
1235	1.211	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1236	1.214	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	105	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1237	1.203	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1238	1.213	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1239	1.205	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	103	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1240	1.213	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1241	1.214	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	655	665	4	92
1242	1.206	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	660	670	3	93
1243	1.209	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	102	0.033	0.23	0.008	0.009	0.04	665	665	4	92
1244	1.213	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1245	1.211	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1246	1.203	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1247	1.203	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	109	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1248	1.183	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1249	1.217	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	106	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1250	1.227	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	105	0.032	0.21	0.009	0.009	0.04	660	670	3	92



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size (mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分 (%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION (%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>el</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB
1251	1.203	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	660	670	3	93
1252	1.216	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	655	665	4	92
1253	1.211	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	103	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1254	1.204	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	92
1255	1.203	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1256	1.208	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1257	1.214	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	102	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1258	1.214	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1259	1.202	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1264	1.204	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	660	665	3	92
1265	1.203	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1272	1.195	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	105	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1273	1.197	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1274	1.208	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1275	1.198	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	103	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1276	1.208	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1277	1.216	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	655	665	4	92
1278	1.214	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	660	670	3	93
1279	1.217	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	102	0.033	0.23	0.008	0.009	0.04	665	665	4	92
1280	1.209	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1281	1.205	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1282	1.205	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1283	1.204	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	109	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1284	1.207	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1285	1.204	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	106	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1286	1.215	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	105	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1287	1.211	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	660	670	3	93
1288	1.202	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	655	665	4	92
1289	1.21	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	103	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1290	1.215	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	92
1291	1.219	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	660	665	4	92
1292	1.218	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1293	1.213	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	102	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1294	1.216	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1295	1.2	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1296	1.213	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	660	665	3	92
1297	1.213	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	665	665	4	93

捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size(mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass(g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>eL</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB
1298	1.206	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	105	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1299	1.204	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1302	1.219	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1303	1.213	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	103	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1304	1.219	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1305	1.216	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	655	665	4	92
1306	1.214	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	660	670	3	93
1307	1.216	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	102	0.033	0.23	0.008	0.009	0.04	665	665	4	92
1308	1.208	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1309	1.21	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1315	1.208	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1316	1.207	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	109	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1319	1.216	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1320	1.217	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	106	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1322	1.219	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	105	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1323	0.987	162	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	660	670	3	93
1224	1.207	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	655	665	4	92
1225	1.209	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	103	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1226	1.209	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	92
1227	1.205	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1228	1.208	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1229	1.204	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	102	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1230	1.211	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1231	1.204	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1260	1.213	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	660	665	3	92
1261	1.203	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1262	1.203	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	105	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1263	1.198	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1266	1.207	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1267	1.208	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	103	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1268	1.209	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1269	1.208	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	655	665	4	92
1270	1.217	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	660	670	3	93
1271	1.225	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	102	0.033	0.23	0.008	0.009	0.04	665	665	4	92
1301	1.209	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1310	1.203	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1311	1.192	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	665	665	4	93



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size(mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass(g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	$R_{el}(N/mm^2)$	$R_m(N/mm^2)$	A (%)	HRB
1312	1.211	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	109	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1313	1.198	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1318	1.204	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	106	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1175	1.211	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	105	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1300	1.21	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	660	670	3	93
1314	1.224	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	655	665	4	92
1317	1.213	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	103	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1321	1.226	200	0.33*851*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	92
1540	1.453	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1541	1.446	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1542	1.442	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	102	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1543	1.479	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1544	1.449	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1556	1.452	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	660	665	3	92
1557	1.451	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1558	1.442	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	105	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1559	1.444	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1560	1.449	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1561	1.44	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	103	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1562	1.441	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1565	1.453	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	655	665	4	92
1566	1.461	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	660	670	3	93
1567	1.45	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	102	0.033	0.23	0.008	0.009	0.04	665	665	4	92
1568	1.457	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1569	1.449	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1570	1.447	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1571	1.443	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1572	1.441	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1573	1.449	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1574	1.447	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	105	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1575	1.454	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	660	670	3	93
1576	1.444	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	655	665	4	92
1577	1.458	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	103	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1578	1.455	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	92
1579	1.458	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1580	1.452	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1581	1.477	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	102	0.032	0.21	0.009	0.009	0.04	660	670	3	92



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size(mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass(g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>el</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB
1582	1.462	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1583	1.445	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1584	1.464	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	660	665	3	92
1585	1.458	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1586	1.453	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	105	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1587	1.441	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1588	1.443	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1589	1.457	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	103	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1590	1.437	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1591	1.438	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	655	665	4	92
1592	1.437	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	660	670	3	93
1593	1.437	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	102	0.033	0.23	0.008	0.009	0.04	665	665	4	92
1594	1.446	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1595	1.452	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1596	1.44	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1599	1.442	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1600	1.453	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1601	1.438	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1605	1.45	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	105	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1606	1.45	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	660	670	3	93
1607	1.463	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	655	665	4	92
1608	1.467	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	103	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1609	1.45	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	92
1610	1.464	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1611	1.471	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1612	1.465	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	102	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1613	1.455	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1614	1.465	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1615	1.457	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	660	665	3	92
1616	1.451	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1617	1.457	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	105	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1618	1.465	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1619	1.457	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1620	1.452	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	103	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1621	1.439	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1622	1.437	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	655	665	4	92
1623	1.462	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	660	670	3	93



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size (mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	$R_{el}$ (N/mm <sup>2</sup> )	$R_m$ (N/mm <sup>2</sup> )	A (%)	HRB
1624	1.455	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	102	0.033	0.23	0.008	0.009	0.04	665	665	4	92
1625	1.449	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1626	1.449	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1627	1.448	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1628	1.46	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1629	1.462	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1630	1.458	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1631	1.449	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	105	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1632	1.441	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	660	670	3	93
1633	1.453	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	655	665	4	92
1634	1.458	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	103	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1635	1.445	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	92
1636	1.446	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1637	1.437	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1638	1.441	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	102	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1639	1.465	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1640	1.471	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1641	1.458	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	660	665	3	92
1642	1.458	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1643	1.456	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	105	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1644	1.458	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1645	1.442	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1646	1.457	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	103	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1647	1.45	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1648	1.434	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	655	665	4	92
1649	1.439	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	660	670	3	93
1650	1.465	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	102	0.033	0.23	0.008	0.009	0.04	665	665	4	92
1651	1.456	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1652	1.457	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1653	1.454	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1656	1.444	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1657	1.438	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	660	665	4	92
1659	1.458	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1660	1.45	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	105	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1661	1.47	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	660	670	3	93
1665	1.457	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	655	665	4	92
1666	1.46	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	103	0.03	0.22	0.008	0.008	0.04	660	670	3	93



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size(mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass(g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	$R_{el}$ (N/mm <sup>2</sup> )	$R_m$ (N/mm <sup>2</sup> )	A (%)	HRB
1667	1.454	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	92
1668	1.461	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1669	1.447	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1670	1.457	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	102	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1671	1.465	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1672	1.453	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1673	1.456	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	660	665	3	92
1674	1.455	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1675	1.441	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	105	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1676	1.438	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1677	1.458	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1678	1.45	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	103	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1679	1.455	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1680	1.462	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	655	665	4	92
1682	1.48	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	660	670	3	93
1683	1.482	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	102	0.033	0.23	0.008	0.009	0.04	665	665	4	92
1684	1.452	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1685	1.46	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1686	1.442	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1687	1.449	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1688	1.446	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1689	1.456	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1690	1.441	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	105	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1691	1.45	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	660	670	3	93
1697	1.45	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	655	665	4	92
1698	1.454	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	103	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1699	1.439	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	92
1700	1.436	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1701	1.457	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1702	1.454	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	102	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1706	1.465	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1707	1.449	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1708	1.431	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	660	665	3	92
1709	1.452	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1710	1.449	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	105	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1712	1.436	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1714	1.436	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	665	665	4	93



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size(mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	$R_{el}$ (N/mm <sup>2</sup> )	$R_m$ (N/mm <sup>2</sup> )	A (%)	HRB
1715	1.454	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	103	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1716	1.457	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1717	1.467	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	655	665	4	92
1718	1.448	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	660	670	3	93
1719	1.471	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	102	0.033	0.23	0.008	0.009	0.04	665	665	4	92
1720	1.459	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1721	1.455	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1723	1.437	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1725	1.452	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1730	1.449	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1731	1.448	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1732	1.451	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	105	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1733	1.444	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	660	670	3	93
1740	1.467	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	655	665	4	92
1741	1.441	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	103	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1748	1.456	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	92
1749	1.452	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1750	1.455	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1751	1.453	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	102	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1752	1.442	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1753	1.431	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1754	1.447	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	660	665	3	92
1755	1.446	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1758	1.455	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	105	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1760	1.454	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1761	1.467	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1762	1.452	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	103	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1764	1.442	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1766	1.456	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	655	665	4	92
1767	1.471	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	660	670	3	93
1768	1.455	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	102	0.033	0.23	0.008	0.009	0.04	665	665	4	92
1770	1.458	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1771	1.447	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1772	1.46	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1773	1.452	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1776	1.458	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1777	1.449	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.033	0.23	0.008	0.009	0.04	665	665	4	93



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size (mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>eL</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB
1778	1.459	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	105	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1779	1.455	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	660	670	3	93
1780	1.464	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	655	665	4	92
1781	1.456	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	103	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1782	1.45	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	92
1784	1.456	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1785	1.453	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1787	1.458	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	102	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1788	1.439	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1793	1.446	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1794	1.444	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	660	665	3	92
1796	1.451	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1798	1.433	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	105	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1799	1.452	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1800	1.462	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1801	1.453	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	103	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1802	1.455	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1803	1.464	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	655	665	4	92
1804	1.456	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	660	670	3	93
1805	1.452	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	102	0.033	0.23	0.008	0.009	0.04	665	665	4	92
1806	1.455	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1807	1.462	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1808	1.457	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1813	1.455	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1815	1.431	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1816	1.473	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1817	1.466	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	105	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1818	1.453	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	660	670	3	93
1823	1.455	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	655	665	4	92
1824	1.45	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	103	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1826	1.452	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	92
1828	1.448	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1829	1.443	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1830	1.454	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	102	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1831	1.449	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1832	1.439	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1844	1.45	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	660	665	3	92



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size(mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass(g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>eL</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB
1846	1.454	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1847	1.443	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	105	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1850	1.431	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1853	1.445	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1861	1.435	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	103	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1862	1.461	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1863	1.449	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	655	665	4	92
1864	1.45	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	660	670	3	93
1865	1.446	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	102	0.033	0.23	0.008	0.009	0.04	665	665	4	92
1868	1.476	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1869	1.463	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1873	1.466	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1876	1.461	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1877	1.442	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1880	1.431	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1881	1.462	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	105	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1882	1.46	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	660	670	3	93
1883	1.44	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	655	665	4	92
1884	1.445	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	103	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1885	1.444	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	92
1886	1.461	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1887	1.444	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1890	1.46	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	102	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1891	1.447	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1894	1.449	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1908	1.458	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	660	665	3	92
1909	1.448	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1910	1.449	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	105	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1911	1.447	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1912	1.448	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1913	1.448	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	103	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1914	1.467	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1915	1.454	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	655	665	4	92
1918	1.452	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	660	670	3	93
1919	1.442	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	102	0.033	0.23	0.008	0.009	0.04	665	665	4	92
1920	1.441	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1921	1.431	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	665	665	4	93



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size (mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分 (%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION (%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	$R_{el}$ (N/mm <sup>2</sup> )	$R_m$ (N/mm <sup>2</sup> )	A (%)	HRB
1922	1.466	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1923	1.455	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1924	1.453	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1925	1.447	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1927	1.443	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	105	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1928	1.445	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	660	670	3	93
1929	1.45	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	655	665	4	92
1930	1.471	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	103	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1931	1.455	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	92
1933	1.444	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1934	1.456	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1936	1.457	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	102	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1938	1.449	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1941	1.456	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1943	1.47	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	660	665	3	92
1944	1.456	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1945	1.469	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	105	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1948	1.453	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1953	1.445	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1957	1.436	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	103	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1961	1.453	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1963	1.588	220	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	655	665	4	92
1545	1.456	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	660	670	3	93
1546	1.448	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	102	0.033	0.23	0.008	0.009	0.04	665	665	4	92
1547	1.447	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1548	1.443	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1549	1.449	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1550	1.439	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1551	1.445	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1552	1.447	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1553	1.474	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	105	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1554	1.452	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	660	670	3	93
1555	1.449	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	655	665	4	92
1563	1.449	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	103	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1564	1.43	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	92
1597	1.443	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1598	1.437	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	665	665	4	93



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size (mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>el</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB
1602	1.458	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	102	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1603	1.454	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1604	1.454	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1654	1.454	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	660	665	3	92
1655	1.448	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1658	1.453	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	105	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1662	1.437	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1663	1.477	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1664	1.5	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	103	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1681	1.447	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1692	1.444	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	655	665	4	92
1693	1.445	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	660	670	3	93
1694	1.445	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	102	0.033	0.23	0.008	0.009	0.04	665	665	4	92
1695	1.435	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1696	1.455	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1703	1.457	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1704	1.445	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1711	1.455	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1713	1.44	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1722	1.447	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	105	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1724	1.446	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	660	670	3	93
1726	1.456	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	655	665	4	92
1727	1.46	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	103	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1728	1.461	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	92
1729	1.443	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1734	1.456	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1735	1.449	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	102	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1736	1.447	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1737	1.462	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1738	1.45	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	660	665	3	92
1739	1.454	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1742	1.451	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	105	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1743	1.446	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1744	1.441	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1745	1.465	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	103	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1746	1.461	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1756	1.456	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	655	665	4	92




捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size (mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>el</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB
1757	1.456	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	660	670	3	93
1759	1.464	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	102	0.033	0.23	0.008	0.009	0.04	665	665	4	92
1763	1.461	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1765	1.464	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1769	1.448	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1774	1.463	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1783	1.457	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1786	1.474	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1789	1.457	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	105	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1790	1.455	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	660	670	3	93
1791	1.453	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	655	665	4	92
1792	1.458	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	103	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1795	1.457	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	92
1797	1.454	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1809	1.458	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1810	1.458	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	102	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1811	1.451	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1812	1.475	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1814	1.454	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	660	665	3	92
1819	1.458	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1820	1.458	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	105	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1821	1.486	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1822	1.464	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1825	1.455	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	103	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1827	1.446	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1833	1.443	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	655	665	4	92
1834	1.451	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	660	670	3	93
1835	1.461	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	102	0.033	0.23	0.008	0.009	0.04	665	665	4	92
1836	1.454	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1837	1.44	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1838	1.448	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1839	1.46	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1840	1.466	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1841	1.46	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1842	1.467	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	105	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1843	1.463	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	660	670	3	93
1845	1.444	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	655	665	4	92



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size (mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	$R_{el}$ (N/mm <sup>2</sup> )	$R_m$ (N/mm <sup>2</sup> )	A (%)	HRB
1848	1.46	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	103	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1849	1.468	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	92
1851	1.472	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1852	1.453	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1854	1.459	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	102	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1855	1.455	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1856	1.46	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1857	1.459	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	660	665	3	92
1858	1.461	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1859	1.462	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	105	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1860	1.442	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1866	1.47	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1867	1.464	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	103	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1870	1.456	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1871	1.451	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	655	665	4	92
1872	1.464	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	660	670	3	93
1874	1.481	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	102	0.033	0.23	0.008	0.009	0.04	665	665	4	92
1875	1.455	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1878	1.455	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	665	665	4	93
1879	1.449	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	655	665	4	92
1888	1.454	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	105	0.032	0.22	0.008	0.009	0.04	660	670	3	93
1889	1.455	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.033	0.23	0.008	0.009	0.04	665	665	4	92
1892	1.45	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	665	3	92
1893	1.456	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	103	0.032	0.21	0.009	0.009	0.04	665	665	4	93
1895	1.446	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	660	670	3	92
1896	1.449	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1897	1.459	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	655	665	4	92
1898	1.464	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	102	0.033	0.23	0.008	0.009	0.04	660	665	3	92
1899	1.439	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	665	665	4	93
1900	1.458	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	660	670	3	92
1901	1.459	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	660	665	3	92
1902	1.46	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.03	0.22	0.008	0.008	0.04	665	665	4	93
1903	1.454	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	105	0.032	0.22	0.008	0.009	0.04	660	670	3	92
1904	1.478	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.22	0.008	0.009	0.04	660	670	3	93
1905	1.45	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.033	0.23	0.008	0.009	0.04	655	665	4	92
1906	1.465	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	103	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1907	1.457	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	665	665	4	92



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size (mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>el</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB
1916	1.467	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	660	665	3	92
1917	1.45	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	665	665	4	93
1926	1.457	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	102	0.032	0.22	0.008	0.009	0.04	660	670	3	92
1932	1.452	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1935	1.462	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.032	0.21	0.009	0.009	0.04	655	665	4	92
1937	1.457	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	660	665	3	92
1939	1.46	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.035	0.26	0.008	0.009	0.04	665	665	4	93
1940	1.465	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	105	0.035	0.26	0.008	0.009	0.04	660	670	3	92
1942	1.464	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1946	1.436	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1947	1.45	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	103	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1949	1.448	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	660	670	3	93
1950	1.46	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.035	0.26	0.008	0.009	0.04	655	665	4	92
1951	1.46	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	108	0.03	0.22	0.008	0.008	0.04	660	670	3	93
1952	1.447	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	102	0.032	0.22	0.008	0.009	0.04	665	665	4	92
1954	1.465	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.22	0.008	0.009	0.04	660	665	3	92
1955	1.457	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	109	0.033	0.23	0.008	0.009	0.04	665	665	4	93
1956	1.454	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	92
1958	1.462	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1959	1.453	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	105	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1960	1.454	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	107	0.035	0.26	0.008	0.009	0.04	660	665	3	92
1962	1.453	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1705	1.441	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1747	1.455	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1775	1.439	200	0.33*851*3000	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
753	1.776	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
754	1.77	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
755	1.776	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
756	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
757	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
758	1.778	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
759	1.778	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
760	1.781	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
761	1.769	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
762	1.78	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
763	1.776	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
764	1.783	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size(mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass(g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>el</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB
765	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
766	1.776	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
767	1.772	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
768	1.775	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
769	1.778	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
770	1.789	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
771	1.777	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
772	1.778	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
773	1.782	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
774	1.776	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
775	1.774	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
776	1.76	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
777	1.763	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
778	1.768	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
779	1.78	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
780	1.762	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
781	1.77	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
782	1.762	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
783	1.773	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
784	1.773	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
785	1.769	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
786	1.764	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
787	1.782	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
788	1.77	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
789	1.781	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
790	1.763	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
791	1.777	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
792	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
793	1.773	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
794	1.77	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
795	1.775	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
796	1.774	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
797	1.787	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
798	1.769	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
799	1.77	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
800	1.769	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
801	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size (mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>el</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB
802	1.767	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
803	1.765	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
804	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
805	1.779	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
806	1.773	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
807	1.775	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
808	1.781	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
809	1.769	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
810	1.77	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
811	1.77	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
812	1.773	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
813	1.772	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
814	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
815	1.765	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
816	1.774	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
817	1.774	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
818	1.764	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
819	1.773	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
820	1.772	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
821	1.767	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
822	1.775	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
823	1.787	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
824	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
825	1.78	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
826	1.778	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
827	1.774	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
828	1.769	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
829	1.768	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
830	1.769	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
831	1.786	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
832	1.779	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
833	1.779	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
834	1.779	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
835	1.777	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
836	1.788	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
837	1.776	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
838	1.769	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size(mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass(g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>el</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB
839	1.776	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
840	1.783	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
841	1.783	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
842	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
843	1.78	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
844	1.776	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
845	1.781	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
846	1.778	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
847	1.773	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
848	1.775	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
849	1.777	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
850	1.773	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
851	1.775	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
852	1.774	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
853	1.772	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
854	1.77	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
855	1.775	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
856	1.775	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
857	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
858	1.772	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
859	1.774	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
860	1.775	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
861	1.772	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
862	1.782	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
863	1.772	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
864	1.772	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
865	1.772	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
866	1.772	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
867	1.774	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
868	1.769	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
869	1.772	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
870	1.775	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
871	1.778	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
872	1.774	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
873	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
874	1.776	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
875	1.776	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size (mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	$R_{el}$ (N/mm <sup>2</sup> )	$R_m$ (N/mm <sup>2</sup> )	A (%)	HRB
876	1.766	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
877	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
878	1.794	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
879	1.776	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
880	1.784	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
881	1.778	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
882	1.781	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
883	1.794	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
884	1.787	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
885	1.778	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
886	1.784	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
887	1.767	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
888	1.767	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
889	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
890	1.774	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
891	1.794	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
892	1.762	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
893	1.779	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
894	1.763	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
895	1.765	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
896	1.769	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
897	1.788	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
898	1.791	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
899	1.788	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
900	1.782	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
901	1.778	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
902	1.769	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
903	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
904	1.763	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
905	1.777	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
906	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
907	1.768	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
908	1.766	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
909	1.775	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
910	1.763	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
911	1.775	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
912	1.776	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size (mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>el</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB
913	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
914	1.767	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
915	1.783	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
916	1.775	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
917	1.777	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
918	1.782	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
919	1.756	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
920	1.783	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
921	1.768	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
922	1.78	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
923	1.764	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
924	1.773	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
925	1.765	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
926	1.758	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
927	1.784	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
928	1.772	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
929	1.767	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
930	1.775	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
931	1.77	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
932	1.759	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
933	1.764	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
934	1.774	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
935	1.777	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
936	1.755	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
937	1.777	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
938	1.778	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
939	1.781	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
940	1.781	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
941	1.778	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
942	1.779	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
943	1.775	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
944	1.774	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
945	1.787	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
946	1.777	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
947	1.787	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
948	1.769	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
949	1.774	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size (mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>el</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB
950	1.776	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
951	1.785	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
952	1.773	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
953	1.765	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
954	1.761	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
955	1.773	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
956	1.765	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
957	1.779	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
958	1.768	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
959	1.786	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
960	1.758	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
961	1.767	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
962	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
963	1.776	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
964	1.774	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
965	1.785	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
966	1.78	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
967	1.756	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
968	1.765	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
969	1.765	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
970	1.784	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
971	1.766	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
972	1.77	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
973	1.774	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
974	1.775	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
975	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
976	1.791	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
977	1.77	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
978	1.774	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
979	1.772	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
980	1.775	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
981	1.773	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
982	1.78	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
983	1.782	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
984	1.772	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
985	1.776	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
986	1.778	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size(mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass(g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>el</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB
987	1.777	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
988	1.78	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
989	1.774	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
990	1.777	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
991	1.778	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
992	1.788	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
993	1.775	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
994	1.777	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
995	1.763	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
996	1.778	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
997	1.775	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
998	1.775	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
999	1.776	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1000	1.779	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1001	1.768	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1002	1.768	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1003	1.776	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1004	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1005	1.781	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1006	1.782	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1007	1.784	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1008	1.785	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1009	1.787	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1010	1.775	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1011	1.785	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1012	1.769	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1013	1.777	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1014	1.774	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1015	1.772	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1016	1.772	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1017	1.777	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1018	1.783	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1019	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1020	1.767	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1021	1.778	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1022	1.783	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1023	1.776	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size(mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass(g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>el</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB
1024	1.764	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1025	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1026	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1027	1.767	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1028	1.779	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1029	1.775	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1030	1.766	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1031	1.768	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1032	1.766	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1033	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1034	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1035	1.772	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1036	1.76	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1037	1.767	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1038	1.772	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1039	1.784	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1040	1.766	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1041	1.787	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1042	1.763	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1043	1.773	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1044	1.769	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1045	1.765	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1046	1.764	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1047	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1048	1.763	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1049	1.761	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1050	1.762	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1051	1.777	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1052	1.762	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1053	1.768	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1054	1.78	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1055	1.768	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1056	1.763	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1057	1.76	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1058	1.77	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1059	1.763	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1060	1.775	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size(mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass(g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	$R_{el}$ (N/mm <sup>2</sup> )	$R_m$ (N/mm <sup>2</sup> )	A (%)	HRB
1061	1.778	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1062	1.767	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1063	1.781	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1064	1.765	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1065	1.778	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1066	1.768	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1067	1.768	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1068	1.765	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1069	1.765	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1070	1.769	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1071	1.764	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1072	1.764	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1073	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1074	1.794	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1075	1.78	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1076	1.793	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1077	1.777	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1078	1.775	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1079	1.77	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1080	1.775	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1081	1.758	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1082	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1083	1.777	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1084	1.763	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1085	1.749	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1086	1.765	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1087	1.786	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1088	1.767	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1089	1.773	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1090	1.766	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1091	1.761	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1092	1.744	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1093	1.76	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1094	1.767	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1095	1.767	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1096	1.767	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1097	1.77	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size(mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass(g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>el</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB
1098	1.77	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1099	1.763	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1100	1.762	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1101	1.763	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1102	1.759	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1103	1.754	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1104	1.763	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1105	1.787	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1106	1.769	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1107	1.763	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1108	1.78	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1109	1.766	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1110	1.757	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1111	1.77	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1112	1.775	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1113	1.77	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1114	1.786	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1115	1.772	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1116	1.78	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1145	1.766	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1146	1.759	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1147	1.776	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1148	1.778	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1149	1.768	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1324	1.787	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1325	1.781	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1326	1.772	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1327	1.757	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1328	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1329	1.75	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1330	1.746	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1331	1.772	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1332	1.763	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1333	1.761	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1334	1.757	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1335	1.772	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1336	1.757	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size (mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>el</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB
1337	1.746	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1338	1.745	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1339	1.78	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1340	1.761	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1341	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1342	1.77	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1343	1.76	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1344	1.751	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1345	1.744	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1346	1.766	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1347	1.777	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1348	1.769	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1349	1.769	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1350	1.766	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1351	1.758	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1352	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1353	1.772	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1354	1.792	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1355	1.767	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1356	1.743	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1357	1.777	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1361	1.766	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1367	1.741	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1368	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1369	1.759	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1372	1.761	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1373	1.756	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1376	1.798	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1379	1.756	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1381	1.777	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1382	1.774	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1383	1.773	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1384	1.755	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1385	1.767	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1386	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1387	1.749	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1388	1.77	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size (mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	$R_{el}$ (N/mm <sup>2</sup> )	$R_m$ (N/mm <sup>2</sup> )	A (%)	HRB
1389	1.76	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1390	1.753	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1391	1.742	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1392	1.763	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1393	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1394	1.764	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1395	1.764	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1396	1.77	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1397	1.763	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1398	1.748	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1399	1.753	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1405	1.759	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1406	1.767	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1408	1.773	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1409	1.763	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1411	1.764	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1412	1.755	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1413	1.752	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1417	1.769	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1418	1.751	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1420	1.75	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1421	1.764	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1422	1.754	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1423	1.775	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1424	1.751	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1425	1.756	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1426	1.755	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1427	1.776	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1428	1.768	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1429	1.76	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1430	1.755	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1431	1.756	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1432	1.77	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1433	1.779	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1434	1.761	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1435	1.767	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1436	1.759	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size(mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass(g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>el</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB
1438	1.749	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1440	1.774	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1442	1.747	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1444	1.784	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1445	1.787	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1446	1.75	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1447	1.768	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1448	1.76	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1450	1.774	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1451	1.767	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1452	1.759	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1454	1.758	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1455	1.764	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1456	1.75	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1458	1.743	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1460	1.762	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1461	1.775	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1462	1.766	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1463	1.753	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1464	1.754	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1465	1.757	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1466	1.74	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1467	1.779	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1469	1.765	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1471	1.76	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1472	1.758	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1473	1.754	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1474	1.786	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1475	1.772	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1476	1.751	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1477	1.769	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1478	1.773	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1479	1.76	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1480	1.761	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1481	1.759	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1482	1.782	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1483	1.763	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size (mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>el</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB
1485	1.756	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1486	1.782	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1487	1.778	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1489	1.762	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1490	1.76	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1491	1.778	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1493	1.783	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1494	1.764	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1496	1.76	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1497	1.767	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1498	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1500	1.76	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1501	1.753	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1502	1.756	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1503	1.77	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1504	1.767	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1506	1.762	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1507	1.775	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1508	1.763	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1509	1.755	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1510	1.779	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1511	1.778	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1512	1.775	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1513	1.758	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1514	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1515	1.786	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1516	1.78	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1518	1.768	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1519	1.786	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1521	1.776	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1522	1.788	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1523	1.764	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1524	1.776	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1528	1.772	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1529	1.781	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1530	1.764	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1532	1.742	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size(mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	$R_{el}$ (N/mm <sup>2</sup> )	$R_m$ (N/mm <sup>2</sup> )	A (%)	HRB
1533	1.77	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1534	1.762	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1535	1.765	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1536	1.762	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1537	1.762	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1538	1.773	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1539	1.775	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1358	1.755	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1359	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1360	1.784	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1363	1.759	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1364	1.783	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1365	1.774	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1366	1.772	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1370	1.778	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1371	1.759	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1374	1.767	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1375	1.757	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1377	1.746	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1378	1.747	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1380	1.768	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1400	1.762	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1401	1.774	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1402	1.758	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1403	1.769	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1404	1.75	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1407	1.776	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1410	1.762	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1414	1.753	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1415	1.753	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1416	1.761	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1419	1.75	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1437	1.775	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1439	1.78	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1441	1.76	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1443	1.77	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1449	1.776	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size(mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass(g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>el</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB
1453	1.768	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1457	1.743	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1459	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1468	1.766	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1470	1.784	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1484	1.767	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1488	1.767	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1492	1.778	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1495	1.761	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1499	1.75	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1505	1.765	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1517	1.766	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1520	1.765	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1527	1.78	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1531	1.767	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1967	1.762	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1968	1.785	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1969	1.773	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1970	1.79	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1971	1.776	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1972	1.794	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1973	1.773	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1975	1.795	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1976	1.77	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1977	1.765	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1980	1.762	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1981	1.752	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1982	1.772	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1983	1.761	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1984	1.755	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1985	1.775	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1986	1.776	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1987	1.77	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1990	1.789	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1991	1.784	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1992	1.782	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1993	1.781	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size (mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>eL</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB
1994	1.779	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1995	1.769	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1998	1.766	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
2001	1.774	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
2002	1.783	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
2003	1.76	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
2004	1.788	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
2005	1.787	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
2006	1.767	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
2009	1.769	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
2010	1.765	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
2011	1.786	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
2012	1.778	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
2013	1.769	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
2014	1.761	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
2015	1.756	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
2016	1.787	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
2017	1.778	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
2018	1.798	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
2019	1.778	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
2020	1.775	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
2021	1.772	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
2022	1.761	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
2023	1.772	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
2024	1.784	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
2025	1.765	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
2026	1.767	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
2027	1.77	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
2034	1.777	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
2040	1.761	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
2041	1.737	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
2043	1.765	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
2044	1.758	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
2045	1.744	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
2046	1.749	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
2047	1.748	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
2048	1.764	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size(mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass(g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>el</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A(%)	HRB
2050	1.799	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
2051	1.78	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
2052	1.778	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
2054	1.763	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
2055	1.777	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
2058	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
2059	1.767	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
2060	1.784	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
2061	1.762	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
2065	1.766	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
2066	1.785	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
2067	1.751	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
2068	1.784	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
2070	1.782	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
2071	1.752	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
2072	1.751	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
2073	1.744	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
2074	1.789	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
2075	1.8	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
2076	1.79	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
2077	1.767	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
2078	1.761	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
2079	1.785	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
2080	1.777	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
2081	1.759	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
2082	1.786	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
2085	1.794	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
2086	1.781	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
2087	1.786	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
2088	1.772	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
2089	1.779	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
2090	1.794	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
2091	1.758	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
2092	1.773	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
2095	1.754	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
2096	1.749	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
2097	1.775	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size(mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass(g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	$R_{el}$ (N/mm <sup>2</sup> )	$R_m$ (N/mm <sup>2</sup> )	A (%)	HRB
2098	1.773	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
2100	1.768	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
2101	1.766	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
2102	1.779	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
2103	1.749	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
2105	1.751	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
2106	1.778	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
2107	1.773	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
2109	1.763	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
2110	1.779	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
2111	1.753	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
2114	1.781	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
2115	1.776	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
2116	1.776	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
2117	1.774	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
2118	1.778	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
2119	1.767	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
2121	1.783	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
2122	1.768	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
2123	1.785	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
2124	1.75	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
2126	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
2128	1.769	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
2131	1.769	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
2139	1.785	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
2141	1.781	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
2144	1.784	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
2145	1.778	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
2146	1.775	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
2147	1.776	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
2154	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1964	1.815	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
1965	1.778	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1966	1.784	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1974	1.758	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1978	1.78	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1979	1.75	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size (mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分 (%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION (%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>el</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB
1988	1.774	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1989	1.777	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1996	1.78	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1997	1.774	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
2000	1.778	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
2007	1.774	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
2008	1.775	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
2028	1.78	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
2029	1.762	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
2030	1.766	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
2031	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
2032	1.781	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
2033	1.794	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
2035	1.769	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
2036	1.765	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
2037	1.773	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
2038	1.781	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
2039	1.793	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
2042	1.77	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
2049	1.755	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
2053	1.783	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
2056	1.765	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
2063	1.774	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
2064	1.775	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
2084	1.778	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
2104	1.768	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
2108	1.783	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
2112	1.798	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
2113	1.773	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
2125	1.78	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
2127	1.78	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
2129	1.794	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
2130	1.792	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
2132	1.766	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
2133	1.776	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
2134	1.79	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
2135	1.771	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size (mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	$R_{el}$ (N/mm <sup>2</sup> )	$R_m$ (N/mm <sup>2</sup> )	A (%)	HRB
2136	1.787	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
2137	1.781	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
2138	1.784	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
2140	1.785	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
2142	1.788	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
2143	1.783	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
2148	1.784	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
2149	1.786	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
2150	1.779	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
2151	1.787	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
2152	1.775	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
2153	1.778	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
2155	1.778	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
2156	1.78	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
2157	1.773	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
2158	2.602	297	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
1362	1.772	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
1525	1.776	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
1526	1.758	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
2057	1.77	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
2069	1.783	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
2083	1.782	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
2093	1.765	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
2094	1.802	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
1999	1.779	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
2062	1.781	200	0.33*851*3660	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
600	1.943	200	0.33*851*4000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
601	1.932	200	0.33*851*4000	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
602	1.94	200	0.33*851*4000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
603	1.933	200	0.33*851*4000	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
604	1.946	200	0.33*851*4000	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
605	1.928	200	0.33*851*4000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
606	1.941	200	0.33*851*4000	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
608	1.934	200	0.33*851*4000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
609	1.931	200	0.33*851*4000	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
610	1.925	200	0.33*851*4000	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
611	1.942	200	0.33*851*4000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size (mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分 (%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION (%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>el</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB
612	1.938	200	0.33*851*4000	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
613	1.927	200	0.33*851*4000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
614	1.956	200	0.33*851*4000	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
615	1.944	200	0.33*851*4000	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
616	1.936	200	0.33*851*4000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
617	1.928	200	0.33*851*4000	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
619	1.942	200	0.33*851*4000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
620	1.942	200	0.33*851*4000	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
621	1.949	200	0.33*851*4000	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
622	1.933	200	0.33*851*4000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
623	1.937	200	0.33*851*4000	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
624	1.93	200	0.33*851*4000	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	660	670	3	92
625	1.932	200	0.33*851*4000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	660	670	3	93
626	1.942	201	0.33*851*4000	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	655	665	4	92
607	1.927	200	0.33*851*4000	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	660	670	3	93
618	1.937	200	0.33*851*4000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	665	665	4	93
	2414.829																	

NOTE: 1、 ReL : lower yield strength    Rm : tensile strength    A: percentage elongation after fracture  
2、 1 N/mm2=1 MPa

证明本表所列制品，均依材料规格制造及试验，并符合规格之要求  
WE HEREBY CERTIFY THAT THE MATERIAL DESCRIBED HEREIN HAS BEEN MANUFACTURED AND TESTED WITH SATISFACTORY RESULT IN ACCORDANCE  
WITH THE REQUIREMENT OF THE ABOVE MATERIAL SPECIFICATION.



质量部  
DEPARTM

**XINGHAN**

冠县众冠新材料有限公司

GUANXIAN ZHONGGUAN NEW MATERIALS CO., LTD.

地址: 中国山东聊城冠县新世纪工业园

Address: Guan Xian industry Park, Liaocheng, Shandong, China

# 产品质量证明书

## MILL'S TEST CERTIFICATE

订货单位 CUSTOMER		CUMIC STEEL LIMITED								钢号 GR.37	产品名称 PRODUCT					GALVALUME STEEL CORRUGATED SHEETS 5V		
收货单位 PURCHASER		CUMIC STEEL LIMITED									签发日期 DATE					2024.11.20		
标准 SPECIFICATION		ASTM A792M									合同号 CONTRACT NO.					ZG202408134488		
捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size (mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分 (%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>el</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB
447	0.94	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	104	0.033	0.23	0.008	0.009	0.04	450	465	27	76
448	0.947	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	103	0.032	0.21	0.009	0.009	0.04	455	465	26	75
449	0.939	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	450	470	27	76
450	0.939	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	455	470	26	75
451	0.945	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	455	465	27	76
452	0.942	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	102	0.032	0.22	0.008	0.009	0.04	450	470	28	76
453	0.938	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	107	0.033	0.23	0.008	0.009	0.04	455	465	26	76
454	0.937	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	109	0.032	0.21	0.009	0.009	0.04	450	465	27	76
455	0.952	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	455	465	26	75
456	0.945	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	106	0.035	0.26	0.008	0.009	0.04	450	470	27	76
457	0.937	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	105	0.03	0.22	0.008	0.008	0.04	455	470	26	75
458	0.944	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.22	0.008	0.009	0.04	455	465	27	76
459	0.944	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	455	465	26	76
460	0.945	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	450	465	27	76
461	0.942	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	455	465	27	75
462	0.954	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	455	470	28	76
463	0.944	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	455	470	27	76
464	0.947	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	102	0.033	0.23	0.008	0.009	0.04	455	470	28	75
465	0.938	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	450	465	27	75
466	0.933	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	455	470	26	76
467	0.948	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	450	465	27	75
468	0.952	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	455	470	27	76
469	0.948	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	105	0.033	0.23	0.008	0.009	0.04	455	470	28	76

捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size(mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass(g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	$R_{eL}$ (N/mm <sup>2</sup> )	$R_m$ (N/mm <sup>2</sup> )	A(%)	HRB
470	0.948	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	107	0.035	0.26	0.008	0.009	0.04	455	465	27	75
471	0.946	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	455	470	28	76
472	0.946	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	455	470	27	76
473	0.948	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	455	470	28	75
474	0.95	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	450	465	27	75
475	0.946	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	455	470	26	76
476	0.949	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	102	0.03	0.22	0.008	0.008	0.04	450	465	27	75
477	0.949	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.22	0.008	0.009	0.04	455	470	27	76
478	0.947	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	109	0.032	0.22	0.008	0.009	0.04	455	470	28	76
479	0.945	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	104	0.033	0.23	0.008	0.009	0.04	450	465	27	75
480	0.944	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.21	0.009	0.009	0.04	455	465	26	76
481	0.942	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	105	0.032	0.21	0.009	0.009	0.04	450	465	27	76
482	0.936	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	455	470	28	76
483	0.937	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	450	465	27	75
484	0.942	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	103	0.032	0.22	0.008	0.009	0.04	455	470	26	76
485	0.941	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	104	0.033	0.23	0.008	0.009	0.04	450	465	27	75
486	0.943	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.21	0.009	0.009	0.04	455	465	26	76
487	0.944	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	108	0.031	0.25	0.007	0.01	0.04	455	465	27	76
488	0.949	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	102	0.035	0.26	0.008	0.009	0.04	450	470	28	76
489	0.945	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	107	0.03	0.22	0.008	0.008	0.04	455	470	26	76
490	0.948	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	109	0.032	0.22	0.008	0.009	0.04	450	465	27	75
491	0.947	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	455	465	28	76
492	0.949	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	106	0.033	0.23	0.008	0.009	0.04	450	465	27	76
493	0.949	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	105	0.032	0.21	0.009	0.009	0.04	455	465	26	75
494	0.947	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	450	470	27	76
495	0.944	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	455	470	26	75
496	0.946	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	103	0.035	0.26	0.008	0.009	0.04	455	465	27	76
497	0.948	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	450	470	28	76
498	0.948	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	455	465	28	76
499	0.938	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	450	465	27	76
500	0.94	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	102	0.032	0.21	0.009	0.009	0.04	455	465	26	75
501	0.94	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	450	470	27	76
502	0.94	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	455	470	26	75
503	0.937	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	455	465	27	76
504	0.937	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	450	470	28	76
505	0.941	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	105	0.035	0.26	0.008	0.009	0.04	455	465	27	75

捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size(mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass(g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>el</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A(%)	HRB
506	0.941	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.22	0.008	0.009	0.04	455	470	28	76
507	0.941	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	104	0.033	0.23	0.008	0.009	0.04	455	470	27	76
508	0.946	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	103	0.032	0.21	0.009	0.009	0.04	455	470	28	75
509	0.948	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	450	465	27	75
510	0.948	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	106	0.035	0.26	0.008	0.009	0.04	455	470	26	76
511	0.944	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	108	0.03	0.22	0.008	0.008	0.04	450	465	27	75
512	0.939	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	102	0.032	0.22	0.008	0.009	0.04	455	470	27	76
513	0.936	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.22	0.008	0.009	0.04	455	470	28	76
514	0.94	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	109	0.033	0.23	0.008	0.009	0.04	450	465	27	75
515	0.94	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	455	465	26	76
516	0.944	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.21	0.009	0.009	0.04	450	465	27	76
517	0.957	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	105	0.031	0.25	0.007	0.01	0.04	455	470	28	76
518	0.945	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	107	0.035	0.26	0.008	0.009	0.04	450	465	27	75
519	0.948	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	455	470	26	76
520	0.947	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	450	465	27	75
521	0.946	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	455	465	27	75
522	0.946	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	455	470	28	76
523	0.944	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	455	470	27	76
524	0.937	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	102	0.032	0.21	0.009	0.009	0.04	455	470	28	75
525	0.942	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	450	465	27	75
526	0.945	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	109	0.035	0.26	0.008	0.009	0.04	455	470	26	76
527	0.933	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	104	0.03	0.22	0.008	0.008	0.04	450	465	27	75
528	0.936	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	455	470	27	76
529	0.939	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	105	0.032	0.22	0.008	0.009	0.04	455	470	28	76
530	0.942	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	107	0.033	0.23	0.008	0.009	0.04	450	465	27	75
531	0.937	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	455	465	26	76
532	0.937	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	103	0.032	0.21	0.009	0.009	0.04	450	465	27	76
533	0.948	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	455	470	28	76
534	0.944	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	106	0.035	0.26	0.008	0.009	0.04	450	465	27	75
535	0.947	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	455	470	26	76
536	0.934	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	102	0.033	0.23	0.008	0.009	0.04	450	465	27	75
537	0.936	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	455	465	26	76
538	0.945	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	455	465	27	76
539	0.95	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	450	470	28	76
540	0.939	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	106	0.03	0.22	0.008	0.008	0.04	455	470	26	76
541	0.937	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	105	0.032	0.22	0.008	0.009	0.04	450	465	27	75

捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size(mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>eL</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB
542	0.944	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.22	0.008	0.009	0.04	455	465	28	76
543	0.947	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	104	0.033	0.23	0.008	0.009	0.04	450	465	27	76
544	0.94	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	103	0.032	0.21	0.009	0.009	0.04	455	465	26	75
545	0.94	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	450	470	27	76
546	0.941	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	455	470	26	75
547	0.931	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	105	0.031	0.25	0.007	0.01	0.04	455	470	28	76
548	0.941	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	107	0.035	0.26	0.008	0.009	0.04	450	465	27	75
549	0.931	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	455	470	26	76
550	0.939	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	450	465	27	75
551	0.946	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	455	465	27	75
552	0.936	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	455	470	28	76
553	0.927	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	455	470	27	76
554	0.945	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	102	0.032	0.21	0.009	0.009	0.04	455	470	28	75
555	0.946	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	450	465	27	75
556	0.931	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	109	0.035	0.26	0.008	0.009	0.04	455	470	26	76
557	0.933	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	104	0.03	0.22	0.008	0.008	0.04	450	465	27	75
558	0.946	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	455	470	27	76
559	0.963	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	105	0.032	0.22	0.008	0.009	0.04	455	470	28	76
560	0.935	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	107	0.033	0.23	0.008	0.009	0.04	450	465	27	75
561	0.936	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	455	465	26	76
562	0.941	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	103	0.032	0.21	0.009	0.009	0.04	450	465	27	76
563	0.943	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	455	470	28	76
564	0.953	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	106	0.035	0.26	0.008	0.009	0.04	450	465	27	75
565	0.946	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	455	470	26	76
566	0.935	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	102	0.033	0.23	0.008	0.009	0.04	450	465	27	75
567	0.939	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	455	465	26	76
568	0.937	200	0.33*895*2000	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	455	465	27	76
181	1.176	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	450	470	28	76
182	1.177	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.03	0.22	0.008	0.008	0.04	455	470	26	76
183	1.17	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	105	0.032	0.22	0.008	0.009	0.04	450	465	27	75
184	1.169	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.22	0.008	0.009	0.04	455	465	28	76
185	1.169	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.033	0.23	0.008	0.009	0.04	450	465	27	76
186	1.169	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	103	0.032	0.21	0.009	0.009	0.04	455	465	26	75
187	1.168	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	450	470	27	76
188	1.17	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	455	470	26	75
189	1.17	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	105	0.031	0.25	0.007	0.01	0.04	455	470	28	76

捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size (mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分 (%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION (%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>eL</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB
190	1.17	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.035	0.26	0.008	0.009	0.04	450	465	27	75
191	1.174	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	455	470	26	76
192	1.174	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	450	465	27	75
193	1.17	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	455	465	27	75
194	1.171	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	455	470	28	76
195	1.175	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	455	470	27	76
196	1.176	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	102	0.032	0.21	0.009	0.009	0.04	455	470	28	75
197	1.172	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	450	465	27	75
198	1.175	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	109	0.035	0.26	0.008	0.009	0.04	455	470	26	76
199	1.176	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.03	0.22	0.008	0.008	0.04	450	465	27	75
200	1.173	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	455	470	27	76
201	1.176	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	105	0.032	0.22	0.008	0.009	0.04	455	470	28	76
202	1.169	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.033	0.23	0.008	0.009	0.04	450	465	27	75
203	1.174	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	455	465	26	76
204	1.172	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	103	0.032	0.21	0.009	0.009	0.04	450	465	27	76
205	1.176	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	455	470	28	76
206	1.173	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.035	0.26	0.008	0.009	0.04	450	465	27	75
207	1.173	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	455	470	26	76
208	1.175	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	102	0.033	0.23	0.008	0.009	0.04	450	465	27	75
209	1.177	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	455	465	26	76
210	1.172	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	455	465	27	76
211	1.171	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	450	470	28	76
212	1.175	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.03	0.22	0.008	0.008	0.04	455	470	26	76
213	1.173	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	105	0.032	0.22	0.008	0.009	0.04	450	465	27	75
214	1.173	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.22	0.008	0.009	0.04	455	465	28	76
215	1.168	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.033	0.23	0.008	0.009	0.04	450	465	27	76
216	1.172	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	103	0.032	0.21	0.009	0.009	0.04	455	465	26	75
217	1.175	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	450	470	27	76
218	1.17	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	455	470	26	75
219	1.17	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	105	0.031	0.25	0.007	0.01	0.04	455	470	28	76
220	1.174	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.035	0.26	0.008	0.009	0.04	450	465	27	75
221	1.176	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	455	470	26	76
222	1.166	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	450	465	27	75
223	1.167	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	455	465	27	75
224	1.168	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	455	470	28	76
225	1.17	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	455	470	27	76


捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size (mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分 (%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	$R_{el}$ (N/mm <sup>2</sup> )	$R_m$ (N/mm <sup>2</sup> )	A (%)	HRB
226	1.171	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	102	0.032	0.21	0.009	0.009	0.04	455	470	28	75
227	1.173	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	450	465	27	75
228	1.175	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	109	0.035	0.26	0.008	0.009	0.04	455	470	26	76
229	1.179	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.03	0.22	0.008	0.008	0.04	450	465	27	75
230	1.171	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	455	470	27	76
231	1.174	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	105	0.032	0.22	0.008	0.009	0.04	455	470	28	76
232	1.181	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.033	0.23	0.008	0.009	0.04	450	465	27	75
233	1.179	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	455	465	26	76
234	1.173	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	103	0.032	0.21	0.009	0.009	0.04	450	465	27	76
235	1.176	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	455	470	28	76
236	1.166	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.035	0.26	0.008	0.009	0.04	450	465	27	75
237	1.166	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	455	470	26	76
238	1.177	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	102	0.033	0.23	0.008	0.009	0.04	450	465	27	75
239	1.177	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	455	465	26	76
240	1.17	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	455	465	27	76
241	1.173	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	450	470	28	76
242	1.17	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.03	0.22	0.008	0.008	0.04	455	470	26	76
243	1.17	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	105	0.032	0.22	0.008	0.009	0.04	450	465	27	75
244	1.173	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.22	0.008	0.009	0.04	455	465	28	76
245	1.176	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.033	0.23	0.008	0.009	0.04	450	465	27	76
246	1.182	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	103	0.032	0.21	0.009	0.009	0.04	455	465	26	75
247	1.176	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	450	470	27	76
248	1.181	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	455	470	26	75
249	1.18	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	105	0.031	0.25	0.007	0.01	0.04	455	470	28	76
250	1.18	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.035	0.26	0.008	0.009	0.04	450	465	27	75
251	1.178	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	455	470	26	76
252	1.178	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	450	465	27	75
253	1.173	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	455	465	27	75
254	1.181	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	455	470	28	76
255	1.177	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	455	470	27	76
256	1.181	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	102	0.032	0.21	0.009	0.009	0.04	455	470	28	75
257	1.182	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	450	465	27	75
258	1.175	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	109	0.035	0.26	0.008	0.009	0.04	455	470	26	76
259	1.179	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.03	0.22	0.008	0.008	0.04	450	465	27	75
260	1.181	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	455	470	27	76
261	1.181	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	105	0.032	0.22	0.008	0.009	0.04	455	470	28	76

捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size (mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分 (%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION (%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>el</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB
262	1.177	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.033	0.23	0.008	0.009	0.04	450	465	27	75
263	1.177	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	455	465	26	76
264	1.177	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	103	0.032	0.21	0.009	0.009	0.04	450	465	27	76
265	1.183	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	455	470	28	76
266	1.176	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.035	0.26	0.008	0.009	0.04	450	465	27	75
267	1.179	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	455	470	26	76
268	1.18	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	102	0.033	0.23	0.008	0.009	0.04	450	465	27	75
269	1.176	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	455	465	26	76
270	1.173	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	455	465	27	76
271	1.18	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	450	470	28	76
272	1.182	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.03	0.22	0.008	0.008	0.04	455	470	26	76
273	1.177	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	105	0.032	0.22	0.008	0.009	0.04	450	465	27	75
274	1.176	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.22	0.008	0.009	0.04	455	465	28	76
275	1.182	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.033	0.23	0.008	0.009	0.04	450	465	27	76
276	1.18	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	103	0.032	0.21	0.009	0.009	0.04	455	465	26	75
277	1.175	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	450	470	27	76
278	1.178	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	455	470	26	75
279	1.183	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	105	0.031	0.25	0.007	0.01	0.04	455	470	28	76
280	1.186	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.035	0.26	0.008	0.009	0.04	450	465	27	75
281	1.183	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	455	470	26	76
282	1.18	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	450	465	27	75
283	1.178	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	455	465	27	75
284	1.176	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	455	470	28	76
285	1.175	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	455	470	27	76
286	1.171	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	102	0.032	0.21	0.009	0.009	0.04	455	470	28	75
287	1.172	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	450	465	27	75
288	1.174	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	109	0.035	0.26	0.008	0.009	0.04	455	470	26	76
289	1.168	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.03	0.22	0.008	0.008	0.04	450	465	27	75
290	1.168	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	455	470	27	76
291	1.174	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	105	0.032	0.22	0.008	0.009	0.04	455	470	28	76
292	1.174	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.033	0.23	0.008	0.009	0.04	450	465	27	75
293	1.174	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	455	465	26	76
294	1.174	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	103	0.032	0.21	0.009	0.009	0.04	450	465	27	76
295	1.17	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	455	470	28	76
296	1.168	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.035	0.26	0.008	0.009	0.04	450	465	27	75
297	1.173	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	455	470	26	76

捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size(mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分 (%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	$R_{el}$ (N/mm <sup>2</sup> )	$R_m$ (N/mm <sup>2</sup> )	A (%)	HRB
298	1.169	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	102	0.033	0.23	0.008	0.009	0.04	450	465	27	75
299	1.176	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	455	465	26	76
300	1.175	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	455	465	27	76
301	1.169	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	450	470	28	76
302	1.169	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.03	0.22	0.008	0.008	0.04	455	470	26	76
303	1.176	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	105	0.032	0.22	0.008	0.009	0.04	450	465	27	75
304	1.175	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.22	0.008	0.009	0.04	455	465	28	76
305	1.175	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.033	0.23	0.008	0.009	0.04	450	465	27	76
306	1.179	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	103	0.032	0.21	0.009	0.009	0.04	455	465	26	75
307	1.172	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	450	470	27	76
308	1.176	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	455	470	26	75
309	1.175	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	105	0.031	0.25	0.007	0.01	0.04	455	470	28	76
310	1.173	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.035	0.26	0.008	0.009	0.04	450	465	27	75
311	1.176	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	455	470	26	76
312	1.176	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	450	465	27	75
313	1.161	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	455	465	27	75
314	1.167	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	455	470	28	76
315	1.175	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	455	470	27	76
316	1.175	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	102	0.032	0.21	0.009	0.009	0.04	455	470	28	75
317	1.171	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	450	465	27	75
318	1.175	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	109	0.035	0.26	0.008	0.009	0.04	455	470	26	76
319	1.174	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.03	0.22	0.008	0.008	0.04	450	465	27	75
320	1.171	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	455	470	27	76
321	1.171	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	105	0.032	0.22	0.008	0.009	0.04	455	470	28	76
322	1.171	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.033	0.23	0.008	0.009	0.04	450	465	27	75
323	1.167	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	455	465	26	76
324	1.173	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	103	0.032	0.21	0.009	0.009	0.04	450	465	27	76
325	1.175	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	455	470	28	76
326	1.176	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.035	0.26	0.008	0.009	0.04	450	465	27	75
327	1.168	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	455	470	26	76
328	1.168	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	102	0.033	0.23	0.008	0.009	0.04	450	465	27	75
329	1.166	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	455	465	26	76
330	1.161	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	455	465	27	76
331	1.175	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	450	470	28	76
332	1.177	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.03	0.22	0.008	0.008	0.04	455	470	26	76
333	1.178	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	105	0.032	0.22	0.008	0.009	0.04	450	465	27	75



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size (mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分 (%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>el</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB
334	1.178	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.22	0.008	0.009	0.04	455	465	28	76
335	1.178	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.033	0.23	0.008	0.009	0.04	450	465	27	76
336	1.185	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	103	0.032	0.21	0.009	0.009	0.04	455	465	26	75
337	1.183	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	450	470	27	76
338	1.182	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	455	470	26	75
339	1.173	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	105	0.031	0.25	0.007	0.01	0.04	455	470	28	76
340	1.176	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.035	0.26	0.008	0.009	0.04	450	465	27	75
341	1.177	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	455	470	26	76
342	1.179	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	450	465	27	75
343	1.174	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	455	465	27	75
344	1.175	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	455	470	28	76
345	1.175	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	455	470	27	76
346	1.176	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	102	0.032	0.21	0.009	0.009	0.04	455	470	28	75
347	1.179	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	450	465	27	75
348	1.175	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	109	0.035	0.26	0.008	0.009	0.04	455	470	26	76
349	1.17	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.03	0.22	0.008	0.008	0.04	450	465	27	75
350	1.177	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	455	470	27	76
351	1.178	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	105	0.032	0.22	0.008	0.009	0.04	455	470	28	76
352	1.176	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.033	0.23	0.008	0.009	0.04	450	465	27	75
353	1.174	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	455	465	26	76
354	1.175	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	103	0.032	0.21	0.009	0.009	0.04	450	465	27	76
355	1.177	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	455	470	28	76
356	1.174	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.035	0.26	0.008	0.009	0.04	450	465	27	75
357	1.179	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	455	470	26	76
358	1.175	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	102	0.033	0.23	0.008	0.009	0.04	450	465	27	75
359	1.175	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	455	465	26	76
360	1.174	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	455	465	27	76
361	1.176	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	450	470	28	76
362	1.179	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.03	0.22	0.008	0.008	0.04	455	470	26	76
363	1.173	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	105	0.032	0.22	0.008	0.009	0.04	450	465	27	75
364	1.165	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.22	0.008	0.009	0.04	455	465	28	76
365	1.176	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.033	0.23	0.008	0.009	0.04	450	465	27	76
366	1.176	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	103	0.032	0.21	0.009	0.009	0.04	455	465	26	75
367	1.167	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	450	470	27	76
368	1.169	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	455	470	26	75
369	1.178	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	105	0.031	0.25	0.007	0.01	0.04	455	470	28	76



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size (mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分 (%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION (%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>el</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB
370	1.167	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.035	0.26	0.008	0.009	0.04	450	465	27	75
371	1.169	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	455	470	26	76
372	1.167	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	450	465	27	75
373	1.169	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	455	465	27	75
374	1.168	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	455	470	28	76
375	1.173	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	455	470	27	76
376	1.177	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	102	0.032	0.21	0.009	0.009	0.04	455	470	28	75
377	1.167	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	450	465	27	75
378	1.172	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	109	0.035	0.26	0.008	0.009	0.04	455	470	26	76
379	1.177	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.03	0.22	0.008	0.008	0.04	450	465	27	75
380	1.181	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	455	470	27	76
381	1.176	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	105	0.032	0.22	0.008	0.009	0.04	455	470	28	76
382	1.177	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.033	0.23	0.008	0.009	0.04	450	465	27	75
383	1.178	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	455	465	26	76
384	1.173	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	103	0.032	0.21	0.009	0.009	0.04	450	465	27	76
385	1.176	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	455	470	28	76
386	1.172	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.035	0.26	0.008	0.009	0.04	450	465	27	75
387	1.178	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	455	470	26	76
388	1.167	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	102	0.033	0.23	0.008	0.009	0.04	450	465	27	75
389	1.173	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	455	465	26	76
390	1.169	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	455	465	27	76
391	1.169	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	450	470	28	76
392	1.169	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.03	0.22	0.008	0.008	0.04	455	470	26	76
393	1.174	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	105	0.032	0.22	0.008	0.009	0.04	450	465	27	75
394	1.177	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.22	0.008	0.009	0.04	455	465	28	76
395	1.167	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.033	0.23	0.008	0.009	0.04	450	465	27	76
396	1.167	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	103	0.032	0.21	0.009	0.009	0.04	455	465	26	75
397	1.179	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	450	470	27	76
398	1.175	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	455	470	26	75
399	1.169	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	105	0.031	0.25	0.007	0.01	0.04	455	470	28	76
400	1.167	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.035	0.26	0.008	0.009	0.04	450	465	27	75
401	1.177	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	455	470	26	76
402	1.177	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	450	465	27	75
403	1.17	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	455	465	27	75
404	1.169	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	455	470	28	76
405	1.177	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	455	470	27	76



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size(mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	$R_{el}$ (N/mm <sup>2</sup> )	$R_m$ (N/mm <sup>2</sup> )	A (%)	HRB
406	1.174	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	102	0.032	0.21	0.009	0.009	0.04	455	470	28	75
407	1.17	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	450	465	27	75
408	1.17	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	109	0.035	0.26	0.008	0.009	0.04	455	470	26	76
409	1.174	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.03	0.22	0.008	0.008	0.04	450	465	27	75
410	1.174	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	455	470	27	76
411	1.172	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	105	0.032	0.22	0.008	0.009	0.04	455	470	28	76
412	1.169	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.033	0.23	0.008	0.009	0.04	450	465	27	75
413	1.175	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	455	465	26	76
414	1.174	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	103	0.032	0.21	0.009	0.009	0.04	450	465	27	76
415	1.178	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	455	470	28	76
416	1.179	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.035	0.26	0.008	0.009	0.04	450	465	27	75
417	1.173	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	455	470	26	76
418	1.173	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	102	0.033	0.23	0.008	0.009	0.04	450	465	27	75
419	1.177	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	455	465	26	76
420	1.183	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	455	465	27	76
421	1.173	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	450	470	28	76
422	1.172	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.03	0.22	0.008	0.008	0.04	455	470	26	76
423	1.175	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	105	0.032	0.22	0.008	0.009	0.04	450	465	27	75
424	1.173	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.22	0.008	0.009	0.04	455	465	28	76
425	1.172	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.033	0.23	0.008	0.009	0.04	450	465	27	76
426	1.174	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	103	0.032	0.21	0.009	0.009	0.04	455	465	26	75
427	1.176	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	450	470	27	76
428	1.178	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	455	470	26	75
429	1.174	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	105	0.031	0.25	0.007	0.01	0.04	455	470	28	76
430	1.175	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.035	0.26	0.008	0.009	0.04	450	465	27	75
431	1.175	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	455	470	26	76
432	1.164	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	450	465	27	75
433	1.178	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	455	465	27	75
434	1.178	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	455	470	28	76
435	1.169	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	455	470	27	76
436	1.171	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	102	0.032	0.21	0.009	0.009	0.04	455	470	28	75
437	1.164	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	450	465	27	75
438	1.165	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	109	0.035	0.26	0.008	0.009	0.04	455	470	26	76
439	1.166	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.03	0.22	0.008	0.008	0.04	450	465	27	75
440	1.167	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	455	470	27	76
441	1.169	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	105	0.032	0.22	0.008	0.009	0.04	455	470	28	76

捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size(mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass(g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>el</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB
442	1.168	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	107	0.033	0.23	0.008	0.009	0.04	450	465	27	75
443	1.169	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	455	465	26	76
444	1.171	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	103	0.032	0.21	0.009	0.009	0.04	450	465	27	76
445	1.169	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	455	470	28	76
446	1.166	200	0.33*895*2500	CHROMATED	72h	55	43.4	1.6	106	0.035	0.26	0.008	0.009	0.04	450	465	27	75
81	1.396	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	455	470	26	76
82	1.398	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	102	0.033	0.23	0.008	0.009	0.04	450	465	27	75
83	1.405	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	455	465	26	76
84	1.406	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	455	465	27	76
85	1.404	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	450	470	28	76
86	1.41	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	106	0.03	0.22	0.008	0.008	0.04	455	470	26	76
87	1.406	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	105	0.032	0.22	0.008	0.009	0.04	450	465	27	75
88	1.405	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.22	0.008	0.009	0.04	455	465	28	76
89	1.403	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.033	0.23	0.008	0.009	0.04	450	465	27	76
90	1.397	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	103	0.032	0.21	0.009	0.009	0.04	455	465	26	75
91	1.408	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	450	470	27	76
92	1.401	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	455	470	26	75
93	1.4	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	105	0.031	0.25	0.007	0.01	0.04	455	470	28	76
94	1.402	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	107	0.035	0.26	0.008	0.009	0.04	450	465	27	75
95	1.395	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	455	470	26	76
96	1.395	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	450	465	27	75
97	1.408	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	455	465	27	75
98	1.402	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	455	470	28	76
99	1.394	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	455	470	27	76
100	1.394	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	450	470	28	76
101	1.401	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	106	0.03	0.22	0.008	0.008	0.04	455	470	26	76
102	1.408	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	105	0.032	0.22	0.008	0.009	0.04	450	465	27	75
103	1.4	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.22	0.008	0.009	0.04	455	465	28	76
104	1.408	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.033	0.23	0.008	0.009	0.04	450	465	27	76
105	1.409	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	103	0.032	0.21	0.009	0.009	0.04	455	465	26	75
106	1.413	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	450	470	27	76
107	1.407	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	455	470	26	75
108	1.413	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	105	0.031	0.25	0.007	0.01	0.04	455	470	28	76
109	1.404	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	107	0.035	0.26	0.008	0.009	0.04	450	465	27	75
110	1.404	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	455	470	26	76
111	1.398	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	450	465	27	75



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size(mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>eL</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB
112	1.408	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	455	465	27	75
113	1.408	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	455	470	28	76
114	1.398	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	455	470	27	76
115	1.405	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	450	470	28	76
116	1.408	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	106	0.03	0.22	0.008	0.008	0.04	455	470	26	76
117	1.404	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	105	0.032	0.22	0.008	0.009	0.04	450	465	27	75
118	1.405	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.22	0.008	0.009	0.04	455	465	28	76
119	1.406	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.033	0.23	0.008	0.009	0.04	450	465	27	76
120	1.408	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	103	0.032	0.21	0.009	0.009	0.04	455	465	26	75
121	1.41	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	450	470	27	76
122	1.411	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	455	470	26	75
123	1.409	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	105	0.031	0.25	0.007	0.01	0.04	455	470	28	76
124	1.397	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	107	0.035	0.26	0.008	0.009	0.04	450	465	27	75
125	1.4	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	455	470	26	76
126	1.399	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	450	465	27	75
127	1.397	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	455	465	27	75
128	1.4	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	455	470	28	76
129	1.407	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	455	470	27	76
130	1.411	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	455	470	26	75
131	1.413	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	105	0.031	0.25	0.007	0.01	0.04	455	470	28	76
132	1.412	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	107	0.035	0.26	0.008	0.009	0.04	450	465	27	75
133	1.411	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	455	470	26	76
134	1.403	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	450	465	27	75
135	1.402	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	455	465	27	75
136	1.405	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	455	470	28	76
137	1.415	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	455	470	27	76
138	1.413	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	450	470	28	76
139	1.413	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	106	0.03	0.22	0.008	0.008	0.04	455	470	26	76
140	1.405	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	105	0.032	0.22	0.008	0.009	0.04	450	465	27	75
141	1.412	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.22	0.008	0.009	0.04	455	465	28	76
142	1.415	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.033	0.23	0.008	0.009	0.04	450	465	27	76
143	1.406	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	103	0.032	0.21	0.009	0.009	0.04	455	465	26	75
144	1.409	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	455	470	26	76
145	1.402	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	450	465	27	75
146	1.405	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	455	465	27	75
147	1.403	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	455	470	28	76

捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size (mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分 (%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION (%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>el</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB
148	1.407	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	455	470	27	76
149	1.403	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	450	470	28	76
150	1.405	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	106	0.03	0.22	0.008	0.008	0.04	455	470	26	76
151	1.411	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	105	0.032	0.22	0.008	0.009	0.04	450	465	27	75
152	1.411	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.22	0.008	0.009	0.04	455	465	28	76
153	1.404	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.033	0.23	0.008	0.009	0.04	450	465	27	76
154	1.399	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	103	0.032	0.21	0.009	0.009	0.04	455	465	26	75
155	1.407	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	455	470	26	76
156	1.408	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	450	465	27	75
157	1.411	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	455	465	27	75
158	1.409	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	455	470	28	76
159	1.401	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	455	470	27	76
160	1.408	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	450	470	28	76
161	1.412	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	106	0.03	0.22	0.008	0.008	0.04	455	470	26	76
162	1.411	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	105	0.032	0.22	0.008	0.009	0.04	450	465	27	75
163	1.41	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.22	0.008	0.009	0.04	455	465	28	76
164	1.409	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.033	0.23	0.008	0.009	0.04	450	465	27	76
165	1.405	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	103	0.032	0.21	0.009	0.009	0.04	455	465	26	75
166	1.408	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	455	470	26	76
167	1.408	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	450	465	27	75
168	1.404	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	455	465	27	75
169	1.406	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	455	470	28	76
170	1.397	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	455	470	27	76
171	1.417	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	450	470	28	76
172	1.414	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	106	0.03	0.22	0.008	0.008	0.04	455	470	26	76
173	1.412	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	105	0.032	0.22	0.008	0.009	0.04	450	465	27	75
174	1.413	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.22	0.008	0.009	0.04	455	465	28	76
175	1.413	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.033	0.23	0.008	0.009	0.04	450	465	27	76
176	1.413	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	103	0.032	0.21	0.009	0.009	0.04	455	465	26	75
177	1.406	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	455	465	27	75
178	1.408	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	455	470	28	76
179	1.407	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	455	470	27	76
180	1.406	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	450	470	28	76
569	1.401	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	106	0.03	0.22	0.008	0.008	0.04	455	470	26	76
570	0.729	101	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	105	0.032	0.22	0.008	0.009	0.04	450	465	27	75
1	1.689	200	0.33*895*3000	CHROMATED	72h	55	43.4	1.6	107	0.032	0.22	0.008	0.009	0.04	455	465	28	76

捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size(mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分 (%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	$R_{el}$ (N/mm <sup>2</sup> )	$R_m$ (N/mm <sup>2</sup> )	A (%)	HRB
2	1.687	200	0.33*895*3000	CHROMATED	72h	55	43.4	1.6	104	0.033	0.23	0.008	0.009	0.04	450	465	27	76
3	1.644	200	0.33*895*3000	CHROMATED	72h	55	43.4	1.6	103	0.032	0.21	0.009	0.009	0.04	455	465	26	75
4	1.638	200	0.33*895*3000	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	455	470	26	76
5	1.674	200	0.33*895*3000	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	450	465	27	75
6	1.635	200	0.33*895*3000	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	455	465	27	75
7	1.635	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	455	465	27	76
8	1.634	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	450	470	28	76
9	1.628	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	106	0.03	0.22	0.008	0.008	0.04	455	470	26	76
10	1.639	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	105	0.032	0.22	0.008	0.009	0.04	450	465	27	75
11	1.632	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.22	0.008	0.009	0.04	455	465	28	76
12	1.63	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.033	0.23	0.008	0.009	0.04	450	465	27	76
13	1.643	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	103	0.032	0.21	0.009	0.009	0.04	455	465	26	75
14	1.66	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	450	470	27	76
15	1.639	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	455	470	26	75
16	1.654	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	455	465	27	76
17	1.681	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	102	0.032	0.22	0.008	0.009	0.04	450	470	28	76
18	1.681	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	107	0.033	0.23	0.008	0.009	0.04	455	465	26	76
19	1.642	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	109	0.032	0.21	0.009	0.009	0.04	450	465	27	76
20	1.657	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	455	465	26	75
21	1.686	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	106	0.035	0.26	0.008	0.009	0.04	450	470	27	76
22	1.683	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	105	0.03	0.22	0.008	0.008	0.04	455	470	26	75
23	1.688	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.22	0.008	0.009	0.04	455	465	27	76
24	1.683	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	455	465	26	76
25	1.685	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	450	465	27	76
26	1.679	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	455	465	27	75
27	1.681	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	455	470	28	76
28	1.69	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	455	470	27	76
29	1.686	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	455	465	27	76
30	1.637	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	450	470	28	76
31	1.648	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	106	0.03	0.22	0.008	0.008	0.04	455	470	26	76
32	1.647	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	105	0.032	0.22	0.008	0.009	0.04	450	465	27	75
33	1.637	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.22	0.008	0.009	0.04	455	465	28	76
34	1.639	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.033	0.23	0.008	0.009	0.04	450	465	27	76
35	1.612	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	103	0.032	0.21	0.009	0.009	0.04	455	465	26	75
36	1.63	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	450	470	27	76
37	1.638	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	455	470	26	75

捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size (mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分 (%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>eL</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB
38	1.651	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	108	0.035	0.26	0.008	0.009	0.04	455	465	27	76
39	1.637	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	102	0.032	0.22	0.008	0.009	0.04	450	470	28	76
40	1.645	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	107	0.033	0.23	0.008	0.009	0.04	455	465	26	76
41	1.642	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	109	0.032	0.21	0.009	0.009	0.04	450	465	27	76
42	1.634	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	455	465	26	75
43	1.64	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	106	0.035	0.26	0.008	0.009	0.04	450	470	27	76
44	1.63	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	105	0.03	0.22	0.008	0.008	0.04	455	470	26	75
45	1.628	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.22	0.008	0.009	0.04	455	465	27	76
46	1.64	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	455	465	26	76
47	1.641	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	450	465	27	76
48	1.634	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	455	465	27	75
49	1.641	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	455	470	28	76
50	1.635	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	455	470	27	76
51	1.638	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.21	0.009	0.009	0.04	455	465	26	76
52	1.683	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	109	0.031	0.25	0.007	0.01	0.04	455	465	27	76
53	1.633	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	450	470	28	76
54	1.629	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	106	0.03	0.22	0.008	0.008	0.04	455	470	26	76
55	1.692	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	105	0.032	0.22	0.008	0.009	0.04	450	465	27	75
56	1.668	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	107	0.032	0.22	0.008	0.009	0.04	455	465	28	76
57	1.635	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.033	0.23	0.008	0.009	0.04	450	465	27	76
58	1.633	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	103	0.032	0.21	0.009	0.009	0.04	455	465	26	75
59	1.647	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	450	470	27	76
60	1.685	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	106	0.031	0.25	0.007	0.01	0.04	455	470	26	75
61	1.645	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	105	0.031	0.25	0.007	0.01	0.04	455	470	28	76
62	1.629	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	107	0.035	0.26	0.008	0.009	0.04	450	465	27	75
63	1.649	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.22	0.008	0.009	0.04	455	470	26	76
64	1.651	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	103	0.033	0.23	0.008	0.009	0.04	450	465	27	75
65	1.63	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.035	0.26	0.008	0.009	0.04	455	465	27	75
66	1.648	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	455	470	28	76
67	1.648	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	108	0.033	0.23	0.008	0.009	0.04	455	470	27	76
68	1.633	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	102	0.032	0.21	0.009	0.009	0.04	455	470	28	75
69	1.645	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	107	0.031	0.25	0.007	0.01	0.04	450	465	27	75
70	1.649	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	109	0.035	0.26	0.008	0.009	0.04	455	470	26	76
71	1.633	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.03	0.22	0.008	0.008	0.04	450	465	27	75
72	1.643	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	106	0.032	0.22	0.008	0.009	0.04	455	470	27	76
73	1.644	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	105	0.032	0.22	0.008	0.009	0.04	455	470	28	76



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size (mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分 (%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>el</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB
74	1.646	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	107	0.033	0.23	0.008	0.009	0.04	450	465	27	75
75	1.644	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.032	0.21	0.009	0.009	0.04	455	465	26	76
76	1.642	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	103	0.032	0.21	0.009	0.009	0.04	450	465	27	76
77	1.64	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	104	0.031	0.25	0.007	0.01	0.04	455	470	28	76
78	1.636	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	106	0.035	0.26	0.008	0.009	0.04	450	465	27	75
79	1.628	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	108	0.032	0.22	0.008	0.009	0.04	455	470	26	76
80	1.635	200	0.33*895*3500	CHROMATED	72h	55	43.4	1.6	102	0.033	0.23	0.008	0.009	0.04	450	465	27	75
	701.91																	

NOTE: 1、ReL : lower yield strength      Rm : tensile strength      A: percentage elongation after fracture  
2、1 N/mm<sup>2</sup>=1 MPa

证明本表所列制品，均依材料规格制造及试验，并符合规格之要求

WE HEREBY CERTIFY THAT THE MATERIAL DESCRIBED HEREIN HAS BEEN MANUFACTURED AND TESTED WITH SATISFACTORY RESULT IN ACCORDANCE WITH THE REQUIREMENT OF THE ABOVE MATERIAL SPECIFICATION.

质量部  
DEPARTM



XINGHAN

冠县众冠新材料有限公司

GUANXIAN ZHONGGUAN NEW MATERIALS CO., LTD.

地址: 中国山东聊城冠县新世纪工业园

Address: Guan Xian industry Park, Liaocheng, Shandong, China

# 产品质量证明书

## MILL'S TEST CERTIFICATE

订货单位 CUSTOMER		CUMIC STEEL LIMITED								钢号 GR.37	产品名称 PRODUCT					GALVALUME STEEL CORRUGATED SHEETS			
收货单位 PURCHASER		CUMIC STEEL LIMITED									签发日期 DATE					2024.11.20			
标准 SPECIFICATION		ASTM A792M									合同号 CONTRACT NO.					ZG202408134488			
捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size(mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES				
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>eL</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB	
2163	1.754	200	0.4*851*3000	CHROMATED	72h	55	43.4	1.6	155	0.03	0.22	0.008	0.008	0.04	665	665	4	92	
2168	1.742	200	0.4*851*3000	CHROMATED	72h	55	43.4	1.6	158	0.032	0.22	0.008	0.009	0.04	660	665	3	92	
2099	1.745	200	0.4*851*3000	CHROMATED	72h	55	43.4	1.6	154	0.032	0.22	0.008	0.009	0.04	665	665	4	93	
2162	1.744	200	0.4*851*3000	CHROMATED	72h	55	43.4	1.6	156	0.033	0.23	0.008	0.009	0.04	660	670	3	92	
2164	1.747	200	0.4*851*3000	CHROMATED	72h	55	43.4	1.6	157	0.032	0.21	0.009	0.009	0.04	660	670	3	93	
2165	1.737	200	0.4*851*3000	CHROMATED	72h	55	43.4	1.6	155	0.032	0.21	0.009	0.009	0.04	655	665	4	92	
2169	1.73	200	0.4*851*3000	CHROMATED	72h	55	43.4	1.6	153	0.031	0.25	0.007	0.01	0.04	660	665	3	92	
2171	1.732	200	0.4*851*3000	CHROMATED	72h	55	43.4	1.6	154	0.035	0.26	0.008	0.009	0.04	665	665	4	93	
2172	1.323	151	0.4*851*3000	CHROMATED	72h	55	43.4	1.6	156	0.032	0.22	0.008	0.009	0.04	660	670	3	92	
2159	1.742	200	0.4*851*3000	CHROMATED	72h	55	43.4	1.6	158	0.033	0.23	0.008	0.009	0.04	660	665	3	92	
2160	1.741	200	0.4*851*3000	CHROMATED	72h	55	43.4	1.6	155	0.032	0.21	0.009	0.009	0.04	655	665	4	92	
2161	1.749	200	0.4*851*3000	CHROMATED	72h	55	43.4	1.6	153	0.031	0.25	0.007	0.01	0.04	660	665	3	92	
2166	1.752	200	0.4*851*3000	CHROMATED	72h	55	43.4	1.6	154	0.035	0.26	0.008	0.009	0.04	665	665	4	93	
2167	1.747	200	0.4*851*3000	CHROMATED	72h	55	43.4	1.6	156	0.032	0.22	0.008	0.009	0.04	660	670	3	92	
2170	1.743	200	0.4*851*3000	CHROMATED	72h	55	43.4	1.6	158	0.033	0.23	0.008	0.009	0.04	660	665	3	92	
2173	2.146	200	0.4*851*3660	CHROMATED	72h	55	43.4	1.6	155	0.032	0.21	0.009	0.009	0.04	655	665	4	92	
2174	2.12	200	0.4*851*3660	CHROMATED	72h	55	43.4	1.6	153	0.031	0.25	0.007	0.01	0.04	660	665	3	92	
2175	2.148	200	0.4*851*3660	CHROMATED	72h	55	43.4	1.6	154	0.035	0.26	0.008	0.009	0.04	665	665	4	93	
2176	2.127	200	0.4*851*3660	CHROMATED	72h	55	43.4	1.6	156	0.032	0.22	0.008	0.009	0.04	660	670	3	92	
2177	2.115	200	0.4*851*3660	CHROMATED	72h	55	43.4	1.6	158	0.033	0.23	0.008	0.009	0.04	660	665	3	92	
2178	2.124	200	0.4*851*3660	CHROMATED	72h	55	43.4	1.6	155	0.032	0.21	0.009	0.009	0.04	655	665	4	92	
2179	2.128	200	0.4*851*3660	CHROMATED	72h	55	43.4	1.6	153	0.031	0.25	0.007	0.01	0.04	660	665	3	92	
2180	2.125	200	0.4*851*3660	CHROMATED	72h	55	43.4	1.6	154	0.035	0.26	0.008	0.009	0.04	665	665	4	93	
2184	2.125	200	0.4*851*3660	CHROMATED	72h	55	43.4	1.6	156	0.032	0.22	0.008	0.009	0.04	660	670	3	92	
2186	2.127	200	0.4*851*3660	CHROMATED	72h	55	43.4	1.6	158	0.033	0.23	0.008	0.009	0.04	660	665	3	92	
2188	2.11	200	0.4*851*3660	CHROMATED	72h	55	43.4	1.6	155	0.032	0.21	0.009	0.009	0.04	655	665	4	92	



捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size(mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>el</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB
2189	2.149	200	0.4*851*3000	CHROMATED	72h	55	43.4	1.6	154	0.035	0.26	0.008	0.009	0.04	665	665	4	93
2190	2.122	200	0.4*851*3000	CHROMATED	72h	55	43.4	1.6	156	0.032	0.22	0.008	0.009	0.04	660	670	3	92
2192	2.089	200	0.4*851*3000	CHROMATED	72h	55	43.4	1.6	158	0.033	0.23	0.008	0.009	0.04	660	665	3	92
2194	2.128	200	0.4*851*3660	CHROMATED	72h	55	43.4	1.6	155	0.032	0.21	0.009	0.009	0.04	655	665	4	92
2195	2.121	200	0.4*851*3660	CHROMATED	72h	55	43.4	1.6	153	0.031	0.25	0.007	0.01	0.04	660	665	3	92
2197	2.127	200	0.4*851*3660	CHROMATED	72h	55	43.4	1.6	154	0.035	0.26	0.008	0.009	0.04	665	665	4	93
2198	2.127	200	0.4*851*3660	CHROMATED	72h	55	43.4	1.6	156	0.032	0.22	0.008	0.009	0.04	660	670	3	92
2200	2.128	200	0.4*851*3660	CHROMATED	72h	55	43.4	1.6	158	0.033	0.23	0.008	0.009	0.04	660	665	3	92
2201	2.137	200	0.4*851*3660	CHROMATED	72h	55	43.4	1.6	155	0.032	0.21	0.009	0.009	0.04	655	665	4	92
2206	2.118	200	0.4*851*3660	CHROMATED	72h	55	43.4	1.6	153	0.031	0.25	0.007	0.01	0.04	660	665	3	92
2212	2.44	232	0.4*851*3660	CHROMATED	72h	55	43.4	1.6	154	0.035	0.26	0.008	0.009	0.04	665	665	4	93
2120	2.11	200	0.4*851*3660	CHROMATED	72h	55	43.4	1.6	156	0.032	0.22	0.008	0.009	0.04	660	670	3	92
2181	2.109	200	0.4*851*3660	CHROMATED	72h	55	43.4	1.6	158	0.033	0.23	0.008	0.009	0.04	660	665	3	92
2182	2.107	200	0.4*851*3660	CHROMATED	72h	55	43.4	1.6	154	0.035	0.26	0.008	0.009	0.04	665	665	4	93
2183	2.125	200	0.4*851*3660	CHROMATED	72h	55	43.4	1.6	156	0.032	0.22	0.008	0.009	0.04	660	670	3	92
2185	2.149	200	0.4*851*3660	CHROMATED	72h	55	43.4	1.6	158	0.033	0.23	0.008	0.009	0.04	660	665	3	92
2187	2.127	200	0.4*851*3660	CHROMATED	72h	55	43.4	1.6	155	0.032	0.21	0.009	0.009	0.04	655	665	4	92
2191	2.11	200	0.4*851*3660	CHROMATED	72h	55	43.4	1.6	153	0.031	0.25	0.007	0.01	0.04	660	665	3	92
2210	2.124	200	0.4*851*3660	CHROMATED	72h	55	43.4	1.6	154	0.035	0.26	0.008	0.009	0.04	665	665	4	93
2193	2.13	200	0.4*851*3660	CHROMATED	72h	55	43.4	1.6	156	0.032	0.22	0.008	0.009	0.04	660	670	3	92
2196	2.131	200	0.4*851*3660	CHROMATED	72h	55	43.4	1.6	158	0.033	0.23	0.008	0.009	0.04	660	665	3	92
2199	2.124	200	0.4*851*3660	CHROMATED	72h	55	43.4	1.6	155	0.032	0.21	0.009	0.009	0.04	655	665	4	92
2202	2.131	200	0.4*851*3660	CHROMATED	72h	55	43.4	1.6	153	0.031	0.25	0.007	0.01	0.04	660	665	3	92
2203	2.127	200	0.4*851*3660	CHROMATED	72h	55	43.4	1.6	154	0.035	0.26	0.008	0.009	0.04	665	665	4	93
2204	2.124	200	0.4*851*3660	CHROMATED	72h	55	43.4	1.6	156	0.032	0.22	0.008	0.009	0.04	660	670	3	92
2205	2.139	200	0.4*851*3660	CHROMATED	72h	55	43.4	1.6	158	0.033	0.23	0.008	0.009	0.04	660	665	3	92
2207	2.105	200	0.4*851*3660	CHROMATED	72h	55	43.4	1.6	155	0.032	0.21	0.009	0.009	0.04	655	665	4	92
2208	2.121	200	0.4*851*3660	CHROMATED	72h	55	43.4	1.6	153	0.031	0.25	0.007	0.01	0.04	660	665	3	92
2209	2.131	200	0.4*851*3660	CHROMATED	72h	55	43.4	1.6	154	0.035	0.26	0.008	0.009	0.04	665	665	4	93
2211	2.122	200	0.4*851*3660	CHROMATED	72h	55	43.4	1.6	156	0.032	0.22	0.008	0.009	0.04	660	670	3	92
	113.155																	

NOTE: 1、ReL : lower yield strength      Rm : tensile strength      A: percentage elongation after fracture  
2、1 N/mm2=1 MPa

证明本表所列制品，均依材料规格制造及试验，并符合规格之要求  
WE HEREBY CERTIFY THAT THE MATERIAL DESCRIBED HEREIN HAS BEEN MANUFACTURED AND TESTED WITH SATISFACTORY RESULT IN ACCORDANCE  
WITH THE REQUIREMENT OF THE ABOVE MATERIAL SPECIFICATION.



XINGHAN

MILL'S TEST CERTIFICATE  
产品质量证明书

冠县众冠新材料有限公司

GUANXIAN ZHONGGUAN NEW MATERIALS CO.,LTD

地址: 中国山东聊城冠县新世纪工业园

Address: Guan Xian industry Park, Liaocheng, Shandong, China

定货单位 CUSTOMER			CUMIC STEEL LIMITED								合同号 CONTRACT NO.				ZG202408134488										
产品名称 PRODUCT			PREPAINTED GALVALUME STEEL CORRUGATED SHEETS								证明书日期 T/C ISSUE DATE				2024.11.20										
捆号 PACK NO.	捆重 NET WEIGHT	片数 PIECE	规格及数量 MATERIAL DESCRIPTION			化学成分 CHEMICAL COMPOSITION% (熔炼分析 HEAT ANALYSIS)					力学性能 MECHANIC PROPERTIES				镀层重量 COATIN	涂层性能 COAT PROPERTY									
			规格mm SIZE	面漆 Top paint	背漆 Back paint	C	Mn	P	S	Si	R <sub>el</sub>	R <sub>m</sub>	A	硬度 HARDNESS		两面 BOTH	面漆涂 层厚度 facial coating	背漆涂 层厚度 Back coating	面漆涂 层T弯 T-bend	背漆涂 层T弯 T-bend	反向冲 击 impact test	涂层擦 拭 wipe coating	光泽 gloss	涂层色 差 chromatici ty difference	
2356	2.067	200	0,4*1219*3000	RAL9017	RAL9002	0.035	0.26	0.008	0.009	0.04	325	385	31	62.5	154	20	8	2T	2T	9J	120/80	57.8	0.31		
2357	2.082	200	0,4*1219*3000	RAL9017	RAL9002	0.035	0.26	0.008	0.009	0.04	330	388	32	62	152	20	8	2T	2T	9J	120/80	58.6	0.31		
2358	2.082	200	0,4*1219*3000	RAL9017	RAL9002	0.035	0.26	0.008	0.009	0.04	330	380	30	63	156	20	8	2T	2T	9J	120/80	58.5	0.31		
2359	2.076	200	0,4*1219*3000	RAL9017	RAL9002	0.035	0.26	0.008	0.009	0.04	333	385	32	64	155	20	8	2T	2T	9J	120/80	59.6	0.33		
2360	2.069	200	0,4*1219*3000	RAL9017	RAL9002	0.035	0.26	0.008	0.009	0.04	325	385	31	62.5	155	20	8	2T	2T	9J	120/80	57.8	0.31		
2361	2.062	200	0,4*1219*3000	RAL9017	RAL9002	0.035	0.26	0.008	0.009	0.04	330	380	30	63	152	20	8	2T	2T	9J	120/80	57.8	0.31		
2362	2.071	200	0,4*1219*3000	RAL9017	RAL9002	0.035	0.26	0.008	0.009	0.04	333	385	31	64	154	20	8	2T	2T	9J	120/80	58.6	0.31		
2363	2.069	200	0,4*1219*3000	RAL9017	RAL9002	0.035	0.26	0.008	0.009	0.04	325	385	31	62.5	152	20	8	2T	2T	9J	120/80	58.5	0.32		
2364	2.054	200	0,4*1219*3000	RAL9017	RAL9002	0.035	0.26	0.008	0.009	0.04	330	388	32	62	156	20	8	2T	2T	9J	120/80	59.6	0.31		
2365	2.078	200	0,4*1219*3000	RAL9017	RAL9002	0.035	0.26	0.008	0.009	0.04	330	380	30	63	155	20	8	2T	2T	9J	120/80	57.8	0.31		
2366	2.05	200	0,4*1219*3000	RAL9017	RAL9002	0.035	0.26	0.008	0.009	0.04	333	385	32	64	155	20	8	2T	2T	9J	120/80	57.8	0.31		
2367	2.086	200	0,4*1219*3000	RAL9017	RAL9002	0.035	0.26	0.008	0.009	0.04	325	385	31	62.5	152	20	8	2T	2T	9J	120/80	58.6	0.32		
2368	2.072	200	0,4*1219*3000	RAL9017	RAL9002	0.035	0.26	0.008	0.009	0.04	330	380	30	63	154	20	8	2T	2T	9J	120/80	58.5	0.31		
2369	2.071	200	0,4*1219*3000	RAL9017	RAL9002	0.035	0.26	0.008	0.009	0.04	333	385	31	64	152	20	8	2T	2T	9J	120/80	59.6	0.33		
2370	2.084	200	0,4*1219*3000	RAL9017	RAL9002	0.035	0.26	0.008	0.009	0.04	325	385	31	62.5	156	20	8	2T	2T	9J	120/80	57.8	0.31		
2371	2.079	200	0,4*1219*3000	RAL9017	RAL9002	0.035	0.26	0.008	0.009	0.04	330	388	32	62	155	20	8	2T	2T	9J	120/80	57.8	0.31		
2372	2.069	200	0,4*1219*3000	RAL9017	RAL9002	0.035	0.26	0.008	0.009	0.04	330	380	30	63	155	20	8	2T	2T	9J	120/80	58.6	0.31		
2373	2.076	200	0,4*1219*3000	RAL9017	RAL9002	0.035	0.26	0.008	0.009	0.04	333	385	32	64	152	20	8	2T	2T	9J	120/80	58.5	0.32		
2374	2.062	200	0,4*1219*3000	RAL9017	RAL9002	0.035	0.26	0.008	0.009	0.04	325	385	31	62.5	154	20	8	2T	2T	9J	120/80	59.6	0.31		



**XINGHAN**

**MILL'S TEST CERTIFICATE**  
**产品质量证明书**

冠县众冠新材料有限公司

GUANXIAN ZHONGGUAN NEW MATERIALS CO.,LTD

地址: 中国山东聊城冠县新世纪工业园

Address: Guan Xian industry Park, Liaocheng, Shandong, China

定货单位 CUSTOMER			CUMIC STEEL LIMITED								合同号 CONTRACT NO.				ZG202408134488										
产品名称 NAME OF PRODUCT			PREPAINTED GALVALUME STEEL CORRUGATED SHEETS								证明书日期 T/C ISSUE DATE				2024.11.20										
捆号 PACK NO.	捆重 NET WEIGHT	片数 PIECE	规格及数量 MATERIAL DESCRIPTION			化学成分 CHEMICAL COMPOSITION% (熔炼分析 HEAT ANALYSIS)					力学性能 MECHANIC PROPERTIES				镀层重量 COATIN	涂层性能 COAT PROPERTY									
			规格mm SIZE	面漆 Top paint	背漆 Back paint	C	Mn	P	S	Si	R <sub>el</sub>	R <sub>m</sub>	A	硬度 HARDNESS		两面 BOTH	面漆涂 层厚度 facial coating	背漆涂 层厚度 Back coating	面漆涂 层T弯 T-bend	背漆涂 层T弯 T-bend	反向冲 击 impact test	涂层擦 拭 wipe coating	光泽 gloss	涂层色 差 chromatici ty difference	
2375	2.074	200	0,4*1219*3000	RAL9017	RAL9002	0.035	0.26	0.008	0.009	0.04	330	380	30	63	152	20	8	2T	2T	9J	120/80	57.8	0.31		
2376	2.07	200	0,4*1219*3000	RAL9017	RAL9002	0.035	0.26	0.008	0.009	0.04	333	385	31	64	156	20	8	2T	2T	9J	120/80	57.8	0.31		
2377	2.08	200	0,4*1219*3000	RAL9017	RAL9002	0.035	0.26	0.008	0.009	0.04	325	385	31	62.5	155	20	8	2T	2T	9J	120/80	58.6	0.32		
2378	2.064	200	0,4*1219*3000	RAL9017	RAL9002	0.035	0.26	0.008	0.009	0.04	333	385	31	64	155	20	8	2T	2T	9J	120/80	58.5	0.31		
2379	2.827	276	0,4*1219*3000	RAL9017	RAL9002	0.035	0.26	0.008	0.009	0.04	325	385	31	62.5	152	20	8	2T	2T	9J	120/80	59.6	0.33		
	50.474																								

NOTE: Rel : lower yield strength      Rm : tensile strength      A: percentage elongation after fracture

证明本表所列制品, 均依材料规格制造及试验, 并符合规格之要求

WE HEREBY CERTIFY THAT THE MATERIAL DESCRIBED HEREIN HAS BEEN MANUFACTURED AND TESTED WITH SATISFACTORY RESULT IN ACCORDANCE WITH THE REQUIREMENT OF THE ABOVE MATERIAL SPECIFICATION



**XNGHAN**

冠县众冠新材料有限公司

# 产品质量证明书

## MILL'S TEST CERTIFICATE

GUANXIAN ZHONGGUAN NEW MATERIALS CO., LTD.

地址: 中国山东聊城冠县新世纪工业园

Address: Guan Xian industry Park, Liaocheng, Shandong, China

订货单位 CUSTOMER		CUMIC STEEL LIMITED								钢号	GR.37					产品名称	PRODUCT		GALVALUME STEEL PLAIN SHEETS	
收货单位 PURCHASER		CUMIC STEEL LIMITED									签发日期 OF ISSUE	DATE					2024.11.20			
标准 SPECIFICATION		ASTM A792M									合同号 NO.	CONTRACT					ZG202408134488			
捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size (mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分 (%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION (%)					力学性能 MECHANIC PROPERTIES					
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>el</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB		
2289	1.572	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	155	0.032	0.21	0.009	0.009	0.04	330	380	30	63		
2290	1.572	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	158	0.031	0.25	0.007	0.01	0.04	333	385	31	64		
2291	1.566	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	154	0.035	0.26	0.008	0.009	0.04	325	385	31	62.5		
2292	1.575	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	156	0.03	0.22	0.008	0.008	0.04	330	388	32	62		
2293	1.574	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	157	0.032	0.22	0.008	0.009	0.04	330	380	30	63		
2294	1.573	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	155	0.032	0.22	0.008	0.009	0.04	333	385	32	64		
2295	1.576	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	153	0.033	0.23	0.008	0.009	0.04	325	385	31	62.5		
2296	1.524	194	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	155	0.032	0.21	0.009	0.009	0.04	330	380	30	63		
2297	1.574	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	158	0.031	0.25	0.007	0.01	0.04	333	385	31	64		
2298	1.568	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	154	0.035	0.26	0.008	0.009	0.04	325	385	31	62.5		
2299	1.562	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	156	0.03	0.22	0.008	0.008	0.04	330	388	32	62		
2300	1.581	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	157	0.032	0.22	0.008	0.009	0.04	330	380	30	63		
2301	1.577	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	155	0.032	0.22	0.008	0.009	0.04	333	385	32	64		
2302	1.577	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	153	0.033	0.23	0.008	0.009	0.04	325	385	31	62.5		
2303	1.581	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	155	0.032	0.21	0.009	0.009	0.04	330	380	30	63		
2304	1.572	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	158	0.031	0.25	0.007	0.01	0.04	333	385	31	64		
2305	1.57	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	154	0.035	0.26	0.008	0.009	0.04	325	385	31	62.5		
2306	1.564	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	156	0.03	0.22	0.008	0.008	0.04	330	388	32	62		
2307	1.583	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	157	0.032	0.22	0.008	0.009	0.04	330	380	30	63		
2308	1.588	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	155	0.032	0.22	0.008	0.009	0.04	333	385	32	64		
2309	1.584	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	153	0.033	0.23	0.008	0.009	0.04	325	385	31	62.5		
2310	1.583	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	155	0.032	0.21	0.009	0.009	0.04	330	380	30	63		
2311	1.583	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	158	0.031	0.25	0.007	0.01	0.04	333	385	31	64		
2312	1.574	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	154	0.035	0.26	0.008	0.009	0.04	325	385	31	62.5		
2313	1.566	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	156	0.03	0.22	0.008	0.008	0.04	330	388	32	62		
2314	1.591	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	157	0.032	0.22	0.008	0.009	0.04	330	380	30	63		
2315	1.572	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	155	0.032	0.22	0.008	0.009	0.04	333	385	32	64		

捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size (mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分 (%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>eL</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB
2316	1.584	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	153	0.033	0.23	0.008	0.009	0.04	325	385	31	62.5
2317	1.572	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	155	0.032	0.21	0.009	0.009	0.04	330	380	30	63
2318	1.571	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	158	0.031	0.25	0.007	0.01	0.04	333	385	31	64
2319	1.574	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	154	0.035	0.26	0.008	0.009	0.04	325	385	31	62.5
2320	1.566	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	156	0.03	0.22	0.008	0.008	0.04	330	388	32	62
2321	1.576	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	157	0.032	0.22	0.008	0.009	0.04	330	380	30	63
2322	1.568	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	155	0.032	0.22	0.008	0.009	0.04	333	385	32	64
2323	1.566	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	153	0.033	0.23	0.008	0.009	0.04	325	385	31	62.5
2324	1.572	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	155	0.032	0.21	0.009	0.009	0.04	330	380	30	63
2325	1.577	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	158	0.031	0.25	0.007	0.01	0.04	333	385	31	64
2326	1.586	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	154	0.035	0.26	0.008	0.009	0.04	325	385	31	62.5
2327	1.573	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	156	0.03	0.22	0.008	0.008	0.04	330	388	32	62
2328	1.577	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	157	0.032	0.22	0.008	0.009	0.04	330	380	30	63
2329	1.581	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	155	0.032	0.22	0.008	0.009	0.04	333	385	32	64
2330	1.574	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	153	0.033	0.23	0.008	0.009	0.04	325	385	31	62.5
2331	1.564	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	155	0.032	0.21	0.009	0.009	0.04	330	380	30	63
2332	1.572	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	158	0.031	0.25	0.007	0.01	0.04	333	385	31	64
2333	1.572	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	154	0.035	0.26	0.008	0.009	0.04	325	385	31	62.5
2334	1.584	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	156	0.03	0.22	0.008	0.008	0.04	330	388	32	62
2335	1.57	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	157	0.032	0.22	0.008	0.009	0.04	330	380	30	63
2336	1.58	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	155	0.032	0.22	0.008	0.009	0.04	333	385	32	64
2337	1.574	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	153	0.033	0.23	0.008	0.009	0.04	325	385	31	62.5
2338	1.554	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	155	0.032	0.21	0.009	0.009	0.04	330	380	30	63
2339	1.577	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	158	0.031	0.25	0.007	0.01	0.04	333	385	31	64
2340	1.569	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	154	0.035	0.26	0.008	0.009	0.04	325	385	31	62.5
2341	1.592	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	156	0.03	0.22	0.008	0.008	0.04	330	388	32	62
2342	1.577	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	157	0.032	0.22	0.008	0.009	0.04	330	380	30	63
2343	1.572	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	155	0.032	0.22	0.008	0.009	0.04	333	385	32	64
2344	1.571	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	153	0.033	0.23	0.008	0.009	0.04	325	385	31	62.5
2345	1.57	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	154	0.032	0.21	0.009	0.009	0.04	330	380	32	62
2346	1.581	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	156	0.032	0.21	0.009	0.009	0.04	330	380	30	63
2347	1.572	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	158	0.031	0.25	0.007	0.01	0.04	333	385	32	64
2348	1.568	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	155	0.035	0.26	0.008	0.009	0.04	330	380	30	63
2349	1.575	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	158	0.032	0.22	0.008	0.009	0.04	333	385	31	64
2350	1.584	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	154	0.032	0.22	0.008	0.009	0.04	325	380	31	62.5
2351	1.584	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	156	0.033	0.23	0.008	0.009	0.04	330	385	32	62
2352	1.565	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	157	0.032	0.21	0.009	0.009	0.04	330	385	31	63
2353	1.574	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	155	0.031	0.25	0.007	0.01	0.04	333	388	32	64
2354	1.57	200	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	153	0.035	0.26	0.008	0.009	0.04	325	380	31	62.5

捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size(mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分(%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>el</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB
2355	1.52	194	0.35*1000*3000	CHROMATED	72h	55	43.4	1.6	154	0.03	0.22	0.008	0.008	0.04	330	385	32	62
2221	1.829	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	156	0.032	0.22	0.008	0.009	0.04	330	385	30	63
2222	1.83	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	158	0.035	0.26	0.008	0.009	0.04	333	380	32	64
2223	1.821	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	155	0.032	0.22	0.008	0.009	0.04	325	380	31	62.5
2224	1.828	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	158	0.033	0.23	0.008	0.009	0.04	330	385	32	62
2225	1.83	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	154	0.032	0.21	0.009	0.009	0.04	330	380	30	63
2226	1.825	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	156	0.031	0.25	0.007	0.01	0.04	333	385	32	64
2227	1.826	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	157	0.035	0.26	0.008	0.009	0.04	333	388	32	64
2228	1.828	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	155	0.03	0.22	0.008	0.008	0.04	325	380	31	62.5
2229	1.835	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	153	0.032	0.22	0.008	0.009	0.04	330	385	32	62
2230	1.844	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	154	0.032	0.22	0.008	0.009	0.04	330	385	30	63
2231	1.826	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	156	0.033	0.23	0.008	0.009	0.04	333	380	32	64
2232	1.826	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	158	0.032	0.21	0.009	0.009	0.04	325	380	31	62.5
2233	1.825	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	155	0.032	0.21	0.009	0.009	0.04	330	385	32	62
2234	1.83	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	158	0.035	0.26	0.008	0.009	0.04	333	380	32	64
2235	1.829	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	155	0.032	0.22	0.008	0.009	0.04	325	380	31	62.5
2236	1.824	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	158	0.033	0.23	0.008	0.009	0.04	330	385	32	62
2237	1.839	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	154	0.032	0.21	0.009	0.009	0.04	330	380	30	63
2238	1.836	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	156	0.031	0.25	0.007	0.01	0.04	333	385	32	64
2239	1.834	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	157	0.035	0.26	0.008	0.009	0.04	333	388	32	64
2240	1.823	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	155	0.03	0.22	0.008	0.008	0.04	325	380	31	62.5
2241	1.823	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	153	0.032	0.22	0.008	0.009	0.04	330	385	32	62
2242	1.832	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	154	0.032	0.22	0.008	0.009	0.04	330	385	30	63
2243	1.819	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	156	0.033	0.23	0.008	0.009	0.04	333	380	32	64
2244	1.823	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	158	0.032	0.21	0.009	0.009	0.04	325	380	31	62.5
2245	1.818	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	155	0.032	0.21	0.009	0.009	0.04	330	385	32	62
2246	1.82	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	158	0.035	0.26	0.008	0.009	0.04	333	380	32	64
2247	1.815	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	155	0.032	0.22	0.008	0.009	0.04	325	380	31	62.5
2248	1.827	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	158	0.033	0.23	0.008	0.009	0.04	330	385	32	62
2249	1.835	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	154	0.032	0.21	0.009	0.009	0.04	330	380	30	63
2250	1.836	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	156	0.031	0.25	0.007	0.01	0.04	333	385	32	64
2251	1.837	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	157	0.035	0.26	0.008	0.009	0.04	333	388	32	64
2252	1.838	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	155	0.03	0.22	0.008	0.008	0.04	325	380	31	62.5
2253	1.816	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	153	0.032	0.22	0.008	0.009	0.04	330	385	32	62
2254	1.815	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	154	0.032	0.22	0.008	0.009	0.04	330	385	30	63
2255	1.825	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	156	0.033	0.23	0.008	0.009	0.04	333	380	32	64
2256	1.823	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	158	0.032	0.21	0.009	0.009	0.04	325	380	31	62.5
2257	1.832	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	155	0.032	0.21	0.009	0.009	0.04	330	385	32	62
2258	1.822	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	155	0.035	0.26	0.008	0.009	0.04	330	380	30	63

捆号 PACK No.	重量 WEIGHT	片数 PIECE	成品规格 Size (mm)	表面处理 surface treatment	盐雾试验 salt spray test	镀层成分 (%) The composition of coating			镀层质量 coating mass (g/m <sup>2</sup> )	化学成分 CHEMICAL COMPOSITION(%)					力学性能 MECHANIC PROPERTIES			
						Al	Zn	Si		C	Mn	P	S	Si	R <sub>eL</sub> (N/mm <sup>2</sup> )	R <sub>m</sub> (N/mm <sup>2</sup> )	A (%)	HRB
2259	1.819	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	158	0.032	0.22	0.008	0.009	0.04	333	385	31	64
2260	1.83	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	154	0.032	0.22	0.008	0.009	0.04	325	380	31	62.5
2261	1.826	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	156	0.033	0.23	0.008	0.009	0.04	330	385	32	62
2262	1.825	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	157	0.032	0.21	0.009	0.009	0.04	330	385	31	63
2263	1.829	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	155	0.031	0.25	0.007	0.01	0.04	333	388	32	64
2264	1.83	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	153	0.035	0.26	0.008	0.009	0.04	325	380	31	62.5
2265	1.826	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	154	0.03	0.22	0.008	0.008	0.04	330	385	32	62
2266	1.827	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	156	0.032	0.22	0.008	0.009	0.04	330	385	30	63
2267	1.824	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	158	0.035	0.26	0.008	0.009	0.04	333	380	32	64
2268	1.824	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	155	0.032	0.22	0.008	0.009	0.04	325	380	31	62.5
2269	1.824	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	158	0.033	0.23	0.008	0.009	0.04	330	385	32	62
2270	1.823	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	154	0.032	0.21	0.009	0.009	0.04	330	380	30	63
2271	1.832	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	156	0.031	0.25	0.007	0.01	0.04	333	385	32	64
2272	1.82	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	157	0.035	0.26	0.008	0.009	0.04	333	388	32	64
2273	1.819	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	155	0.03	0.22	0.008	0.008	0.04	325	380	31	62.5
2274	1.82	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	153	0.032	0.22	0.008	0.009	0.04	330	385	32	62
2275	1.826	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	154	0.032	0.22	0.008	0.009	0.04	330	385	30	63
2276	1.822	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	156	0.033	0.23	0.008	0.009	0.04	333	380	32	64
2277	1.821	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	158	0.032	0.21	0.009	0.009	0.04	325	380	31	62.5
2278	1.827	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	155	0.032	0.21	0.009	0.009	0.04	330	385	32	62
2279	1.824	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	158	0.031	0.25	0.007	0.01	0.04	330	380	30	63
2280	1.82	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	154	0.032	0.21	0.009	0.009	0.04	330	380	32	62
2281	1.821	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	156	0.032	0.21	0.009	0.009	0.04	330	380	30	63
2282	1.813	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	158	0.031	0.25	0.007	0.01	0.04	333	385	32	64
2283	1.817	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	155	0.035	0.26	0.008	0.009	0.04	330	380	30	63
2284	1.827	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	158	0.032	0.22	0.008	0.009	0.04	333	385	31	64
2285	1.817	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	154	0.032	0.22	0.008	0.009	0.04	325	380	31	62.5
2286	1.818	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	156	0.033	0.23	0.008	0.009	0.04	330	385	32	62
2287	1.825	200	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	157	0.032	0.21	0.009	0.009	0.04	330	385	31	63
2288	1.953	215	0.4*1000*3000	CHROMATED	72h	55	43.4	1.6	155	0.031	0.25	0.007	0.01	0.04	333	388	32	64
	229.663																	

NOTE: 1、ReL : lower yield strength      Rm : tensile strength      A: percentage elongation after fracture  
2、1 N/mm<sup>2</sup>=1 MPa

证明本表所列制品，均依材料规格制造及试验，并符合规格之要求

WE HEREBY CERTIFY THAT THE MATERIAL DESCRIBED HEREIN HAS BEEN MANUFACTURED AND TESTED WITH SATISFACTORY RESULT IN ACCORDANCE WITH THE REQUIREMENT OF THE ABOVE MATERIAL SPECIFICATION.

质量部  
DEPARTM

