



日钢营口中板有限公司
RIZHAO STEEL YINGKOU MEDIUM PLATE CO.,LTD.
辽宁省营口市老边区冶金街/115005
Yejinstreet,Laobianidistrict,Yingkou,Liaoning,P.R.China/115005
TEL:0417-3256081 FAX:0417-3256057 NO.:DT2101501/A

产品质量证明书
INSPECTION-CERTIFICATE



订货单位 PURCHASER	HYUNDAICORPORATION	普通碳素结构钢 General carbon structural steel	
收货单位 CONSIGNEE	HYUNDAICORPORATION	YGR1ZANN240583008-01	
技术标准/牌号 SPEC/GRADE	ASTM A36/A36M;ASTM A36	热轧(AR)	签发日期 DATE OF ISSUE
		20240711	
车号 TRAINNO.	240711Z00382		

炉号 HEATNO.	批号 LOTNO.	钢板号 PLATENO.	规格 (MM) DIMENSION	数量 QTY	重量 WEIGHT kg	分析区域 AA	化学成分 CHEMICAL ANALYSIS %														B0A01	B0A02	B0A03	B0A04	B0B01	A0C01	A0C012	A0C013	A0C02
							C	Si	Mn	P	S	CEV	Cr	Mo	V	Ni	Cu	Nb	Ti	屈服强度 MPa Rp0.2	抗拉强度 MPa Rm	断后伸长率 %	断后伸长率 B5	屈服强度 MPa d=3a 180°	冲击 J	冲击 J	冲击 J	冲击 J	
							$\times 10^{-3}$	$\times 10^{-3}$	$\times 10^{-3}$	$\times 10^{-4}$	$\times 10^{-4}$	$\times 10^{-2}$	$\times 10^{-3}$	$\times 10^{-4}$	$\times 10^{-4}$														
24111331A	S47100011	S4709462101	8x2440x12000	1	1.839	L	138	137	835	180	92	30	80	20	2	180	7	20	20	304	445	24	0.68	CK	89	72	76	79	
24111331A	S47100011	S4709462201	8x2440x12000	1	1.839	L	138	137	835	180	92	30	80	20	2	180	7	20	20	304	445	24	0.68	CK	89	72	76	79	
24111331A	S47100011	S4709462301	8x2440x12000	1	1.839	L	138	137	835	180	92	30	80	20	2	180	7	20	20	304	445	24	0.68	CK	89	72	76	79	
24111331A	S47100011	S4709463101	8x2440x12000	1	1.839	L	138	137	835	180	92	30	80	20	2	180	7	20	20	304	445	24	0.68	CK	89	72	76	79	
24111331A	S47100011	S4709463201	8x2440x12000	1	1.839	L	138	137	835	180	92	30	80	20	2	180	7	20	20	304	445	24	0.68	CK	89	72	76	79	
24111331A	S47100011	S4709463301	8x2440x12000	1	1.839	L	138	137	835	180	92	30	80	20	2	180	7	20	20	304	445	24	0.68	CK	89	72	76	79	
合计(TOTAL):				6	11.034																								

注释
NOTES

L: 熔炼成分 SMELTING COMPOSITION
拉伸标距(GAUGE LENGTH) Lo=200 mm
A0C冲击试验IMPACT TEST: 20℃, 纵向LONGITUDINAL,
近表 CLOSE TO SURFACE, 尺寸SIZE10*5*55
B0A01=YIELD STRENGTH
B0A02=TENSILE STRENGTH
B0A03=PERCENTAGE ELONGATION AFTER FRACTURE

B0A04=YIELD STRENGTH RATIO
B0B01=BEND TEST
A0C01=IMPACT TEST A
A0C012=IMPACT TEST B
A0C013=IMPACT TEST C
A0C02=IMPACT AVERAGE

According to EN 10204 3.1

本产品已按照标准要求进行制造和检验, 其结果符合要求, 特此证明。
WE HEREBY CERTIFY THAT MATERIAL DESCRIBED HAS MANUFACTURED AND TESTED WITH SATISFACTORY RESULTS IN ACCORDANCE WITH THE REQUIREMENTS OF THE ABOVE MATERIAL SPECIFICATION

冶金技术处处长
DIRECTOR OF METALLURGICAL DEPARTMENT

殷新刚

