



日钢营口中板有限公司
RIZHAO STEEL YINGKOU MEDIUM PLATE CO.,LTD.
辽宁省营口市老边区冶金街/115005
Yejinstreet,Laobianidistrict,Yingkou,Liaoning,P.R.China/115005
TEL:0417-3256081 FAX:0417-3256057 NO.:DT2101501/A

产品质量证明书
INSPECTION CERTIFICATE



订货单位 PURCHASER	CUMIC STEEL LIMITED	船川钢板 Hull Steel plate
收货单位 CONSIGNEE	CUMIC STEEL LIMITED	YGR1ZANN240783010-03
技术标准/牌号 SPEC/GRADE	LR RULES ; LRB	正火轧制(NR) 240831Z00414
车号 TRAIN NO.		签发日期 DATE OF ISSUE 20240904
		控制号 CONTROL NUMBER DLN2401071



炉号 HEAT NO.	批号 LOT NO.	钢板号 PLATENO.	分段号 SECTION NO.	规格 (MM) DIMENSION	数量 QTY	重量 WEIGHT kg	化学成分 CHEMICAL ANALYSIS %														力学性能					
							C	Si	Mn	P	S	Als	Ti	Nb	Ni	Cr	Cu	Mo	CeqA	B0A01 屈服强度 MPa Rel	B0A02 抗拉强度 MPa Rm	B0A03 断后伸长率 %	A0C01 冲击值 J	A0C012 冲击值 J	A0C013 冲击值 J	A0C02 冲击平均值 J
24206728C	S48300136	S4830183101		10x2440x12000	1	2.298	135	22	781	12	4	37	160	20	180	32	7	10	265	300	432	34.5	150	115	120	128
24206728C	S48300136	S4830183201		10x2440x12000	1	2.298	135	22	781	12	4	37	160	20	180	32	7	10	265	300	432	34.5	150	115	120	128
24206728C	S48300136	S4830183301		10x2440x12000	1	2.298	135	22	781	12	4	37	160	20	180	32	7	10	265	300	432	34.5	150	115	120	128
合计(TOTAL):					3	6.894																				

注释 NOTES	L: 熔炼成分 SMELTING COMPOSITION 拉伸标距(GAUGE LENGTH) Lo=5.65√S0 mm A0C冲击试验IMPACT TEST: 0C, 纵向LONGITUDINAL, 近表 CLOSE TO SURFACE, 尺寸SIZE 10*7.5*55 CeqA=C+Mn/6 B0A01=YIELD STRENGTH B0A02=TENSILE STRENGTH	B0A03=PERCENTAGE ELONGATION AFTER FRACTURE A0C01=IMPACT TEST A A0C012=IMPACT TEST B A0C013=IMPACT TEST C A0C02=IMPACT AVERAGE
	According to EN 10204 3.2 我们在此证明此材料采用已被认可的方法制造, 并且经检验符合LR船级社规范的要求。 We hereby certify, that the material has been made by an approved process and satisfactorily tested in accordance with the Rules of Lloyd's Register.	



冶金技术处处长
DIRECTOR OF
METALLURGICAL
DEPARTMENT

验船师
SURVEYOR

耿新刚

S.J. He
Dalian Office
Lloyd's Register Classification Society China Co Ltd


