



MILL TEST CERTIFICATE

<u>Customer:</u>	<u>PRODALAM S.A.</u>
<u>Commodity:</u>	<u>PRESTRESSED CONCRETE STRAND</u>
<u>Nominal Diameter:</u>	<u>15.24MM</u>
<u>Standard:</u>	<u>ASTM A416/A416M-15</u>
<u>Production Licence No:</u>	<u>XK 05-003-00098</u>
<u>Page No:</u>	<u>7/12</u>
<u>Inspection Date:</u>	<u>OCT.21, 2022</u>
<u>Invoice No:</u>	<u>PCLPY2203C</u>
<u>Container No.</u>	<u>TGHU1268443</u>



Mark on Coil	Coil No.	Dia MM	Section Area (mm ²)	Breaking Load (kN)	Tensile Strength MPA	1%Extension Yield Load (kN)	Yield Strength MPA	Elongation (%)	Modules of Elasticity GPA	Length Approx. Meter	Coil Weight KGS
J7	2210389-1	15.28	141.53	274.1	1958	250.1	1786	5.0	194.1	2854	3176
J7	2210523-4	15.24	140.76	274.1	1958	249.8	1784	5.2	193.8	2482	2764
J7	2210524-6	15.24	140.89	271.4	1939	252.8	1806	6.0	196.1	2464	2744
J7	2210525-3	15.26	141.02	274.3	1959	251.6	1797	5.5	193.6	2839	3160
J7	2210525-4	15.26	141.02	275.2	1966	255.3	1824	5.0	191.1	2839	3160
J7	2210525-5	15.26	141.02	274.2	1959	251.6	1797	6.0	193.6	2838	3158
J7	2210526-2	15.28	141.02	274.2	1959	251.6	1797	5.5	193.4	2839	3160
J7	2210527-3	15.28	141.27	275.2	1966	254.7	1819	5.1	197.0	2650	2950
J7	2210527-4	15.28	141.27	275.6	1969	252.6	1804	5.2	194.2	2648	2948

Filed by :Zhangchunting

Approved by : Shenyingxiang