



日钢营口中板有限公司
RIZHAO STEEL YINGKOU MEDIUM PLATE CO.,LTD.
辽宁省营口市老边区冶金街/115005
Yejinstreet,Laobiandistrict,Yingkou,Liaoning,P.R.China/115005
TEL:0417-3256081 FAX:0417-3256057 NO.:DT2101501/A

产品质量证明书
INSPECTION CERTIFICATE



订货单位 PURCHASER	HYUNDAI CORPORATION	普通碳素结构钢 General carbon structural steel	
收货单位 CONSIGNEE	HYUNDAI CORPORATION	YGR1ZANN240583008-01	
技术标准/牌号 SPEC/GRADE	ASTM A36/A36M;ASTM A36	热轧(AR)	签发日期 DATE OF ISSUE
		20240706	
车号 TRAIN NO.	240706Z00428		

炉号 HEATNO.	批号 LOTNO.	钢板号 PLATENO.	规格 (MM) DIMENSION	数量 QTY	重量 WEIGHT kg	分析区域 AA	化学成分 CHEMICAL ANALYSIS %														B0A01 屈服强度 MPa Rp0.2	B0A02 抗拉强度 MPa Rm	B0A03 断后伸长率 %	B0A04 屈服比	B0B01 弯曲试验 d=3a 180°	A0C01 冲击单值 J	A0C02 冲击单值 J	A0C03 冲击单值 J	A0C04 冲击平均值 J
							C	Si	Mn	P	S	ClV	Cr	Mo	V	Ni	Cu	Nb	Ti										
							$\times 10^{-3}$	$\times 10^{-3}$	$\times 10^{-3}$	$\times 10^{-4}$	$\times 10^{-4}$	$\times 10^{-2}$	$\times 10^{-3}$	$\times 10^{-4}$															
24110875A	2471133	24G1597007	8x2000x12000	1	1,507	L	135	185	867	180	71	29	45	30	2	130	10	20	20	291	444	32.5	0.66	CK	64	68	76	69	
24110875A	2471133	24G1597008	8x2000x12000	1	1,507	L	135	185	867	180	71	29	45	30	2	130	10	20	20	291	444	32.5	0.66	CK	64	68	76	69	
24110875A	2471133	24G1597010	8x2000x12000	1	1,507	L	135	185	867	180	71	29	45	30	2	130	10	20	20	291	444	32.5	0.66	CK	64	68	76	69	
合计(TOTAL):				3	4,521																								

注释
NOTES

L: 熔炼成分 SMELTING COMPOSITION
拉伸标距(GAUGE LENGTH) Lo=200 mm
A0C冲击试验IMPACT TEST: 20°C, 纵向LONGITUDINAL, 近表 CLOSE TO SURFACE, 尺寸SIZE 10*5*55
B0A01=YIELD STRENGTH
B0A02=TENSILE STRENGTH
B0A03=PERCENTAGE ELONGATION AFTER FRACTURE

B0A04=YIELD STRENGTH RATIO
B0B01=BEND TEST
A0C01=IMPACT TEST A
A0C02=IMPACT TEST B
A0C03=IMPACT TEST C
A0C04=IMPACT AVERAGE

According to EN 10204 3.1

本产品已按照标准要求进行制造和检验, 其结果符合要求, 特此证明。
WE HEREBY CERTIFY THAT MATERIAL DESCRIBED HAS MANUFACTURED AND TESTED WITH SATISFACTORY RESULTS IN ACCORDANCE WITH THE REQUIREMENTS OF THE ABOVE MATERIAL SPECIFICATION

冶金技术处处长
DIRECTOR OF METALLURGICAL DEPARTMENT

野牛

致新刚