



日钢营口中板有限公司  
RIZHAO STEEL YINGKOU MEDIUM PLATE CO.,LTD.  
辽宁省营口市老边区冶金街/115005  
Yejinstreet,Laobianidistrict,Yingkou,Liaoning,P.R.China/115005  
TEL:0417-3256081 FAX:0417-3256057 NO.:DT2101501/A

# 产品质量证明书

## INSPECTION CERTIFICATE



订货单位 PURCHASER	PRODALAM SA	产品名称 PRODUCT	普通碳素结构钢 General carbon structural steel		
收货单位 CONSIGNEE	PRODALAM SA	合同编号 CONTRACT NO.	YGCAZANN250383008/YKSG253059D-01		
技术标准/牌号 SPEC/GRADE	ASTM A36/A36M;ASTM A36	交货状态 DELIVERY CONDITION	热轧(AR)	签发日期 DATE OF ISSUE	20250604
		证明书编号 CERTIFICATE NO.	250604Z00428	是否保性能 GUARANTEE OR NOT	是 YES
车号 TRAIN NO.					

炉号 HEAT NO.	批号 LOT NO.	钢板号 PLATE NO.	规格 (MM) DIMENSION	数量 QTY	重量 WEIGHT kg	分析区域 AA	化学成分 CHEMICAL ANALYSIS %														B0A01	B0A02	B0A03	B0A04	B0B01	A0C01	A0C012	A0C013	A0C02
							C	Si	Mn	P	S	CEV	Cr	Mo	V	Ni	Cu	Nb	Ti	屈服强度	抗拉强度	断后伸长率	屈强比	弯曲试验	冲击单值 A	冲击单值 B	冲击单值 C	冲击平均值 Ave	
							<sup>-3</sup> x10	<sup>-3</sup> x10	<sup>-3</sup> x10	<sup>-4</sup> x10	<sup>-4</sup> x10	<sup>-2</sup> x10	<sup>-3</sup> x10	<sup>-4</sup> x10	<sup>-3</sup> x10	<sup>-4</sup> x10	<sup>-4</sup> x10	<sup>-3</sup> x10	<sup>-4</sup> x10	<sup>-4</sup> x10	MPa Rp0.2	MPa Rm	% B5		d=3a 180°	J	J	J	J
25304757C	S56010185	S5601343302	10x2440x6000	1	1,149	L	144	176	828	230	110	30	98	10	1	350	10	30	30	332	467	23.5	0.71	OK	121	110	128	120	
25304757C	S56010185	S5601344101	10x2440x6000	1	1,149	L	144	176	828	230	110	30	98	10	1	350	10	30	30	332	467	23.5	0.71	OK	121	110	128	120	
25304757C	S56010185	S5601344102	10x2440x6000	1	1,149	L	144	176	828	230	110	30	98	10	1	350	10	30	30	332	467	23.5	0.71	OK	121	110	128	120	
25304757C	S56010185	S5601344201	10x2440x6000	1	1,149	L	144	176	828	230	110	30	98	10	1	350	10	30	30	332	467	23.5	0.71	OK	121	110	128	120	
25304757C	S56010185	S5601344202	10x2440x6000	1	1,149	L	144	176	828	230	110	30	98	10	1	350	10	30	30	332	467	23.5	0.71	OK	121	110	128	120	
25304757C	S56010185	S5601344203	10x2440x6000	1	1,149	L	144	176	828	230	110	30	98	10	1	350	10	30	30	332	467	23.5	0.71	OK	121	110	128	120	
25304757C	S56010185	S5601344301	10x2440x6000	1	1,149	L	144	176	828	230	110	30	98	10	1	350	10	30	30	332	467	23.5	0.71	OK	121	110	128	120	
25304757C	S56010185	S5601344302	10x2440x6000	1	1,149	L	144	176	828	230	110	30	98	10	1	350	10	30	30	332	467	23.5	0.71	OK	121	110	128	120	
25304757C	S56010185	S5601345101	10x2440x6000	1	1,149	L	144	176	828	230	110	30	98	10	1	350	10	30	30	332	467	23.5	0.71	OK	121	110	128	120	
25304757C	S56010185	S5601345102	10x2440x6000	1	1,149	L	144	176	828	230	110	30	98	10	1	350	10	30	30	332	467	23.5	0.71	OK	121	110	128	120	
25304757C	S56010185	S5601345201	10x2440x6000	1	1,149	L	144	176	828	230	110	30	98	10	1	350	10	30	30	332	467	23.5	0.71	OK	121	110	128	120	
25304757C	S56010185	S5601345202	10x2440x6000	1	1,149	L	144	176	828	230	110	30	98	10	1	350	10	30	30	332	467	23.5	0.71	OK	121	110	128	120	
<b>合计(TOTAL):</b>							<b>12</b>	<b>13,788</b>																					

注释 NOTES	L : 熔炼成分 SMELTING COMPOSITION 拉伸标距(GAUGE LENGTH) Lo=200 mm A0C冲击试验IMPACTTEST : 20 ,纵向LONGITUDINAL , 近表 CLOSE TO SURFACE , 尺寸SIZE10*7.5*55 B0A01=YIELD STRENGTH B0A02=TENSILE STRENGTH B0A03=PERCENTAGE ELONGATION AFTER FRACTURE	B0A04=YIELD STRENGTH RATIO B0B01=BENDTEST A0C01=IMPACT TEST A A0C012=IMPACT TEST B A0C013=IMPACT TEST C A0C02=IMPACT AVERAGE
	According to EN 10204 3.1	

	本产品已按照标准要求进行制造和检验,其结果符合要求,目视及尺寸检验均符合标准要求,特此证明。 WE HEREBY CERTIFY THAT MATERIAL DESCRIBED HAS MANUFACTURED AND TESTED WITH SATISFACTORY RESULTS IN ACCORDANCE WITH THE REQUIREMENTS OF THE ABOVE MATERIAL SPECIFICATION Both BOTH VISUAL AND DIMENSIONAL INSPECTION MEET THE STANDARD REQUIREMENTS	冶金技术处处长 DIRECTOR OF METALLURGICAL DEPARTMENT