



TEL:0417-3256081 0311-966666 FAX:0417-3256057

INSPECTION CERTIFICATE



注释

NOTES

L: 熔炼成分 SMELTING COMPOSITION
 拉伸标距(GAUGE LENGTH) Lo=200 mm
 A0C冲击试验IMPACTTEST: 20°C, 纵向LONGITUDINAL,
 近表 CLOSE TO SURFACE, 尺寸SIZE10*5*55
 B0A01=YIELD STRENGTH
 B0A02=TENSILE STRENGTH
 B0A03=PERCENTAGE ELONGATION AFTER FRACTURE

According to EN 10204 3.1

B0A04=YIELD STRENGTH RATIO

B0B01=BENDTEST

A0C01=IMPACT TEST A

A0C012=IMPACT TEST B

A0C013=IMPACT TEST C

A0C02=IMPACT AVERAGE



本产品已按照标准要求进行制造和检验，其结果符合要求，目视及尺寸检验均符合标准要求，特此证明。

WE HEREBY CERTIFY THAT MATERIAL DESCRIBED HAS MANUFACTURED AND TESTED WITH SATISFACTORY RESULTS IN ACCORDANCE WITH THE REQUIREMENTS OF THE ABOVE MATERIAL SPECIFICATION Both BOTH VISUAL AND DIMENSIONAL INSPECTION MEET THE STANDARD REQUIREMENTS

技术中心
Technology Center

郑治龙