



	产品名称 PRODUCT	
	合同编号 CONTRACT NO.	
	交货状态 DELIVERY CONDITION	
	证明书编号 CERTIFICATE NO.	
	船号	

[illegible]

注释	L：熔炼成分 SMELTING COMPOSITION 拉伸标距(GAUGE LENGTH) Lo=5.65 √ S0 mm A0C冲击试验IMPACTTEST：0℃, 纵向LONGITUDINAL, 近表 CLOSE TO SURFACE, 尺寸SIZE10*5*55 CeqA=C+Mn/6 B0A01=YIELD STRENGTH B0A02=TENSILE STRENGTH	B0A03=PERCENTAGE ELONGATION AFTER FRACTURE A0C01=IMPACT TEST A A0C012=IMPACT TEST B A0C013=IMPACT TEST C A0C02=IMPACT AVERAGE
NOTES	According to EN 10204 3.2	
	我们在此证明此材料采用已被认可的方法制造, 并且经检验符合LR船级社规范的要求。 We hereby certify that the material has been made by an approved process and satisfactorily tested in accordance with the Rules of Lloyd ' s Register.	冶金技术处处长 DIRECTOROF METALLURGICAL DEPARTMENT
		 S.J. He Dalian Office Lloyd's Register Classification Society China Co Ltd