



日钢营口中板有限公司
RIZHAO STEEL YINGKOU MEDIUM PLATE CO.,LTD.
辽宁省营口市老边区冶金街/115005
Yejinstreet,Laobiandistrict,Yingkou,Liaoning,P.R.China/115005
TEL:0417-3256081 FAX:0417-3256057 NO.:DT2101501/A

产品质量证明书
INSPECTION CERTIFICATE



订货单位 PURCHASER	HYUNDAICORPORATION	普通碳素结构钢 General carbon structural steel	
收货单位 CONSIGNEE	HYUNDAICORPORATION	YGR1ZANN240583008-01	
技术标准/牌号 SPEC/GRADE	ASTM A36/A36M;ASTM A36	热轧(AR)	签发日期 DATE OF ISSUE 20240708
车号 TRAINNO.	240708Z00871		

炉号 HEATNO.	批号 LOTNO.	钢板号 PLATE NO.	规格 (MM) DIMENSION	数量 QTY	重量 WEIGHT kg	分析区域 AA	化学成分 CHEMICAL ANALYSIS %										C	C	C	C	B	A	A	A	A	
							C										0A01	0A02	0A03	0A04	0B01	0C01	0C012	0C013	0C02	
							C	Si	Mn	P	S	CEV	Cr	Mo	V	Ni	Cu	屈服强度 MPa Rp0.2	抗拉强度 MPa Rm	断后伸长率 %	屈强比 B2	弯曲试验 d=3a 180°	冲击单值 J	冲击单值 J	冲击单值 J	冲击平均值 Ave
24205264B	S47060039	S4705387101	75x2000x6000	1	7.065	L	181	191	904	100	106	34	33	40	2	180	11	273	460	39	0.59	CK	139	132	137	136
24205264B	S47060040	S4705387102	75x2000x6000	1	7.065	L	181	191	904	100	106	34	33	40	2	180	11	270	462	38.5	0.58	CK	134	148	141	141
合计(TOTAL):				2	14.130																					

注释
NOTES

L: 熔炼成分 SMELTING COMPOSITION
拉伸标距(GAUGE LENGTH) Lo=50 mm
A0C冲击试验IMPACTTEST: 20℃, 纵向LONGITUDINAL, 1/4位置 1/4 LOCATION, 尺寸SIZE10*10*55
C0A01=YIELD STRENGTH
C0A02=TENSILE STRENGTH
C0A03=PERCENTAGE ELONGATION AFTER FRACTURE

C0A04=YIELD STRENGTH RATIO
B0B01=BEND TEST
A0C01=IMPACT TEST A
A0C012=IMPACT TEST B
A0C013=IMPACT TEST C
A0C02=IMPACT AVERAGE

According to EN 10204 3.1

野牛

本产品已按照标准要求进行制造和检验, 其结果符合要求, 特此证明。
WE HEREBY CERTIFY THAT MATERIAL DESCRIBED HAS MANUFACTURED AND TESTED WITH SATISFACTORY RESULTS IN ACCORDANCE WITH THE REQUIREMENTS OF THE ABOVE MATERIAL SPECIFICATION

冶金技术处处长
DIRECTOR OF METALLURGICAL DEPARTMENT

殷新刚