日钢营口中板有限公司
RIZHAO STEEL YINGKOU MEDIUM PLATE CO.,LTD.
辽宁省营口市老边区冶金街/115005
Yejinstreet,Laobiandistrict,Yingkou,Liaoning,P.R.China/115005
TEL:0417-3256081 FAX:0417-3256057 NO.:DT2101501/A

产品质量证明书
INSPECTION CERTIFICATE

订货单位 PURCHASER	HYUNDAI CORPORATION	产品名称 PRODUCT	船用钢板 Hull Steel plate		
收货单位 CONSIGNEE	HYUNDAI CORPORATION	合同编号 CONTRACT NO.	YGR1ZANN240583008-01		
技术标准/牌号 SPEC/GRADE	LR RULES;LRB	交货状态 DELIVERY CONDITION	正火轧制(NR)	签发日期 DATE OF ISSUE	20240730
		证明书编号 CERTFICATE NO.	240724Z00904	控制号 CONTROL NUMBER	DLN2400913
车 号 TRAIN NO.		船号 HULL NO.			

炉号 HEAT NO.	批号 LOT NO.	钢板号 PLATE NO.	分段号 SECTION NO.	规格 (MM) DIMENSION	数量 QTY	重量 WEIGHT kg	化学成分 CHEMICAL ANALYSIS % C	Si	Mn	P	S	Als	Ti	Nb	Ni	Cr	Cu	Mo	CeqA	B0A01 屈服强度 MPa ReH	B0A02 抗拉强度 MPa Rm	B0A03 断后伸长率 % B1	A0C01 冲击单值A J	A0C012 冲击单值B J	A0C013 冲击单值C J	A0C02 冲击均值Ave J
							$\times10^{-3}$	$\times10^{-2}$	$\times10^{-3}$	$\times10^{-3}$	$\times10^{-3}$	$\times10^{-3}$	$\times10^{-4}$	$\times10^{-4}$	$\times10^{-4}$	$\times10^{-3}$	$\times10^{-3}$	$\times10^{-4}$	$\times10^{-3}$							
24111167A	S47080008	S4707490101		6x2440x12000	1	1,379	140	20	830	22	3	41	140	20	110	31	9	30	278	357	465	40	75	60	75	70
24111167A	S47080008	S4707490201		6x2440x12000	1	1,379	140	20	830	22	3	41	140	20	110	31	9	30	278	357	465	40	75	60	75	70
24111167A	S47080008	S4707490301		6x2440x12000	1	1,379	140	20	830	22	3	41	140	20	110	31	9	30	278	357	465	40	75	60	75	70
24111167A	S47080008	S4707491101		6x2440x12000	1	1,379	140	20	830	22	3	41	140	20	110	31	9	30	278	357	465	40	75	60	75	70
24111167A	S47080008	S4707491201		6x2440x12000	1	1,379	140	20	830	22	3	41	140	20	110	31	9	30	278	357	465	40	75	60	75	70
24111167A	S47080008	S4707491301		6x2440x12000	1	1,379	140	20	830	22	3	41	140	20	110	31	9	30	278	357	465	40	75	60	75	70
24111167A	S47080008	S4707492101		6x2440x12000	1	1,379	140	20	830	22	3	41	140	20	110	31	9	30	278	357	465	40	75	60	75	70
24111167A	S47080008	S4707492201		6x2440x12000	1	1,379	140	20	830	22	3	41	140	20	110	31	9	30	278	357	465	40	75	60	75	70
24111167A	S47080008	S4707493101		6x2440x12000	1	1,379	140	20	830	22	3	41	140	20	110	31	9	30	278	357	465	40	75	60	75	70
24111167A	S47080008	S4707493201		6x2440x12000	1	1,379	140	20	830	22	3	41	140	20	110	31	9	30	278	357	465	40	75	60	75	70
24111167A	S47080008	S4707493301		6x2440x12000	1	1,379	140	20	830	22	3	41	140	20	110	31	9	30	278	357	465	40	75	60	75	70
24111167A	S47080008	S4707495101		6x2440x12000	1	1,379	140	20	830	22	3	41	140	20	110	31	9	30	278	357	465	40	75	60	75	70
				合计(TOTAL)：	12	16,548																				

注释 NOTES

L：熔炼成分 SMELTING COMPOSITION
拉伸标距(GAUGE LENGTH) Lo=5.65√S0 mm
A0C冲击试验IMPACTTEST：0°C，纵向LONGITUDINAL，近表 CLOSE TO SURFACE，尺寸SIZE10*5*55
CeqA=C+Mn/6
B0A01=YIELD STRENGTH
B0A02=TENSILE STRENGTH

B0A03=PRECENTAGE ELONGATION AFTER FRACTURE
A0C01=IMPACT TEST A
A0C012=IMPACT TEST B
A0C013=IMPACT TEST C
A0C02=IMPACT AVERAGE

According to EN 10204 3.2

野牛

我们在此证明此材料采用已被认可的方法制造，并且经检验符合LR船级社规范的要求。
We hereby certify, that the material has been made by an approved process and satisfactorily tested in accordance with the Rules of Lloyd ' s Register.

冶金技术处处长 DIRECTOR OF METALLURGICAL DEPARTMENT

殿彩刚

验船师 SURVEYOR

S.J. He
Dalian Office
Lloyd's Register Classification Society China Co Ltd