



日钢营口中板有限公司  
RIZHAO STEEL YINGKOU MEDIUM PLATE CO.,LTD.  
辽宁省营口市老边区冶金街/115005  
Yejinstreet,Laobianidistrict,Yingkou,Liaoning,P.R.China/115005  
TEL:0417-3256081 FAX:0417-3256057 NO.:DT2101501/A

产品质量证明书  
INSPECTION CERTIFICATE



订货单位 PURCHASER	PRODALAM SA	产品名称 PRODUCT	船用钢板 Hull Steel plate		
收货单位 CONSIGNEE	PRODALAM SA	合同编号 CONTRACT NO.	YGCAZANN250383008/YKSG253059D-03		
技术标准/牌号 SPEC/GRADE	LR RULES;LRB	交货状态 DELIVERY CONDITION	正火轧制(NR)	签发日期 DATE OF ISSUE	20250529
		证明书编号 CERTIFICATE NO.	250527Z00646	控制号 CONTROL NUMBER	DLN2501137
车号 TRAIN NO.		船号 HULL NO.		是否保性能 GUARANTEE OR NOT	是 YES



炉号 HEAT NO.	批号 LOT NO.	钢板号 PLATE NO.	分段号 SECTION NO.	规格 (MM) DIMENSION	数量 QTY	重量 WEIGHT kg	化学成分 CHEMICAL ANALYSIS %														B 0A01 屈 服 强 度 MPa ReH	B 0A02 抗 拉 强 度 MPa Rm	B 0A03 断 后 伸 长 率 %	A 0C01 冲 击 单 值 A J	A 0C12 冲 击 单 值 B J	A 0C13 冲 击 单 值 C J	A 0C02 冲 击 均 值 Ave J
							C	Si	Mn	P	S	Als	Ti	Nb	Ni	Cr	Cu	Mo	CeqA								
							<sup>-3</sup> x10	<sup>-2</sup> x10	<sup>-3</sup> x10	<sup>-3</sup> x10	<sup>-3</sup> x10	<sup>-3</sup> x10	<sup>-4</sup> x10	<sup>-4</sup> x10	<sup>-4</sup> x10	<sup>-3</sup> x10	<sup>-3</sup> x10	<sup>-4</sup> x10	<sup>-3</sup> x10								
25109968A	S55260037	S5526358101		10x2440x12000	1	2,298	146	25	820	19	4	36	150	30	280	78	14	30	283	294	444	36	147	166	183	165	
25109968A	S55260037	S5526358201		10x2440x12000	1	2,298	146	25	820	19	4	36	150	30	280	78	14	30	283	294	444	36	147	166	183	165	
25109968A	S55260037	S5526359101		10x2440x12000	1	2,298	146	25	820	19	4	36	150	30	280	78	14	30	283	294	444	36	147	166	183	165	
25109968A	S55260037	S5526359201		10x2440x12000	1	2,298	146	25	820	19	4	36	150	30	280	78	14	30	283	294	444	36	147	166	183	165	
25109968A	S55260037	S5526359301		10x2440x12000	1	2,298	146	25	820	19	4	36	150	30	280	78	14	30	283	294	444	36	147	166	183	165	
合计(TOTAL):					5	11,490																					

注释 NOTES	<p>L : 熔炼成分 SMELTING COMPOSITION 拉伸标距(GAUGE LENGTH) Lo=5.65 S0 mm A0C冲击试验IMPACTTEST : 0 , 纵向LONGITUDINAL , 近表 CLOSE TO SURFACE , 尺寸SIZE10*7.5*55 CeqA=C+Mn/6 B0A01=YIELD STRENGTH B0A02=TENSILE STRENGTH</p>	<p>B0A03=PERCENTAGE ELONGATION AFTER FRACTURE A0C01=IMPACT TEST A A0C012=IMPACT TEST B A0C013=IMPACT TEST C A0C02=IMPACT AVERAGE</p>
-------------	--	--

野牛	<p>我们在此证明此材料采用已被认可的方法制造, 并且经检验符合LR船级社规范的要求。 We hereby certify, that the material has been made by an approved process and satisfactorily tested in accordance with the Rules of Lloyd ' s Register.</p>	<p>冶金技术处处长 DIRECTOR OF METALLURGICAL DEPARTMENT</p>	<p>验船师 SURVEYOR</p>
			