



敬业 (营口) 中板有限公司
JINGYE (YINGKOU) MEDIUM PLATE CO.LTD.

辽宁省营口市老边区冶金街/115005

Yejinstreet, Laobiandistrict, Yingkou, Liaoning, P.R.China/115005

TEL:0417-3256081 FAX:0417-3256057 NO.:DT2101501/A

产品质量证明书

INSPECTION CERTIFICATE



订货单位 PURCHASER	PRODALAM SA	产品名称 PRODUCT	普通碳素结构钢 General carbon structural steel		
收货单位 CONSIGNEE	PRODALAM SA	合同编号 CONTRACT NO.	YGCAZANN250683001-01		
技术标准/牌号 SPEC/GRADE	ASTM A36/A36M;ASTM A36	交货状态 DELIVERY CONDITION	热轧(AR)	签发日期 DATE OF ISSUE	20250717
		证明书编号 CERTIFICATE NO.	250717Z00144	是否保性能 GUARANTEE OR NOT	是 YES
车号 TRAIN NO.					

炉号 HEAT NO.	批号 LOT NO.	钢板号 PLATE NO.	规格 (MM) DIMENSION	数量 QTY	重量 WEIGHT kg	分析 区域 AA	化学成分 CHEMICAL ANALYSIS %														B 0A01	B 0A02	B 0A03	B 0A04	B 0B01	A 0C01	A 0C012	A 0C013	A 0C02
							C	Si	Mn	P	S	CEV	Cr	Mo	V	Ni	Cu	Nb	Ti	屈服 强度	抗 拉 强度	断后 伸 长 率	屈 强 比	弯 曲 试 验	冲 击 单 值 A	冲 击 单 值 B	冲 击 单 值 C	冲 击 均 值 Ave	
							x10 ⁻³	x10 ⁻³	x10 ⁻³	x10 ⁻⁴	x10 ⁻⁴	x10 ⁻²	x10 ⁻³	x10 ⁻⁴	x10 ⁻⁴	MPa Rp0.2	MPa Rm	% B5		d=3a 180°	J	J	J						
25113372A	2573285	25G6202005	12x2440x6000	1	1,379	L	131	151	841	160	66	30	101	70	1	410	27	30	30	282	432	23	0.65	OK	247	257	254	253	
25113372A	2573285	25G6202008	12x2440x6000	1	1,379	L	131	151	841	160	66	30	101	70	1	410	27	30	30	282	432	23	0.65	OK	247	257	254	253	
25113372A	2573285	25G6204001	12x2440x6000	1	1,379	L	131	151	841	160	66	30	101	70	1	410	27	30	30	282	432	23	0.65	OK	247	257	254	253	
25113372A	2573285	25G6204002	12x2440x6000	1	1,379	L	131	151	841	160	66	30	101	70	1	410	27	30	30	282	432	23	0.65	OK	247	257	254	253	
25113372A	2573285	25G6204003	12x2440x6000	1	1,379	L	131	151	841	160	66	30	101	70	1	410	27	30	30	282	432	23	0.65	OK	247	257	254	253	
25113372A	2573285	25G6204004	12x2440x6000	1	1,379	L	131	151	841	160	66	30	101	70	1	410	27	30	30	282	432	23	0.65	OK	247	257	254	253	
25113372A	2573285	25G6204005	12x2440x6000	1	1,379	L	131	151	841	160	66	30	101	70	1	410	27	30	30	282	432	23	0.65	OK	247	257	254	253	
25113372A	2573285	25G6204006	12x2440x6000	1	1,379	L	131	151	841	160	66	30	101	70	1	410	27	30	30	282	432	23	0.65	OK	247	257	254	253	
25113372A	2573285	25G6204007	12x2440x6000	1	1,379	L	131	151	841	160	66	30	101	70	1	410	27	30	30	282	432	23	0.65	OK	247	257	254	253	
25113372A	2573285	25G6204008	12x2440x6000	1	1,379	L	131	151	841	160	66	30	101	70	1	410	27	30	30	282	432	23	0.65	OK	247	257	254	253	
25113372A	2573285	25G6204009	12x2440x6000	1	1,379	L	131	151	841	160	66	30	101	70	1	410	27	30	30	282	432	23	0.65	OK	247	257	254	253	
25113372A	2573285	25G6204010	12x2440x6000	1	1,379	L	131	151	841	160	66	30	101	70	1	410	27	30	30	282	432	23	0.65	OK	247	257	254	253	
合计(TOTAL):							12	16,548																					

注释 NOTES	L: 熔炼成分 SMELTING COMPOSITION 拉伸标距(GAUGE LENGTH) Lo=200 mm A0C冲击试验IMPACTTEST: 20, 纵向LONGITUDINAL, 近表 CLOSE TO SURFACE, 尺寸SIZE10*10*55 B0A01=YIELD STRENGTH B0A02=TENSILE STRENGTH B0A03=PERCENTAGE ELONGATION AFTER FRACTURE	B0A04=YIELD STRENGTH RATIO B0B01=BENDTEST A0C01=IMPACT TEST A A0C012=IMPACT TEST B A0C013=IMPACT TEST C A0C02=IMPACT AVERAGE
	According to EN 10204 3.1	

	本产品已按照标准要求进行制造和检验, 其结果符合要求, 目视及尺寸检验均符合标准要求, 特此证明。 WE HEREBY CERTIFY THAT MATERIAL DESCRIBED HAS MANUFACTURED AND TESTED WITH SATISFACTORY RESULTS IN ACCORDANCE WITH THE REQUIREMENTS OF THE ABOVE MATERIAL SPECIFICATION Both BOTH VISUAL AND DIMENSIONAL INSPECTION MEET THE STANDARD REQUIREMENTS	冶金技术处处长 DIRECTOR OF METALLURGICAL DEPARTMENT