



敬业 (营口) 中板有限公司
JINGYE (YINGKOU) MEDIUM PLATE CO.LTD.

辽宁省营口市老边区冶金街/115005

Yejinstreet, Laobiandistrict, Yingkou, Liaoning, P.R.China/115005

TEL:0417-3256081 FAX:0417-3256057 NO.:DT2101501/A

产品质量证明书
INSPECTION CERTIFICATE



订货单位 PURCHASER	PRODALAM SA	产品名称 PRODUCT	普通碳素结构钢 General carbon structural steel		
收货单位 CONSIGNEE	PRODALAM SA	合同编号 CONTRACT NO.	YGCAZANN250483008-01		
技术标准/牌号 SPEC/GRADE	ASTM A36/A36M-2019 ; ASTM A36	交货状态 DELIVERY CONDITION	热轧(AR)	签发日期 DATE OF ISSUE	20250615
		证明书编号 CERTIFICATE NO.	250615Z01135	是否保性能 GUARANTEE OR NOT	是 YES
车号 TRAIN NO.					

炉号 HEAT NO.	批号 LOT NO.	钢板号 PLATE NO.	规格 (MM) DIMENSION	数量 QTY	重量 WEIGHT kg	分析 区域 AA	化学成分 CHEMICAL ANALYSIS %														B 0A01	B 0A02	B 0A03	B 0A04	B 0B01	A 0C01	A 0C012	A 0C013	A 0C02
							C	Si	Mn	P	S	CEV	Cr	Mo	V	Ni	Cu	Nb	Ti	屈服 强度	抗 拉 强度	断后 伸 长 率	屈 强 比	弯 曲 试 验	冲 击 单 值 A	冲 击 单 值 B	冲 击 单 值 C	冲 击 均 值 Ave	
							$\times 10^{-3}$	$\times 10^{-3}$	$\times 10^{-3}$	$\times 10^{-4}$	$\times 10^{-4}$	$\times 10^{-2}$	$\times 10^{-3}$	$\times 10^{-4}$	$\times 10^{-4}$	MPa Rp0.2	MPa Rm	% B5		d=3a 180°	J	J	J						
25110567A	S56100169	S5612529301	6x2440x12000	1	1,379	L	134	142	838	260	106	30	128	50	2	400	14	30	20	328	458	27.5	0.72	OK	80	80	80	80	
25110569A	S56130025	S5612535101	6x2440x12000	1	1,379	L	132	148	835	220	133	30	110	40	1	370	12	30	20	336	439	27.5	0.77	OK	68	71	74	71	
25110569A	S56130025	S5612536101	6x2440x12000	1	1,379	L	132	148	835	220	133	30	110	40	1	370	12	30	20	336	439	27.5	0.77	OK	68	71	74	71	
25110569A	S56130025	S5612536201	6x2440x12000	1	1,379	L	132	148	835	220	133	30	110	40	1	370	12	30	20	336	439	27.5	0.77	OK	68	71	74	71	
25110569A	S56130025	S5612536202	6x2440x12000	1	1,379	L	132	148	835	220	133	30	110	40	1	370	12	30	20	336	439	27.5	0.77	OK	68	71	74	71	
25110569A	S56130025	S5612537101	6x2440x12000	1	1,379	L	132	148	835	220	133	30	110	40	1	370	12	30	20	336	439	27.5	0.77	OK	68	71	74	71	
25110569A	S56130025	S5612537201	6x2440x12000	1	1,379	L	132	148	835	220	133	30	110	40	1	370	12	30	20	336	439	27.5	0.77	OK	68	71	74	71	
25110569A	S56130025	S5612537301	6x2440x12000	1	1,379	L	132	148	835	220	133	30	110	40	1	370	12	30	20	336	439	27.5	0.77	OK	68	71	74	71	
25110403A	S56080155	S5614400101	8x2440x12000	1	1,839	L	139	189	845	210	143	30	104	20	2	390	12	30	30	307	471	26	0.65	OK	80	99	78	86	
25110403A	S56080155	S5614400201	8x2440x12000	1	1,839	L	139	189	845	210	143	30	104	20	2	390	12	30	30	307	471	26	0.65	OK	80	99	78	86	
25110403A	S56080155	S5614400301	8x2440x12000	1	1,839	L	139	189	845	210	143	30	104	20	2	390	12	30	30	307	471	26	0.65	OK	80	99	78	86	
合计(TOTAL):				11	16,549																								

注释 NOTES	L : 熔炼成分 SMELTING COMPOSITION 拉伸标距(GAUGE LENGTH) Lo=200 mm A0C冲击试验IMPACTTEST : 20 , 纵向LONGITUDINAL , 近表 CLOSE TO SURFACE , 尺寸SIZE10*5*55	B0A04=YIELD STRENGTH RATIO B0B01=BENDTEST A0C01=IMPACT TEST A A0C012=IMPACT TEST B A0C013=IMPACT TEST C A0C02=IMPACT AVERAGE
	B0A01=YIELD STRENGTH B0A02=TENSILE STRENGTH B0A03=PERCENTAGE ELONGATION AFTER FRACTURE	
According to EN 10204 3.1		

	本产品已按照标准要求制造和检验, 其结果符合要求, 目视及尺寸检验均符合标准要求, 特此证明。 WE HEREBY CERTIFY THAT MATERIAL DESCRIBED HAS MANUFACTURED AND TESTED WITH SATISFACTORY RESULTS IN ACCORDANCE WITH THE REQUIREMENTS OF THE ABOVE MATERIAL SPECIFICATION Both BOTH VISUAL AND DIMENSIONAL INSPECTION MEET THE STANDARD REQUIREMENTS	冶金技术处处长 DIRECTOR OF METALLURGICAL DEPARTMENT