5173 -BGCW016

注文者 SHIPPER : SAMSUNG C&T JAPAN CORPORATION
契約番号 CONTRACT No. : 2-831-H1-5-Y-BS01　船番 SHIP No. :
商品名 COMMODITY : HOT ROLLED STEEL PLATES
規格 SPECIFICATION : LR GRADE LRB(LBK)
需要家 CUSTOMER : PRODALAM S A
需要家管理番号 CUSTOMER'S CONTROL No. :
文書番号 DOCUMENT No. :

日本製鉄株式会社
NIPPON STEEL CORPORATION

鋼材検査証明書
INSPECTION CERTIFICATE

本社 HEAD OFFICE : 〒100-8071 東京都千代田区丸の内二丁目6番1号 2-6-1, MARUNOUCHI, CHIYODA-KU, TOKYO, 100-8071, JAPAN
東日本製鉄所 鹿島 EAST NIPPON WORKS KASHIMA : 〒314-0014 茨城県鹿嶋市光3番地 3, HIKARI, KASHIMA-CITY, IBARAKI-PREF., 314-0014, JAPAN

証明書番号 CERTIFICATE No. : EL2315640　頁 PAGE : 6
発行年月日 DATE OF ISSUE : 2023-01-07

需要家照合番号 ORDER ITEM No.	寸法 DIMENSION mm, H:inch, F:feet	員数 QUANTITY	質量 MASS KG	製鋼番号 HEAT No. / 試験番号 TEST No.	製品番号 PLATE No.	区分※1	位置※2	方向※3	厚内※4	GL※5	降伏点・耐力 YP, YS N/MM2	引張強さ TS N/MM2	伸び EL %	% ※7	BOND TEST 曲げ試験※8	位置※2	区分※1	方向※3	SIZE※9	厚内※4	試験温度 TEST TEMP.	ABSORBED ENERGY KV2 J 1	2	3	AVG	分析区分※10	C 2	Si 2	Mn 2	P 3	S 3	Cu	Ni	Cr	Mo	Nb	V	T.Al	Sol.Al	CE1 2	PCM	脱酸	溶解※11	寸・外・形※12	供給状態※13
					TO 011520503																																								
01 6X2440X12000		3	4137	2A32907 L04432	FROM 011523001		T	C	F D		349	463	30		A	T	L		S 5	+	0 C	83	81	81	82	L	15	19	71	17	2								27		A R	A
					TO 011523003																																								
01 6X2440X12000		1	1379	2A32907 L04432	011523101		T	C	F D		349	463	30		A	T	L		S 5	+	0 C	83	81	81	82	L	15	19	71	17	2								27		A R	A
01 6X2440X12000		3	4137	2A32907 L04432	FROM 011523401		T	C	F D		349	463	30		A	T	L		S 5	+	0 C	83	81	81	82	L	15	19	71	17	2								27		A R	A
					TO 011523403																																								
01 6X2440X12000		3	4137	2A32907 L04432	FROM 011523501		T	C	F D		349	463	30		A	T	L		S 5	+	0 C	83	81	81	82	L	15	19	71	17	2								27		A R	A
					TO 011523503																																								
01 6X2440X12000		1	1379	2B23006 N00685	Y60503301		T	C	F D		354	465	25		A	T	L		S 5	+	0 C	83	85	88	85	L	15	17	67	16	2								26		A R	A
02 6X2440X12000		1	1379	2A32814 M01449	X53000801		T	C	F D		331	454	29		A	T	L		S 5	+	0 C	180	181	173	178	L	15	18	70	15	3								27		A R	A
02 6X2440X12000		2	2758	2A32906 L04423	FROM X60404201		T	C	F D		307	447	28		A	T	L		S 5	+	0 C	88	87	89	88	L	15	18	69	17	2								26		A R	A
					TO X60404202																																								

化学成分 CHEMICAL COMPOSITION % (0: x1, 1: 1/10, 2: 1/100, 3: 1/1000, 4: 1/10000, 5: 1/100000)

注釈 NOTES
※1 試験片熱処理区分 Test piece heat treatment, H:試験片熱処理後 Heat treated for test piece. ブランク blank:供給ままAs-supplied
※2 位置 Location T:Top, B:Bottom.
※3 方向 Direction L:圧延方向 Longitudinal, C:直角方向 Transverse, Z:板厚方向 Through Thickness, R:45°方向 45Deg. to the Longitudinal Axis
※4 厚内位置 Position in thickness, F:全厚 Full-thick., S:表層 Surface, B:Bottom surface, Q:1/4厚 Quarter-thick., M:1/2厚 Mid-thick., T:1/3厚 Third-thick., 3:3/4厚 Three quarter-thick., W:表面下12.5mm 12.5mm-under surface, H:半厚 Half-thick
※5 GL 標点距離 Gauge Length. 平形試験片 Rectangular type specimen. A:50mm, B:70mm, C:80mm, D:200mm, E:2", F:8", G:5.65√So, H:4√So. 丸形試験片 Round type specimen. 1:50mm, 2:70mm, 3:2", 4:5.65√So, 5:4√So
※6 YP, YS:Yield Point or Yield Strength, 0.2YS:0.2% Offset, 0.5YS:0.5% total extension under load, LYP:Lower yield point
※7 RA:絞り Reduction of Area, YR:降伏比 Yield Ratio
※8 A:合格 Acceptable
※9 SIZE衝撃試験片サイズ F:10mm Full, 2:2.5mm Sub, 3:3.3mm Sub, 4:3.33mm Sub, 5:5mm Sub, 6:6.67mm Sub, 7:7.5mm Sub, 8:6.7mm Sub, 9:19.8mm, A:Plate Thick.
※10 分析区分 Analysis L:レードル分析 Ladle, P:製品分析 Product
※11 超音波試験 Ultrasonic test A:Acceptable
※12 寸法、外観、形状検査 Dimension, Visual, Shape Inspection A:Acceptable.
※13 供給状態 Condition of supply AR:AS-ROLLED
※MISC 温度 Temperature/ C:°C F:°F, 1MPa=1N/mm2
FA:延性破面率 Fracture Appearance(Shear Fracture), CF:脆性破面率 Crystallinity Fracture, LE:横膨出 Lateral Expansion, AGS:オーステナイト粒度 Austenite Grain Size, FGS:フェライト粒度 Ferrite Grain Size, SR:Stress Relieved/PostWeld Heat Treatment

All plates are produced by following process.
STEEL MAKING:LD Process and Fully-Killed practice.

上記注文品は御指定の規格または仕様に従って製造され、その要求事項を満足していることを証明します。

WE HEREBY CERTIFY THAT THE MATERIAL HAS BEEN MADE BY AN APPROVED PROCESS AND SATISFACTORILY TESTED IN ACCORDANCE WITH THE RULES OF LLOYD'S REGISTER. THIS CERTIFICATE IS ISSUED UNDER THE ARRANGEMENTS AUTHORISED BY LLOYD'S REGISTER IN ACCORDANCE WITH THE REQUIREMENTS OF THE MATERIALS QUALITY SCHEME AND CERTIFICATE NUMBER MQS002.

APPROVED LR MATERIALS QUALITY SCHEME

HIDENORI FUKAMI 深水 秀範
東日本製鉄所 品質保証室長
HEAD OF DEPARTMENT
QUALITY ASSURANCE DEPT.
EAST NIPPON WORKS

111PN631A01Q0LR04E1L

<注意とお願い>本証明書の改竄や不正使用は、固く禁じられております。本証明書の真偽についてご質問がある場合は、次の当社窓口までお問い合わせ下さい (E-mail, mc-pl@jp.nipponsteel.com)。
<Notice>Modification to or unauthorized use of this certificate is strictly prohibited. If you have any questions on the authenticity of this certificate, you can contact us by E-mail, mc-pl@jp.nipponsteel.com.

FOJ0033001772