



日钢营口中板有限公司
RIZHAO STEEL YINGKOU MEDIUM PLATE CO.,LTD.
辽宁省营口市老边区冶金街/115005
Yejinstreet,Laobianidistrict,Yingkou,Liaoning,P.R.China/115005
TEL:0417-3256081 FAX:0417-3256057 NO.:DT2101501/A

产品质量证明书
INSPECTION CERTIFICATE



订货单位 PURCHASER	CUMIC STEEL LIMITED		普通碳素结构钢 General carbon structural steel
收货单位 CONSIGNEE	CUMIC STEEL LIMITED		YGR1ZANN240783010
技术标准/牌号 SPEC/GRADE	ASTM A36/A36M-2019	热轧(AR)	交货日期 DATE OF ISSUE 20240903 240903Z00664
车号 TRAIN NO.			

炉号 HEAT NO.	批号 LOT NO.	钢板号 PLATE NO.	规格 MM DIMENSION	数量 QTY	重量 WEIGHT kg	分析区域 AA	化学成分 CHEMICAL ANALYSIS %																B				A				A			
							C	Si	Mn	P	S	Cr	Cr	Mo	V	Nb	Cu	Nb	B	0A01 屈服强度	0A02 抗拉强度	0A03 断后伸长率	0A04 屈服比	0B01 弯曲试验	0C01 冲击值 A	0C02 冲击值 B	0C03 冲击值 C	0C04 冲击平均值						
24406625C	2490311	24J0301005	12x2440x12000	1	2.758	L	1.41	156	841	230	103	30	90	10	2	310	16	30	30	MPa	MPa	%	d 3a	J	J	J	J							
24406625C	2490311	24J0301006	12x2440x12000	1	2.758	L	1.41	156	841	230	103	30	90	10	2	310	16	30	30	Rp0.2	Rm	B5	180	OK	OK	OK	OK							
合计(TOTAL):				2	5.516																													

注释 NOTES	L: 熔炼成分 SMELTING COMPOSITION 拉伸标距(GAUGE LENGTH) Lo=200 mm A0C冲击试验IMPACT TEST: 20C, 纵向LONGITUDINAL, 近表 CLOSE TO SURFACE, 尺寸SIZE10*10*55 B0A01=YIELD STRENGTH B0A02=TENSILE STRENGTH B0A03=PERCENTAGE ELONGATION AFTER FRACTURE	B0A04=YIELD STRENGTH RATIO B0B01=BEND TEST A0C01=IMPACT TEST A A0C02=IMPACT TEST B A0C013=IMPACT TEST C A0C02=IMPACT AVERAGE
	According to EN 10204 3.1 本产品已按照标准要求制造和检验, 其结果符合要求, 特此证明。 WE HEREBY CERTIFY THAT MATERIAL DESCRIBED HAS MANUFACTURED AND TESTED WITH SATISFACTORY RESULTS IN ACCORDANCE WITH THE REQUIREMENTS OF THE ABOVE MATERIAL SPECIFICATION	



冶金技术处处长
DIRECTOR OF
METALLURGICAL
DEPARTMENT

耿新刚