



日钢营口中板有限公司  
RIZHAO STEEL YINGKOU MEDIUM PLATE CO.,LTD.  
辽宁省营口市老边区冶金街/115005  
Yejinstreet,Laobiandistrict,Yingkou,Liaoning,P.R.China/115005  
TEL:0417-3256081 FAX:0417-3256057 NO.:DT2101501/A

产品质量证明书  
INSPECTION CERTIFICATE



订货单位 PURCHASER	CUMIC STEEL LIMITED		普通碳素结构钢 General carbon structural steel
收货单位 CONSIGNEE	CUMIC STEEL LIMITED		合同编号 CONTRACT NO. YGR1ZANN240783010
技术标准/牌号 SPEC/GRADE	ASTM A36/A36M-2019	交货状态 DELIVERY CONDITION 热轧(AR)	签发日期 DATE OF ISSUE 20240822
车号 TRAIN NO.			240822Z00860

炉号 HEAT NO.	批号 LOT NO.	钢板号 PLATE NO.	规格 DIMENSION	数量 QTY	重量 WEIGHT kg	分析区域 AA	化学成分 CHEMICAL ANALYSIS %														力学性能					
							C	Si	Mn	P	S	CBV	Cr	Mo	V	Ni	Cu	C0A01	C0A02	C0A03	C0A04	B0B01	A0C01	A0C012	A0C013	A0C02
24406124B	S48180174	S4818318101	75x2000x6000	1	7.065	I.	1.80	202	919	210	83	35	48	10	1	210	7	287	447	33.5	0.64	OK	192	197	225	205
24406124B	S48180174	S4818318102	75x2000x6000	1	7.065	I.	1.80	202	919	210	83	35	48	10	1	210	7	287	447	33.5	0.64	OK	192	197	225	205
合计(TOTAL):				2	14.130																					

注释 NOTES	L: 熔炼成分 SMELTING COMPOSITION 拉伸标距(GAUGE LENGTH) Lo=50 mm A0C冲击试验IMPACT TEST: 20℃, 纵向LONGITUDINAL, 1/4位置 1/4 LOCATION, 尺寸SIZE10*10*55 C0A01=YIELD STRENGTH C0A02=TENSILE STRENGTH C0A03=PERCENTAGE ELONGATION AFTER FRACTURE	C0A04=YIELD STRENGTH RATIO B0B01=BEND TEST A0C01=IMPACT TEST A A0C012=IMPACT TEST B A0C013=IMPACT TEST C A0C02=IMPACT AVERAGE
	According to EN 10204 3.1  本产品已按照标准要求制造和检验, 其结果符合要求, 特此证明。 WE HEREBY CERTIFY THAT MATERIAL DESCRIBED HAS MANUFACTURED AND TESTED WITH SATISFACTORY RESULTS IN ACCORDANCE WITH THE REQUIREMENTS OF THE ABOVE MATERIAL SPECIFICATION	



冶金技术处处长  
DIRECTOR OF  
METALLURGICAL  
DEPARTMENT

耿新刚