




订货单位 PURCHASER	SAMSUNG C&T CORPORATION	产品名称 PRODUCT	低合金高强度结构钢 High strength low alloy structural steel		
收货单位 CONSIGNEE	SAMSUNG C&T CORPORATION	合同编号 CONTRACT NO.	YGCAZANN260383004-01		
技术标准/牌号 SPEC/GRADE	ASTM A572/572M;A572 Gr.50	交货状态 DELIVERY CONDITION	热轧(AR)	签发日期 DATE OF ISSUE	20260504
		证明书编号 CERTIFICATE NO.	260504Z00048	是否保性能 GUARANTEE OR NOT	是 YES
车 号 TRAIN NO.					

炉号	批号	钢板号	规格 (MM)	数量	重量 kg	分析区域 AA	化学成分 CHEMICAL ANALYSIS %																B 0A01	B 0A02	B 0A03	B 0A04	B 0B01	A 0C01	A 0C012	A 0C013	A 0C02								
																							屈 服 强 度	抗 拉 强 度	断 后 伸 长 率	屈 强 比	弯 曲 试 验	冲 击 单 值 A	冲 击 单 值 B	冲 击 单 值 C	冲 击 均 值 Ave								
							C	Si	Mn	P	S	Als	Nb	Cr	Ni	Cu	Mo	V	Ti	CE																			
							×10 ⁻³	×10 ⁻³	×10 ⁻³	×10 ⁻⁴	×10 ⁻⁴	×10 ⁻³	×10 ⁻⁴	×10 ⁻³	×10 ⁻⁴	×10 ⁻³	×10 ⁻⁴	×10 ⁻³	×10 ⁻⁴	×10 ⁻³	×10 ⁻⁴	×10 ⁻³	×10 ⁻⁴	×10 ⁻²	MPa	MPa	%		d=3a	J	J	J	J						
																		Rp0.2	Rm	B5		180°																	
26105888D	S65030022	S6502483101	20x2440x12000	1	4,597	L	162	187	1370	180	60	27	120	64	220	7	50	2	160	41	426	548	24	0.78	OK	230	236	268	245										
26105888D	S65030022	S6502483201	20x2440x12000	1	4,597	L	162	187	1370	180	60	27	120	64	220	7	50	2	160	41	426	548	24	0.78	OK	230	236	268	245										
26105888D	S65030022	S6502483301	20x2440x12000	1	4,597	L	162	187	1370	180	60	27	120	64	220	7	50	2	160	41	426	548	24	0.78	OK	230	236	268	245										
			合计(TOTAL) :	3	13,791																																		

注释 NOTES	L : 熔炼成分 SMELTING COMPOSITION 拉伸标距(GAUGE LENGTH) Lo=200 mm A0C冲击试验IMPACTTEST : 4°C, 纵向LONGITUDINAL, 近表 CLOSE TO SURFACE, 尺寸SIZE10*10*55 B0A01=YIELD STRENGTH B0A02=TENSILE STRENGTH B0A03=PERCENTAGE ELONGATION AFTER FRACTURE B0A04=YIELD STRENGTH RATIO B0B01=BENDTEST A0C01=IMPACT TEST A A0C02=IMPACT TEST B A0C03=IMPACT TEST C A0C02=IMPACT AVERAGE According to EN 10204 3.1	技术中心 Technology Center 
	本产品已按照标准要求进行制造和检验，其结果符合要求，目视及尺寸检验均符合标准要求，特此证明。 WE HEREBY CERTIFY THAT MATERIAL DESCRIBED HAS MANUFACTURED AND TESTED WITH SATISFACTORY RESULTS IN ACCORDANCE WITH THE REQUIREMENTS OF THE ABOVE MATERIAL SPECIFICATION Both BOTH VISUAL AND DIMENSIONAL INSPECTION MEET THE STANDARD REQUIREMENTS	