



产品名称 PRODUCT	
合同编号 CONTRACT NO.	
交货状态 DELIVERY CONDITION	
证明书编号 CERTIFICATE NO.	

[illegible]

注释 NOTES	L：熔炼成分SMELTING COMPOSITION 拉伸标距(GAUGE LENGTH) Lo=200 mm A0C冲击试验IMPACTTEST：20°C, 纵向LONGITUDINAL, 近表 CLOSE TO SURFACE, 尺寸SIZE10*5*55 B0A01=YIELD STRENGTH B0A02=TENSILE STRENGTH B0A03=PERCENTAGE ELONGATION AFTER FRACTURE B0A04=YIELD STRENGTH RATIO B0B01=BENDTEST A0C01=IMPACT TEST A A0C012=IMPACT TEST B A0C013=IMPACT TEST C A0C02=IMPACT AVERAGE According to EN 10204 3.1	冶金技术处处长 DIRECTOR OF METALLURGICAL DEPARTMENT  野牛
	本产品已按照标准要求进行制造和检验，其结果符合要求，特此证明。 WE HEREBY CERTIFY THAT MATERIAL DESCRIBED HAS MANUFACTURED AND TESTED WITH SATISFACTORY RESULTS IN ACCORDANCE WITH THE REQUIREMENTS OF THE ABOVE MATERIAL SPECIFICATION	