




**MILL TEST CERTIFICATE**

**Customer:** PRODALAM S.A.  
**Commodity:** PRESTRESSED CONCRETE STRAND  
**Nominal Diameter:** 15.24 MM  
**Standard:** ASTM A416/A416M-15  
**Production Licence No:** XK 05-003-00098  
**Page No:** 8/12  
**Inspection Date:** Jun.22th,2023  
**Invoice No:** PCLPID2305C  
**Container No.** MSMU1510643

| Mark on Coil | Coil No.  | Dia MM | Section Area (mm <sup>2</sup> ) | Breaking Load (kN) | Tensile Strength MPA | 1%Extension Yield Load (kN) | Yield Strength MPA | Elongation (%) | Modules of Elasticity GPa | Length Approx. Meter | Coil Weight KGS |
|--------------|-----------|--------|---------------------------------|--------------------|----------------------|-----------------------------|--------------------|----------------|---------------------------|----------------------|-----------------|
| A8           | 2306144-2 | 15.22  | 140.25                          | 275.3              | 1966                 | 251.7                       | 1798               | 5.0            | 191.6                     | 2792                 | 3108            |
| A8           | 2306144-3 | 15.22  | 140.25                          | 275.8              | 1970                 | 252.6                       | 1804               | 5.2            | 198.8                     | 2819                 | 3138            |
| A8           | 2306146-2 | 15.28  | 141.27                          | 276.2              | 1973                 | 249.6                       | 1783               | 5.1            | 191.8                     | 2805                 | 3122            |
| A8           | 2306392-6 | 15.24  | 139.62                          | 273.0              | 1950                 | 252.6                       | 1804               | 5.1            | 198.1                     | 2928                 | 3258            |
| A8           | 2306149-5 | 15.25  | 140.51                          | 268.1              | 1915                 | 251.4                       | 1796               | 5.5            | 191.1                     | 2439                 | 2716            |
| A8           | 2306151-4 | 15.26  | 140.13                          | 273.3              | 1952                 | 251.3                       | 1795               | 5.6            | 194.8                     | 2733                 | 3042            |
| A8           | 2306546-1 | 15.23  | 140.25                          | 270.1              | 1929                 | 249.8                       | 1784               | 5.2            | 193.6                     | 2453                 | 2732            |
| A8           | 2306546-2 | 15.23  | 140.25                          | 271.4              | 1939                 | 251.0                       | 1793               | 5.0            | 196.3                     | 2453                 | 2732            |
| A8           | 2306546-3 | 15.23  | 140.25                          | 271.8              | 1941                 | 252.8                       | 1806               | 5.2            | 193.6                     | 2458                 | 2738            |



**Filled by :Zhangchunting**

**Approved by : Shenyingsiang**