



日钢营口中板有限公司  
RIZHAO STEEL YINGKOU MEDIUM PLATE CO.,LTD.  
辽宁省营口市老边区冶金街/115005  
Yejinstreet,Laobiandistrict,Yingkou,Liaoning,P.R.China/115005  
TEL:0417-3256081 FAX:0417-3256057 NO.:DT2101501/A

产品质量证明书  
INSPECTION CERTIFICATE



订货单位 PURCHASER	PRODALAM SA	产品名称 PRODUCT	普通碳素结构钢 General carbon structural steel		
收货单位 CONSIGNEE	PRODALAM SA	合同编号 CONTRACT NO.	YGCAZANN250292005/YKHK251054D-01		
技术标准/牌号 SPEC/GRADE	ASTM A36/A36M;ASTM A36	交货状态 DELIVERY CONDITION	热轧(AR)	签发日期 DATE OF ISSUE	20250415
		证明书编号 CERTIFICATE NO.	250415Z00719	是否保性能 GUARANTEE OR NOT	是 YES
车号 TRAIN NO.					

炉号 HEAT NO.	批号 LOT NO.	钢板号 PLATE NO.	规格 (MM) DIMENSION	数量 QTY	重量 WEIGHT kg	分析 区域 AA	化学成分 CHEMICAL ANALYSIS %														B 0A01	B 0A02	B 0A03	B 0A04	B 0B01	A 0C01	A 0C012	A 0C013	A 0C02
							C	Si	Mn	P	S	CEV	Cr	Mo	V	Ni	Cu	Nb	Ti	屈服 强度	抗 拉 强度	断后 伸 长 率	屈 强 比	弯 曲 试 验	冲 击 单 值 A	冲 击 单 值 B	冲 击 单 值 C	冲 击 均 值 Ave	
							$\times 10^{-3}$	$\times 10^{-3}$	$\times 10^{-3}$	$\times 10^{-4}$	$\times 10^{-4}$	$\times 10^{-2}$	$\times 10^{-3}$	$\times 10^{-4}$	$\times 10^{-4}$	MPa Rp0.2	MPa Rm	% B5		d=3a 180°	J	J	J						
25106739A	S54130125	S5413282201	6x2440x12000	1	1,379	L	132	179	820	250	79	28	35	20	1	70	12	20	20	323	447	28	0.72	OK	96	102	91	96	
25106739A	S54130125	S5413282301	6x2440x12000	1	1,379	L	132	179	820	250	79	28	35	20	1	70	12	20	20	323	447	28	0.72	OK	96	102	91	96	
25106739A	S54130125	S5413283101	6x2440x12000	1	1,379	L	132	179	820	250	79	28	35	20	1	70	12	20	20	323	447	28	0.72	OK	96	102	91	96	
25106739A	S54130125	S5413283201	6x2440x12000	1	1,379	L	132	179	820	250	79	28	35	20	1	70	12	20	20	323	447	28	0.72	OK	96	102	91	96	
25106739A	S54130125	S5413283301	6x2440x12000	1	1,379	L	132	179	820	250	79	28	35	20	1	70	12	20	20	323	447	28	0.72	OK	96	102	91	96	
25106739A	S54130125	S5413284101	6x2440x12000	1	1,379	L	132	179	820	250	79	28	35	20	1	70	12	20	20	323	447	28	0.72	OK	96	102	91	96	
25106739A	S54130125	S5413284201	6x2440x12000	1	1,379	L	132	179	820	250	79	28	35	20	1	70	12	20	20	323	447	28	0.72	OK	96	102	91	96	
25106739A	S54130125	S5413284301	6x2440x12000	1	1,379	L	132	179	820	250	79	28	35	20	1	70	12	20	20	323	447	28	0.72	OK	96	102	91	96	
25106739A	S54130126	S5413285101	6x2440x12000	1	1,379	L	132	179	820	250	79	28	35	20	1	70	12	20	20	311	441	27.5	0.71	OK	89	91	93	91	
25106739A	S54130126	S5413285201	6x2440x12000	1	1,379	L	132	179	820	250	79	28	35	20	1	70	12	20	20	311	441	27.5	0.71	OK	89	91	93	91	
25106739A	S54130126	S5413286101	6x2440x12000	1	1,379	L	132	179	820	250	79	28	35	20	1	70	12	20	20	311	441	27.5	0.71	OK	89	91	93	91	
25106739A	S54130126	S5413286201	6x2440x12000	1	1,379	L	132	179	820	250	79	28	35	20	1	70	12	20	20	311	441	27.5	0.71	OK	89	91	93	91	
合计(TOTAL):							12	16,548																					

注释 NOTES	L : 熔炼成分 SMELTING COMPOSITION 拉伸标距(GAUGE LENGTH) Lo=200 mm A0C冲击试验IMPACTTEST : 20 ,纵向LONGITUDINAL , 近表 CLOSE TO SURFACE , 尺寸SIZE10*5*55	B0A04=YIELD STRENGTH RATIO B0B01=BENDTEST A0C01=IMPACT TEST A A0C012=IMPACT TEST B A0C013=IMPACT TEST C A0C02=IMPACT AVERAGE
	B0A01=YIELD STRENGTH B0A02=TENSILE STRENGTH B0A03=PERCENTAGE ELONGATION AFTER FRACTURE	
According to EN 10204 3.1		

	本产品已按照标准要求进行制造和检验,其结果符合要求,目视及尺寸检验均符合标准要求,特此证明。 WE HEREBY CERTIFY THAT MATERIAL DESCRIBED HAS MANUFACTURED AND TESTED WITH SATISFACTORY RESULTS IN ACCORDANCE WITH THE REQUIREMENTS OF THE ABOVE MATERIAL SPECIFICATION Both BOTH VISUAL AND DIMENSIONAL INSPECTION MEET THE STANDARD REQUIREMENTS	冶金技术处处长 DIRECTOR OF METALLURGICAL DEPARTMENT