



日钢营口中板有限公司
RIZHAO STEEL YINGKOU MEDIUM PLATE CO.,LTD.
辽宁省营口市老边区裕金街115005
Yejinstreet,Laobiandistrict,Yingkou,Liaoning,P.R.China/115005
TEL:0417-3256081 FAX:0417-3256057 NO.:DT2101501/A

产品质量证明书
INSPECTION CERTIFICATE



订货单位 PURCHASER	CUMIC STEEL LIMITED		普通碳素结构钢 General carbon structural steel
收货单位 CONSIGNEE	CUMIC STEEL LIMITED		YGR1ZANN240783010
技术标准/牌号 SPEC/GRADE	ASTM A36/A36M-2019	热轧(AR)	签发日期 DATE OF ISSUE
车号 TRAINNO.			20240816 240816Z00011

炉号 HEATNO.	批号 LOTNO.	钢板号 PLATENO.	规格 (MM) DIMENSION	数量 QTY	重量 WEIGHT kg	分析 区域 AA	化学成分 CHEMICAL ANALYSIS %																	B								
							C	Si	Mn	P	S	Cr	Cr	Mo	V	Ni	Cu	Nb	Ti	B	B	B	B	B	A	A	A	A				
							1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24		
24114075A	S48150017	S4814503101	8x2440x12000	1	1,839	1.	127	147	856	180	74	29	66	30	1	210	7	20	30	299	437	27	0.68	OK	102	90	93	95				
24114075A	S48150017	S4814503201	8x2440x12000	1	1,839	1.	127	147	856	180	74	29	66	30	1	210	7	20	30	299	437	27	0.68	OK	102	90	93	95				
24114075A	S48150017	S4814503301	8x2440x12000	1	1,839	1.	127	147	856	180	74	29	66	30	1	210	7	20	30	299	437	27	0.68	OK	102	90	93	95				
24114075A	S48150017	S4814504101	8x2440x12000	1	1,839	1.	127	147	856	180	74	29	66	30	1	210	7	20	30	299	437	27	0.68	OK	102	90	93	95				
24114075A	S48150017	S4814504201	8x2440x12000	1	1,839	1.	127	147	856	180	74	29	66	30	1	210	7	20	30	299	437	27	0.68	OK	102	90	93	95				
24114075A	S48150017	S4814506201	8x2440x12000	1	1,839	1.	127	147	856	180	74	29	66	30	1	210	7	20	30	299	437	27	0.68	OK	102	90	93	95				
24114075A	S48150017	S4814506301	8x2440x12000	1	1,839	1.	127	147	856	180	74	29	66	30	1	210	7	20	30	299	437	27	0.68	OK	102	90	93	95				
24114075A	S48150017	S4814509101	8x2440x12000	1	1,839	1.	127	147	856	180	74	29	66	30	1	210	7	20	30	299	437	27	0.68	OK	102	90	93	95				
24114075A	S48150017	S4814509201	8x2440x12000	1	1,839	1.	127	147	856	180	74	29	66	30	1	210	7	20	30	299	437	27	0.68	OK	102	90	93	95				
24114075A	S48150017	S4814509301	8x2440x12000	1	1,839	1.	127	147	856	180	74	29	66	30	1	210	7	20	30	299	437	27	0.68	OK	102	90	93	95				
24114075A	S48150017	S4814510101	8x2440x12000	1	1,839	1.	127	147	856	180	74	29	66	30	1	210	7	20	30	299	437	27	0.68	OK	102	90	93	95				
24114075A	S48150017	S4814510201	8x2440x12000	1	1,839	1.	127	147	856	180	74	29	66	30	1	210	7	20	30	299	437	27	0.68	OK	102	90	93	95				
				合计(TOTAL):	12	22,068																										

注释 NOTES	L: 熔炼成分 SMELTING COMPOSITION 拉伸标距(GAUGE LENGTH) Lo=200 mm A0C冲击试验IMPACT TEST: 20 C, 纵向LONGITUDINAL, 近表 CLOSE TO SURFACE, 尺寸SIZE10*5*55 B0A01=YIELD STRENGTH B0A02=TENSILE STRENGTH B0A03=PERCENTAGE ELONGATION AFTER FRACTURE	B0A04=YIELD STRENGTH RATIO B0B01=BEND TEST A0C01=IMPACT TEST A A0C012=IMPACT TEST B A0C013=IMPACT TEST C A0C02=IMPACT AVERAGE
	According to EN 10204 3.1 本产品已按照标准要求进行制造和检验, 其结果符合要求, 特此证明。 WE HEREBY CERTIFY THAT MATERIAL DESCRIBED HAS MANUFACTURED AND TESTED WITH SATISFACTORY RESULTS IN ACCORDANCE WITH THE REQUIREMENTS OF THE ABOVE MATERIAL SPECIFICATION	



冶金技术处处长
DIRECTOR OF
METALLURGICAL
DEPARTMENT
殷新刚