



鞍钢股份有限公司  
Angang Steel Company Limited

# 产品质量证明书

## INSPECTION CERTIFICATE



中国鞍山市铁东区团结街42号 邮编 114002  
No.42 Tuanjie Street Tiedong District 114002  
Anshan. P. R. China  
Tel 0086-8008900858 Fax 0086-0412-6728486

制造厂: 鞍钢股份有限公司鲅鱼圈中厚板厂3800线  
Manufacturer: Bayuquan Heavy Plate Plant 3800 Line of AnSteel

正页 第 1 页, 共 2 页

订货单位 Buyer	鞍钢集团国际经济贸易有限公司	产品名称 Product	中厚板 Medium and Heavy plate	合同编号 Contract No.	C24B0178001	证明书编号 Certificate No.	C02411160022
收货单位 Consignee	鞍钢股份有限公司 (外贸出口)	客户名称 Customer	鞍钢集团国际经济贸易有限公司	交货状态 Delivery Condition	热轧		
标准 Specification	Q/ASB 146.2	许可证编号 License No.					
钢牌号 Grade	A36	发货日期 Date of Delivery	20241116	计量方式 Weight Mode	理论重量 Theory		

序号 No.	物料号 Pack No.	熔炼号 Heat No.	规格(mm) Dimensions mm.	重量(kg) Weight	件数 Pcs.	化学成分 Chemical Composition (%)										冷弯Bend		
						C		Si		Mn		P		S		试样描述 *2	α=	试批号 Batch No.
						10 -2	10 -2	10 -2	10 -3	10 -3	10 -3	10 -3						
1	S4B141441000	24BD6718	6*2000*12000	1130	1	0	14	15	68	11	14							
2	S4B141451000	24BD6718	6*2000*12000	1130	1	0	14	15	68	11	14							
3	S4B141452000	24BD6718	6*2000*12000	1130	1	0	14	15	68	11	14							
4	S4B141461000	24BD6718	6*2000*12000	1130	1	0	14	15	68	11	14							
5	S4B141462000	24BD6718	6*2000*12000	1130	1	0	14	15	68	11	14							
6	S4B141463000	24BD6718	6*2000*12000	1130	1	0	14	15	68	11	14							
7	S4B141473000	24BD6718	6*2000*12000	1130	1	0	14	15	68	11	14							
8	S4B141511000	24BD6718	6*2000*12000	1130	1	0	14	15	68	11	14							
合计Total				9040	8													

序号 No.	物料号 Pack No.	拉伸Tension					试批号 Batch No.	试样描述 p&d *2	温度 C	冲击Charpy				试批号 Batch No.	试样描述 p&d *2	硬度Hardness				厚度方向性能(Z)				试批号 Batch No.			
		屈服 Y.S. MPa	抗拉 T.S. MPa	伸长率 El %	收缩率 Sh %	屈服比 Y.S./ T.S. %				J						1	2	3	Ave	1	2	3	Ave				
										纤维率 SA %																	
1	S4B141441000	T141	288	420	45		4P1171993800																				
2	S4B141451000	T141	288	420	45		4P1171993800																				
3	S4B141452000	T141	288	420	45		4P1171993800																				
4	S4B141461000	T141	288	420	45		4P1171993800																				
5	S4B141462000	T141	288	420	45		4P1171993800																				
6	S4B141463000	T141	288	420	45		4P1171993800																				
7	S4B141473000	T141	288	420	45		4P1171993800																				
8	S4B141511000	T141	288	420	45		4P1171993800																				

探伤NDT	标准Standard:	级别Class:	结果Result:
-------	-------------	----------	-----------

注释 Notes: \*1化学成分: 0熔炼分析 Heat Analysis, 1.产品分析Product Analysis; \*2试样描述: 大样位置-T.头部Head, B.尾部Tail + 试验方向-1.横向 Transverse, 2.纵向Longitudinal, 3.Z向 + 取样位置- 1.板宽1/4, 2.板宽1/2, 3.板边; 4.厚度方向位置-1.原厚, 2.表面下2mm, 3.厚度1/4, 4.厚度1/2, 5.保留一个轧制面, 6.表面下小于2mm, 7.厚度1/3, 8.厚度之半 + 试样热处理前/后区分-0.交货态Delivery Condition, 1.模拟焊后 PWHT, 2.最大模拟焊后热处理 Max PWHT, 3.最大模拟焊后热处理 Max PWHT.

备注 Remarks: 上述元素仅列出参与复合公式的有意添加元素, 但复合元素结果是严格按公式计算得出。The above elements only list the intentionally added elements that participate in the composite formula, but the composite element results are strictly calculated according to the formula.

说明 Description: 本产品已按上述标准制造和检验, 其结果符合要求。特此证明。贵方如查询有问题, 请与我公司联系。We hereby certify that material described herein has been manufactured and tested with satisfactory results in accordance with requirements of the above material specification. If you have any questions, please contact our company.



质量保证负责人  
Quality Manager  
CHINA

监埋  
Surveyor