日钢营口中板有限公司
RIZHAO STEEL YINGKOU MEDIUM PLATE CO.,LTD.
辽宁省营口市老边区冶金街/115005
Yejinstreet,Laobiandistrict,Yingkou,Liaoning,P.R.China/115005
TEL:0417-3256081 FAX:0417-3256057 NO.:DT2101501/A

产品质量证明书
INSPECTION CERTIFICATE

订货单位 PURCHASER	SHARPMAX INTERNATIONAL (HONGKONG) CO., LIMITED	产品名称 PRODUCT	普通碳素结构钢 General carbon structural steel		
收货单位 CONSIGNEE	SHARPMAX INTERNATIONAL (HONGKONG) CO., LIMITED	合同编号 CONTRACT NO.	YGR1ZANN240583001-02		
技术标准/牌号 SPEC/GRADE	ASTM A36/A36M-2019 ; ASTM A36	交货状态 DELIVERY CONDITION	热轧(AR)	签发日期 DATE OF ISSUE	20240601
		证明书编号 CERTIFICATE NO.	240601Z00123		
车 号 TRAIN NO.					

炉号 HEAT NO.	批号 LOT NO.	钢板号 PLATE NO.	规格 (MM) DIMENSION	数量 QTY	重量 WEIGHT kg	分析区域 AA	化学成分 CHEMICAL ANALYSIS % C ×10⁻³	Si ×10⁻³	Mn ×10⁻³	P ×10⁻⁴	S ×10⁻⁴	Cr ×10⁻³	Ni ×10⁻⁴	Cu ×10⁻³	Mo ×10⁻⁴	V ×10⁻³	Ti ×10⁻⁴	Nb ×10⁻⁴	CEV ×10⁻²	A0A01 屈服强度 MPa Rp0.2	A0A02 抗拉强度 MPa Rm	A0A03 断后伸长率 % B5
24108007D	2457350	24E8402003	20x2440x12000	1	4,597	L	133	226	858	250	35	102	320	6	10	1	150	30	30	293	449	26.5
24108007D	2457350	24E8402004	20x2440x12000	1	4,597	L	133	226	858	250	35	102	320	6	10	1	150	30	30	293	449	26.5
			合计(TOTAL)：	2	9,194																	

注释 NOTES

L：熔炼成分 SMELTING COMPOSITION
拉伸标距(GAUGE LENGTH) Lo=200 mm
A0A01=YIELD STRENGTH
A0A02=TENSILE STRENGTH
A0A03=PRECENTAGE ELONGATION AFTER FRACTURE

According to EN 10204 3.1

野牛

本产品已按照标准要求进行制造和检验，其结果符合要求，特此证明。
WE HEREBY CERTIFY THAT MATERIAL DESCRIBED HAS MANUFACTURED AND TESTED WITH SATISFACTORY RESULTS IN ACCORDANCE WITH THE REQUIREMENTS OF THE ABOVE MATERIAL SPECIFICATION

冶金技术处处长
DIRECTOR OF METALLURGICAL DEPARTMENT