日钢营口中板有限公司
RIZHAO STEEL YINGKOU MEDIUM PLATE CO.,LTD.
辽宁省营口市老边区冶金街/115005
Yejinstreet,Laobiandistrict,Yingkou,Liaoning,P.R.China/115005
TEL:0417-3256081 FAX:0417-3256057 NO.:DT2101501/A

产品质量证明书
INSPECTION CERTIFICATE

订货单位 PURCHASER	PRODALAM S A	产品名称 PRODUCT	船用钢板 Hull Steel plate		
收货单位 CONSIGNEE	PRODALAM S A	合同编号 CONTRACT NO.	YGCAZANN250783005/YKSG253344D-02		
技术标准/牌号 SPEC/GRADE	LR RULES;LRB	交货状态 DELIVERY CONDITION	正火轧制(NR)	签发日期 DATE OF ISSUE	20250826
		证明书编号 CERTIFICATE NO.	250825Z00538	控制号 CONTROL NUMBER	DLN2501863
车 号 TRAIN NO.		船号 HULL NO.		是否保性能 GUARANTEE OR NOT	是 YES

炉号 HEAT NO.	批号 LOT NO.	钢板号 PLATE NO.	分段号 SECTION NO.	规格 (MM) DIMENSION	数量 QTY	重量 WEIGHT kg	化学成分 CHEMICAL ANALYSIS % C	Si	Mn	P	S	Als	Ti	Nb	Ni	Cr	Cu	Mo	CeqA	B0A01 屈服强度 MPa ReH	B0A02 抗拉强度 MPa Rm	B0A03 断后伸长率 % B1	A0C01 冲击单值 A J	A0C012 冲击单值 B J	A0C013 冲击单值 C J	A0C02 冲击均值 Ave J
							$\times10^{-3}$	$\times10^{-2}$	$\times10^{-3}$	$\times10^{-3}$	$\times10^{-3}$	$\times10^{-3}$	$\times10^{-4}$	$\times10^{-4}$	$\times10^{-4}$	$\times10^{-3}$	$\times10^{-3}$	$\times10^{-4}$	$\times10^{-3}$							
25116158A	S58230242	S5823398201		6x2440x12000	1	1,379	152	20	770	24	5	31	110	20	180	40	11	20	280	367	473	36.5	85	88	85	86
25116158A	S58230242	S5823398301		6x2440x12000	1	1,379	152	20	770	24	5	31	110	20	180	40	11	20	280	367	473	36.5	85	88	85	86
25116158A	S58230242	S5823399101		6x2440x12000	1	1,379	152	20	770	24	5	31	110	20	180	40	11	20	280	367	473	36.5	85	88	85	86
25116158A	S58230242	S5823399201		6x2440x12000	1	1,379	152	20	770	24	5	31	110	20	180	40	11	20	280	367	473	36.5	85	88	85	86
25116158A	S58230242	S5823399301		6x2440x12000	1	1,379	152	20	770	24	5	31	110	20	180	40	11	20	280	367	473	36.5	85	88	85	86
25116158A	S58230242	S5823400101		6x2440x12000	1	1,379	152	20	770	24	5	31	110	20	180	40	11	20	280	367	473	36.5	85	88	85	86
25116158A	S58230242	S5823400201		6x2440x12000	1	1,379	152	20	770	24	5	31	110	20	180	40	11	20	280	367	473	36.5	85	88	85	86
25116158A	S58230242	S5823400301		6x2440x12000	1	1,379	152	20	770	24	5	31	110	20	180	40	11	20	280	367	473	36.5	85	88	85	86
25116158A	S58230242	S5823401101		6x2440x12000	1	1,379	152	20	770	24	5	31	110	20	180	40	11	20	280	367	473	36.5	85	88	85	86
25116158A	S58230242	S5823401201		6x2440x12000	1	1,379	152	20	770	24	5	31	110	20	180	40	11	20	280	367	473	36.5	85	88	85	86
25116158A	S58230242	S5823401301		6x2440x12000	1	1,379	152	20	770	24	5	31	110	20	180	40	11	20	280	367	473	36.5	85	88	85	86
				合计(TOTAL)：	11	15,169																				

注释 NOTES

L：熔炼成分 SMELTING COMPOSITION
拉伸标距(GAUGE LENGTH) Lo=5.65√S0 mm
A0C冲击试验IMPACTTEST：0°C，纵向LONGITUDINAL，近表 CLOSE TO SURFACE，尺寸SIZE10*5*55
CeqA=C+Mn/6
B0A01=YIELD STRENGTH
B0A02=TENSILE STRENGTH

B0A03=PRECENTAGE ELONGATION AFTER FRACTURE
A0C01=IMPACT TEST A
A0C012=IMPACT TEST B
A0C013=IMPACT TEST C
A0C02=IMPACT AVERAGE

According to EN 10204 3.2

野牛

我们在此证明此材料采用已被认可的方法制造，并且经检验符合LR船级社规范的要求。
We hereby certify that the material has been made by an approved process and satisfactorily tested in accordance with the Rules of Lloyd ' s Register.

冶金技术处处长 DIRECTOROF METALLURGICAL DEPARTMENT

段彩刚

验船师 SURVEYOR

S.J. He
Dalian Office
Lloyd's Register Classification Society China Co Ltd